MIL-T-52504B(ME)
25 September 1980
SUPERSEDING
MIL-T-52504A(ME)
20 November 1975

MILITARY SPECIFICATION

TRAINING AID, PANEL, GRID REFERENCE BOX

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a grid reference box training aid panel displaying instructional data.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
LLL-B-810	- Building Board (Hardboard) Hard Pressed, Vegetable Fiber.

o FSC 6910

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:21Z
Check the source to verify that this is the current version before use.

PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-B-640	- Boxes, Fiberboard, Corrugated, Triple-Wall.

MILITARY

MIL-P-116	- Preservation-Packaging, Methods of.
MIL-T-704	- Treatment and Painting of Materiel.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-1188	- Commercial Packaging of Supplies and Equipment.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Description. The training aid shall be a panel printed and blocked as shown on Figure 1 and as specified herein.

3.2 Material. Material shall be as specified herein. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification (see 6.3).

3.3 Construction.

3.3.1 Building board. Building board shall conform to LLL-B-810, Type I, Surface 2, Finish C, Design a, size 1/8 inch thick.

3.3.1.1 Panel size. The panel shall be 36.00 inches wide x 48.00 inches high.

3.3.2 Characters. All characters, except those specially dimensioned on Figure 1, shall be 0.50 inch high, and the lines of lettering shall be spaced 0.50 inch apart.

Source: https://assist.dla.mil -- Downloaded: 20260-22T21:21Z
Check the source to verify that this is the current version before use.

3.4 Treatment and painting. The portions of the training aid normally painted shall be cleaned, treated, and painted in accordance with MIL-T-704, Type A. The panel background shall be painted white. Lines and characters shall be painted black.

3.5 Workmanship. Particular attention shall be given to neatness and legibility of all markings. Panels shall have smooth edges free from spots, blisters, tears, scuffs, and checks.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Material inspection. The contractor is responsible for insuring that materials used are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Quality conformance inspection (see 4.3).
(b) Inspection of packaging (see 4.5).

4.3 Quality conformance inspection.

4.3.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined as specified in 4.4. AQL shall be 2.5 percent defective.

4.4 Inspection procedure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:21Z
Check the source to verify that this is the current version before use.

4.4.1 Examination. The indicator shall be examined as specified herein for the following major defects:

101. Dimensions not as specified.
102. Materials not as specified.
103. Size of characters not as specified.
104. Treatment and painting not as specified.
105. Marking missing, incomplete, or illegible.
106. Workmanship not as specified.

4.5 Inspection of packaging.

4.5.1 Quality conformance inspection of pack.

4.5.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.5.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.5.1.3 Examination. Samples selected in accordance with 4.5.1.2 shall be examined for the following major defects. AQL shall be 2.5 percent defective.

107. Materials, methods, and containers not as specified for Level A or Level B. Each incorrect material, method, or container shall constitute one defect.
108. Panel bent for Level A or Commercial.
109. Consolidation not as specified for Level A.
110. Gross weight of size exceeds the limitations of the box specification for Level A or Level B.
111. Strapping not as specified for Level A.
112. Marking missing, illegible, incorrect, or incomplete.

5. PACKAGING

5.1 Preservation. Preservation shall be Level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each indicator shall be preserved in accordance with MIL-P-116, Method IC-1 or IC-3. Bending of the panel shall not be permitted.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:21Z
Check the source to verify that this is the current version before use.

5.1.1.1 Consolidation. The preserved indicators shall be consolidated together in a close-fitting box conforming to PPP-B-636, W5c, style optional, in quantities not to exceed the weight limitation of the box specification.

5.1.2 Commercial. Each panel shall be preserved in accordance with MIL-STD-1188. Bending of the panel shall not be permitted.

5.2 Packing. Packing shall be Level A, Level B or Commercial as specified (see 6.2).

5.2.1 Level A. Panels preserved as specified in 5.1 shall be packed in a close-fitting box conforming to PPP-B-601, Overseas Type, Grade B, style optional, in quantities not to exceed the weight limitation of the box. Strapping shall conform to QQ-S-781, Class 1, Type I or IV, size as applicable; and, unless otherwise specified herein, shall be Finish B. When specified (see 6.2), strapping shall be Finish A.

5.2.2 Level B. Panels, preserved as specified in 5.1 shall be packed in close-fitting boxes conforming to PPP-B-636, V3c, style optional or PPP-B-640, Class 2, style optional. The gross weight or size shall not exceed the limitation of the box specification.

5.2.3 Commercial. Panels preserved as specified in 5.1 shall be packed in accordance with MIL-STD-1188.

5.3 Marking.

5.3.1 Military packaging. Marking shall be in accordance with MIL-STD-129.

5.3.2 Commercial packaging. Marking shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The panel is a component of a map reading set and is used as an aid in teaching the location of grid reference boxes on military maps.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number, and date of this specification.
(b) Degree of preservation and degree of packing required (see 5.1 and 5.2).
(c) When Finish A strapping shall be required (see 5.2.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:21Z
Check the source to verify that this is the current version before use.

6.3 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of this specification (see 3.2).


Custodian:
Army - ME

Preparing activity:
Army - ME


Project 6910-A393

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:21Z
Check the source to verify that this is the current version before use.

500,000 YARD (SMALL LETTER) AND 100,000 YARD (LARGE LETTER) SQUARE IDENTIFICATIONS



IGNORE THE SMALLER FIGURES OF ANY GRID NUMBER: THESE ARE FOR FINDING THE FULL COORDINATES. USE ONLY THE LARGER FIGURE OF THE GRID NUMBER; EXAMPLE:



TO GIVE A STANDARD REFERENCE ON THIS SHEET TO THE NEAREST 1000 YARDS

SAMPLE POINT: CHURCH

5/8"

1. LOCATE FIRST VERTICAL GRID LINE TO LEFT OF POINT AND READ LARGE FIGURES LABELING THE LINE EITHER IN THE TOP OR BOTTOM MARGIN, OR ON THE LINE ITSELF: 22
   ESTIMATE TENTHS FROM GRID LINE TO POINT: 5
2. LOCATE FIRST HORIZONTAL GRID LINE BELOW POINT AND READ LARGE FIGURES LABELING THE LINE EITHER IN THE LEFT OR RIGHT MARGIN, OR THE LINE ITSELF: 18
   ESTIMATE TENTHS FROM GRID LINE TO POINT: 4

5/8"

SAMPLE REFERENCE: 225184

IF REPORTING BEYOND 100,000 YARDS OR IF SHEET BEARS AN OVERLAPPING GRID, PREFIX WITH 100,000 YARD SQUARE IDENTIFICATION, AS: P225184

IF REPORTING BEYOND 500,000 YARDS PREFIX WITH 500,000 YARD SQUARE IDENTIFICATION, AS: TP 225184

FIGURE 1. Training aid panel.

X-3038

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T21:21Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
USA Mobility Equipment R&D Command
ATTN: DRDME-DES
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:21Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-T-52504B(ME) Training Aid, Panel, Grid Reference Box

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:21Z
Check the source to verify that this is the current version before use.