[METRIC]
A-A-2081D
November 3, 1993
SUPERSEDING
A-A-2081C
December 10, 1991

COMMERCIAL ITEM DESCRIPTION

CREDENZA (OFFICE, TRADITIONAL STYLE)

The General Services Administration has authorized the use of this Commercial Item Description in preference to Interim Federal Specification AA-0-00240

Scope. This Commercial Item Description covers credenzas which are a part of a traditional line of metal office furniture.

Salient characteristics. These characteristics concisely describe the essential physical and functional/performance features of the commercially available items

Design The credenzas shall be traditional style designed for heavy duty, commercial office use.

Styles.

Style A - Double sliding or hinged door section with adjustable shelf Overall dimension 735 mm W X 455 mm D X 750 mm H

Style B - Two pedestal sections with a double sliding or hinged door section between. Each pedestal section shall have 1 storage drawer over a file drawer and the sliding or hinged door section shall have an adjustable shelf. Minimum of one lock located on either a file drawer, sliding door, or top. Overall dimensions 1500 mm W X 455 mm D X 750 mm H.

Note: 1. Height shall be measured with glides fully retracted.
2. Unless otherwise specified, dimensions shall have a tolerance of ± 25 mm.

FSC 7110

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

3. For Style A, the plus tolerance on the width dimension shall be 210 mm For Style B, the plus tolerance on the width dimension shall be 110 mm

General construction.

Top Steel construction reinforced with formations extending the full length of the top for maximum rigidity Top edges shall have a binding strip. The top shall be covered with a decorative, high pressure, laminated plastic. Alternatively, the top may be particleboard with a high pressure, laminated plastic face and backing sheet to produce a balanced sandwich construction A protective edging shall be used around the entire top and the color shall be gray, similar to the gray enamel finish (self-edging, not allowed). The white leather laminated plastic shall match GSA Standard Sample No FSS-L-01001. Alternatively, the manufacturer may provide his equivalent commercial, white leather laminated plastic, subject to contracting officer approval Overall top thickness shall be 25 mm, minimum.

Locks. The locks shall be of the disk or pin tumbler type, having not less than four disks or pin tumblers, and shall be operated by a grooved key. The locks shall have not less than 125 key changes. No one key shall open more than the lock on one unit up to a minimum of 125 units consecutively produced. All locks on the credenza shall be keyed alike Two keys shall be furnished with each credenza.

Drawers. The drawers shall have stops to prevent accidental removal, but allow removal without the use of tools. The minimum inside clear dimensions shall be as specified in Table I. File, and storage drawers shall be welded construction with double wall drawer fronts. The storage drawer body shall be constructed to accommodate partitions. Each storage drawer shall have a minimum of one partition. The storage drawers shall be suspended on telescoping ball bearing slides, rollers, or nylon glides. The slides, glides, or rollers shall promote smooth quiet operation and prevent metal to metal contact between suspension members. The file drawers shall be on full progressive suspensions or telescoping ball bearing slides. The file drawer shall have a spring-activated follower block which operates smoothly. Bumpers shall cushion drawer stops in both

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

closed and extended positions.

Drawer and door pulls. The finish shall be polished, chrome plate on steel, die-cast zinc, brass or bronze; polished stainless steel; or polished anodized aluminum

Adjustable shelf The shelf shall be formed on all four sides. Shelf adjusting devices shall not be visible on the exterior of case. Shelf supports shall be provided. Minimum dimensions shall be 620 mm W X 380 mm D.

TABLE I Drawer dimensions.

Drawer type	Minimum inside clear dimension		
	Width	Height	Depth
Storage drawers	288 mm	130 mm	280 mm
File drawers	300 mm	250 mm	350 mm

Legs . Legs shall be attached to the under side of the credenza pedestal or end panel. The legs shall be equipped with adjustable glides

Finish. The finish shall be baked enamel. The color shall match Fed. Std No 595 gray (26134). Alternatively, the manufacturer may provide his equivalent commercial, gray, baked enamel finish, subject to contracting officer approval

Identification label The label shall have the contractor's name or trademark, contract number, National Stock Number (if specified), and month, and year of manufacture legible marked with permanent dark ink The label shall be applied to the back of the credenza and shall not be removable by hand without defacement after being affixed for 4 hours

Workmanship. The workmanship shall be of the quality to produce finished credenzas acceptable in appearance, function and serviceability and prevent potential hazard to personnel or their clothing.

Quality Assurance Provisions. Unless otherwise specified in the contract or purchase order, the contractor is responsible for

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

the performance of all inspection requirements specified herein Sampling for inspection shall be performed in accordance with MIL-STD-105, unless an equal or better plan is approved by the contracting officer or his/her representative A lot shall consist of units of one style and color. The sample shall be one each Inspection levels and AQL's shall be as follows.

For fit, finish and all other workmanship - Level II, AQL 6.5 defects per hundred units.

For packaging, packing and marking - Level S-2, AQL 4 0 percent defective

Any failure to meet the dimensions, color, identification label or performance requirements shall cause rejection of the lot

Performance

ANSI/BIFMA Each credenza shall comply with the requirements of BIFMA Desk Products Standard X5.5-1989, with the following exceptions.

Exceptions to BIFMA American National Standard X5 5-1989 Sections 13.2.2, 13.2.3, 14, 15, 16, 17, 18, and 19 are not applicable.

Level test for top This test unit shall be located on a flat surface. Place a steel straight-edge on edge, diagonally (corner to corner) across the top The length of the straight-edge shall be greater than the diagonal length of the top. There shall be no gap between the straight-edge and top greater than 3 mm at any point along the diagonal length of the top This test shall be performed along both diagonals of the top before and after performing the top loading test specified in BIFMA

Regulatory requirement. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:19Z
Check the source to verify that this is the current version before use.

Standards The issues of ANSI/BIFMA X5.5, MIL-STD-105, and Fed Std. 595 in effect on the date of the solicitation shall be used to determine compliance with the stated requirements.

Notes

Ordering options Purchasers should specify style.

Plastic laminate panel. A sample of the decorative plastic laminate sheet is available from the General Services Administration, Federal Supply Service, National Furniture Center, Engineering Division, Washington, DC 20406.

Color panel A sample of the baked enamel finish referenced in Fed. Std No. 595 is available from the General Services Administration, Business Center, Federal Supply Service, Washington, DC 20407 or the Business Service Center in the nearest General Services Administration Regional Offices.

Federal standards. Federal Standard No. 595 is available from the General Services Administration Business Service Centers in Boston, MA; New York, NY; Philadelphia, PA, Washington, DC, Atlanta, GA; Chicago, IL; Kansas City, MO; Fort Worth, TX, Houston, TX; Denver, CO; San Francisco, CA, Los Angeles, CA; and Seattle, WA

ANSI/BIFMA standard Copies of the ANSI/BIFMA Standard X5.5 are available from the American National Standards Institute, Inc , 1430 Broadway, New York, NY 10018.

MIL-STD-105 Copies of MIL-STD-105 are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:19Z
Check the source to verify that this is the current version before use.