COMMERCIAL ITEM DESCRIPTION

SAW, BUTCHER'S; AND BLADE, BUTCHER'S HANDSAW

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers two sizes of butcher's handsaws and related blades.

Salient characteristics:

The handsaws and blades shall be available in the following sizes:

Item I - Handsaw complete with blade
Size 1 - 14 inches blade length
Size 2 - 24 inches blade length

Item II - Blade only
Size 1 - 14 inches cutting edge length
Size 2 - 24 inches cutting edge length

Part Numbering System for Commercial Item Description A-A-2574

Example: AA2574 - I 1 (AA2574-I1)
1 — Size, 1 - 14 inch blade length
I — Item, I - Handsaw complete with blade

The complete handsaw shall consist of an open steel frame with a handle and a removable blade which has a pin in each end. A device for applying tension to the blade shall also be provided and shall be a trigger type. The hand saw and blade shall conform to the dimensions shown in table I and II, respectively. The frame thickness shall be a minimum of 1/4 inch.

TABLE I. Handsaw dimensions

Size	O/A Length +/- 1 inch	Blade length (pin to pin)	Minimum depth from teeth of blade to inside edge of frame	Cross Section width of frame (minimum)
1	21	14	4	3/4
2	31	24	4-3/8	3/4

Note: All dimensions are in inches.

The handsaw frame shall be nonadjustable and fabricated from steel bar stock. The frame shall be capable of passing the compressive load test with no permanent set or failure of any component.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

TABLE II. Blade Dimensions

Size	Pin-to-pin length +/- 1/8	Minimum blade width	Teeth per inch	Minimum blade thickness	Center of pin to blade end
1	14	1/2	10	0.025	1/4
2	24	1/2	10	0.025	1/4

Note: All dimensions are in inches.

The handle shall be made from high impact plastic which complies with FDA regulations covering polymers for use in contact with food for human consumption as stated in 21 CFR 177. Handle edges shall be rounded. The handle shall be secured to the frame with a minimum of three oval head screws. The undersurface of the screw heads shall be flush with the surface of the handle.

The blade shall be made of steel and heat treated to the following specification:

Tooth area - Rockwell C 65-70
Body of the blade - Rockwell C 43-50

The body of the blade is that area below the tooth gullet. The overall set of the teeth shall be 0.033 to 0.038 inch. The teeth of the blade shall be evenly spaced and of uniform height.

The blade holding device shall prevent rotation or twisting of the blade and shall be capable of applying a minimum tension of 20 pounds to the blade when tested as specified. The blade holding device shall be attached to the frame at the handle end of the handsaw. The blade bearing surfaces shall be smoothly finished (free from burrs, rough edges and scratches) and provision shall be made to prevent the blade holding devices from falling out of the frame in the event of blade breakage.

All carbon steel frames shall be plated. Cadmium plating shall be used. Blades shall be coated with white oil.

Each handsaw frame shall be permanently marked with manufacturer's name or trademark.

Workmanship. The handsaw and blade shall be free from burrs, rough or sharp edges or other defects which affect appearance, safety or serviceability.

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:24Z
Check the source to verify that this is the current version before use.

Quality Assurance:

Responsibility for inspection: Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. Inspection records of the examinations or tests shall be kept complete and available to the Government as specified in the contract or purchase order. The Government reserves the right to perform any of the inspections set forth in the Commercial Item Description where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Visual inspection. The visual examination of the handsaw and blade shall be for construction and workmanship defects in accordance with Table III. The inspection level shall be level II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects, expressed in terms of defects per hundred units.

Table III. Classification of Defects

Examine	Defect	Major	Minor
Finish	Frame not plated	X	
Construction and Workmanship	Frame not one-piece	X	
	Burrs, rough or sharp edges, or corners on frame	X	
	Handle not high impact plastic	X	
	Handle edges not rounded		X
	Handle not secured to frame with at least three screws	X	
	Screws not oval head		X
	Undersurface of screw not flush with surface of handle	X	
	Blade has no pins	X	
	Rear blade holding device not specified type	X	
	Blade holding devices not integral part of frame or not permanently attached to frame or combination of both	X	
	Blade bearing surfaces of blade holding devices not flat		X
Marking	Missing, incomplete, illegible		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

Dimensional examination. The handsaw and blade shall be examined for defects in dimensions. Any dimension not within specified requirements shall be classified a defect. The inspection level shall be S-2 with an AQL of 4.0, expressed in terms of defects per hundred units.

End product testing. The handsaw and blade, as applicable, shall be tested for load, blade hardness and tension. The inspection level for each test shall be S-4 with an AQL of 4.0, expressed in terms of defects per hundred units.

Load test. The distance between the blade holding devices shall be measured and recorded while the frame is subjected to a 20 pound compressive load applied between the blade holding devices. The load test shall then proceed as follows:

(a) The compressive load in the frame shall then be increased from 20 to 100 pounds and held while the distance between the bladeholding devices is measured and compared to the original measurement. Any contraction over 1/4 inch or parts breakage shall constitute failure of this test.

(b) The compressive load in the frame shall then be decreased from 100 to 20 pounds and held while the distance between the bladeholding devices is measured and compared to the original measurement. Any permanent set or parts breakage shall constitute failure of this test.

Blade hardness test. Blades shall be tested for hardness in accordance with ASTM E18, Standard Test Methods for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials and ASTM E384, Standard Test Method for Microhardness of Materials, to determine compliance. The hardness of the tooth area shall be measured 0.004 inch down from the tooth tip. The measurement shall be checked on microhardness Vickers Scale and converted to Rockwell C Scale. The hardness of the body of the blade shall be measured at the midpoint between the bottom of the tooth gullet and the back (plain) edge of the blade. Nonconformance shall constitute failure of this test.

Tension test. The tension applied by the rear bladeholding device shall be measured to determine compliance with the minimum tension requirement. This measurement shall be obtained by attaching a scale or other suitable measuring device between the blade holding devices and tightening the rear blade holding device. Noncompliance with tension requirements shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.

Inspection for preparation and delivery. An inspection shall be made to determine whether the packaging, packing, and marking comply with the requirements of the contract or purchase order. Examination for defects shall be in accordance with Table IV. For examination of interior packaging, the sample unit shall be one shipping container fully prepared for delivery. Sampling shall be in accordance with MIL-STD-105. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 with an AQL of 4.0 defects per hundred units.

Table IV
Preparation for delivery defects.

Examine	Defects
Markings	Omitted; incorrect; illegible; improper size, location, sequence, or method of application.
Material	Any component missing, damaged, or not conforming to applicable requirements stated herein.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, or distortion of container.
Contents	Quantity of container is more or less than required. Gross weight exceeds requirements of the box specification.

Regulatory requirements: In accordance with Section 23.403 of the Federal Acquisition Regulations, the Government°s policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers° employees to undue hazards from the recovered materials.

Preservation, packaging, packing and marking (Civil Agencies): Preservation, packaging, packing, and marking shall be as specified in the contract or purchase order.

Packaging (DOD): Packaging shall be in accordance with ASTM Standard D 3951.

Notes: Purchaser should specify item number and size.

Copies of military standards may be obtained from the Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:24Z
Check the source to verify that this is the current version before use.

Applications for copies of American Society for Testing and Materials (ASTM) Standards should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

The standards referenced in this document shall be the issues in effect on the date of the invitation for bids or request for quotation and shall be used to determine compliance with these requirements. In the event that there is a conflict between this document and a standard referenced herein, this document shall take precedence.

Supersession data: The items covered by this commercial item description replaces the identical items previously covered by GGG-S-60C with the following exceptions: Item I, Size 2 replaces Item I, Size 4; Item II, Size 2, replaces Item II, Size 4.

MILITARY INTERESTS:

Military Coordinating Activity:

Army - GL

Custodians:

Army - GL
Navy - SA
Air Force - 99

Review Activities:

Army - MD, TS

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:24Z
Check the source to verify that this is the current version before use.