[Metric]
A-A-2993
March 25, 1996

COMMERCIAL ITEM DESCRIPTION
TRAYS, REPOSITIONAL NOTE PAD

The General Services Administration has authorized the use of this commercial item description by all federal agencies.

1. Scope: This Commercial Item Description covers desk top repositional note pad trays designed to hold repositional note pads described in Commercial Item Description A-A-2546 Pad, Writing Paper (Repositional).

2. Salient Characteristics:

2.1 The note trays shall be made of high-impact plastic and shall have a weighted, non-slip bottom that doesn't mar the desk and shall be provided in colors of either black or putty.

2.2 The note trays shall have the following dimensional requirements: 152.4 mm ± 25.4 mm x 152.4 mm ± 25.4 mm (6.0 inch ± 1. inch x 6.0 inch ± 1. inch) and shall be capable of accommodating pad sizes 38.1 mm x 50.8 mm (1.5 inch x 2 inch), 76.2 mm x 76.2 mm (3 inch x 3 inch), and 76.2 mm x 127.0 mm (3 inch x 5 inch).

2.2 The note tray shall be capable of holding repositional pads up to 76.2 mm x 127.0 mm (3 x 5 inch) size on the horizontal surface. An additional vertical tray, capable of holding pads up to 127.0 mm (5 inches) in length shall be placed at the back of the tray. An area shall also be provided to allow a pen or pencil to be stored horizontally in the tray.

2.3 Feet or a rubberized base shall be attached to the tray's bottom to protect the work area surface and to provide slip resistance during operation.

2.4 The tray is intended to be used with note pads having the bottom liner intact. The bottom liner is placed under the hold-down plate. The pad and hold-down plate is then pressured against the tray body. The pad shall be secure and shall not slip or slide.

2.5 The tray shall not slide, slip or lift when a sheet is removed using a side to side motion. The tray surface shall be angled 10 ° (referenced only) for ease of writing, writing comfort, and visibility.

2.6 The tray shall be contemporarily designed and constructed with color and finish in accordance with the manufacturer's standard commercial practice.

2.7 Workmanship. The tray frame shall be free of any defects which may affect appearance or impair serviceability, including but not limited to, superfluous coating of any kind, burrs, or scratches.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to General Services Administration, Federal Supply Service, Engineering Branch, 26 Federal Plaza, New York, NY 10278.

FSC 7520

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

4. Regulatory Requirements:

4.1 The offerer/contractor is encouraged to use recovered materials to the maximum extent practicable in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR)

4.2 Certification: The contractor shall certify that if polystyrene is used in the manufacture of the item, it shall contain a minimum of 25 percent Post-consumer Recovered Materials in accordance with Title 40 Code of Federal Regulations Part 247, Comprehensive Guideline for Procurement of Products Containing Recovered Materials; final rule. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provision of the contract.

5. Quality Assurance Requirements:

5.1 General Quality Statement. The products provided shall conform to the producer's own drawings, specifications, standards and quality assurance practices and be the same product offered for sale in the commercial market. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provision of the contract.

5.2 Examinations & Testing.

5.2.1 Suppliers are encouraged to use quality control (QC) techniques that exhibit control over their processes (e.g. (Statistical Process Control) SPC Techniques) as defined in American National Standards Institute (ANSI) Z1.1, Z1.2 and Z1.3 / American Society for Quality Control (ASQC) B.1, B.2 and B.3 that systematically reduce excess variations. If used, objective evidence shall be available that demonstrates overall measurement adequacy techniques and controls. These techniques shall ensure quality levels equal to, or greater than, those cited in applicable technical document or, herein

5.2.2 End item inspection may be used by the offerer or the Government representative, as a means to determine the effectiveness of the in process quality controls. While in-process controls shall not be substituted for end item performance testing they may be used for visual and dimensional sampling.

5.2.3 For those characteristics for which there are no such controls, lot by lot sampling for inspection shall be required. The sample unit for this item shall be one tray. Sampling shall be in accordance with the American National Standards Institute (ANSI) / American Society for Quality Control (ASQC) Z1.4, Sampling Procedures and Tables for Inspection by Attributes.

5.2.4 An inspection lot shall consist of all like items submitted for inspection at one time. The inspection level for visual, and dimensional inspections shall be S-2 with an AQL of 4.0 percent defective. The supplier must provide objective evidence (inspection records) that the presented material meets the requirements of the sampling plan as indicated above

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

6. Packaging:

6.1 Preservation, packing, and marking shall be specified in the contract or order.

7. Notes:

7.1 Applicable Documents. Issues of the following documents, in effect on the date of invitation for bids or request for proposal form a part of this document to the extent specified herein.

7.1.1 Federal Acquisition Regulation (FAR) may be obtained from the Superintendent of Documents, Government Printing Office, Washington. DC 20402.

7.1.2 Application for copies of (ANSI) Z1.1, Z1.2, Z1.3 and (ASQC) B.1, B.2 and B.3 may be obtained from the American Society for Quality Control. PO Box 3005, 611 E. Wisconsin Avenue, Milwaukee, WI 53201-4606.

7.2 National Stock Number Listing (NSNs. The following is a list of NSNs assigned which correspond to this CID. The list may not be indicative of all possible NSNs associated with the CID.

7520-01-166-0878
7520-01-207-4351

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice.

Preparing Activity:

GSA-FSS

Source: https://assist.dla.mil - Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.