[INCH-POUND]
A-A-3008
May 1, 1998

COMMERCIAL ITEM DESCRIPTION

FAN, CIRCULATING, PEDESTAL (OSCILLATING)

The General Services Administration has authorized the use of this commercial item description, for all federal agencies.

1. SCOPE.

1.1 Description. This document covers two speed pedestal mounted oscillating fans for 24 and 30 inch diameter blade assembly.

1.2 Intended Use. The fans described in this CID are for use in a industrial or commercial environment.

2. CLASSIFICATION

2.1 Design Form. The fans shall be in accordance with the plug style and blade diameter specified in Table 1.

Table 1.

PLUG STYLE	BLADE DIA.	CFM MIN. High/Low	WATTS MAX.	VOLTS	FREQUENCY	PHASE
North America	24 Inches	5350/3925	240	120	60	Single
North America	30 Inches	7300/5000	240	120	60	Single

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Federal Supply and Services, Tools and Appliances Center, ATTN: 6FET, 1500 East Bannister Road, Kansas City, MO. 64131-0038

FSC 4140

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

3. SALIENT CHARACTERISTICS

3.1 Standard product. The fans furnished under this CID shall be the manufacturer's current standard products including accessories and optional components that are offered to the commercial market. All accessories and options shall be identified with proposals tendered to the government in response to solicitations citing this document.

3.2 Design and construction. The fans covered in this document shall include a pedestal, adjustable column, blade assembly, fan guard, motor, switch, cable assembly, and all other parts necessary to constitute a complete and functional product.

3.2.1 Voltage and frequency. Unless otherwise specified, the motor for the fans shall be designed for a rated voltage of 120 volts alternating current +/- 10 percent, and a rated frequency of 60 hertz + 5 percent.

3.2.2 Insulation. Insulation shall be Class A or B in accordance with National Electrical Manufacturers Association (NEMA) Standard No. MG-1.

3.2.3 Switch. The switch shall have not less than one off and not less than two on speed positions.

3.2.4 Power cord and plug. The flexible cord shall be rated for use at a voltage not less than the rated voltage for the type as specified in paragraph 3.2.1 of this document. The fans shall be furnished with a three wire power supply cord with an integral ground. The power supply cord shall have a useable minimum overall length of ten feet. The power supply cord shall be terminated with the plug style as specified in paragraph 2.1, Table 1.

3.2.5 Blade assembly. The blade assembly shall consist of a complete air screw having at least three metal or plastic blades together with a hub or central support. The diameter of the blade assembly shall be as specified in paragraph 2.1 with a tolerance of +/- 1/2 inch.

3.2.6 Head tilt. The fan head shall be adjustable in a vertical plane from 5 degrees below the horizontal plane to not less than 15 degrees above the horizontal plane. The fan head shall have a locking device capable of locking the fan head in any position. If a tool is necessary to lock the fan head into position, the tool shall be supplied with each fan.

3.2.7 Oscillating mechanism. The oscillating mechanism shall have a cycle with a minimum angle range oscillation of 80 degrees. The mechanism shall be designed to disengage in any position within the oscillation cycle. The fan shall remain stationary in the position of disengagement.

3.2.8 Column and pedestal. The column shall be of a telescoping design consisting of an upper column sliding into or out of a lower column. The lower column shall prevent the accidental removal of the upper column. Without the use of special tools, the upper column shall lock at any height within the vertical adjustment limits of the column. When the column is at its highest adjustable positions, the top of the fan guard shall not be less than 90 inches, nor more than 96 inches from the floor. The column shall have an adjustable height of not less than 30 inches above its lowest adjustable position. The power supply cord shall exit the pedestal, at any point that is less than 3 inches above the floor level. A bushing shall be used to protect the supply cord against abrasion and fraying where the supply cord enters and exits the column. The supply cord shall also have a bushing where the cord enters the fan motor.

3.2.9 Guard. The guard shall enclose the entire face, perimeter, and reverse side of the fan blades and associated moving parts. The guard shall consist of a front section and a rear section, designed so that when assembled to form a complete guard. Additionally, the sections must be readily separable, without the use of special purpose tools, so as to permit access to the blade assembly and associated moving parts

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

3.2.10 Codes and standards. Fans shall conform to the applicable requirements of the codes and standards specified in 3.2.10.1 through 3.2.10.3.

3.2.10.1 NFPA. Wiring shall conform to National Fire Protection (NFPA) Standard No. 70, The National Electrical Code.

3.2.10.2 NEMA. Motors shall conform to National Electrical Manufacturers Association (NEMA) Publication No. MG-1.

3.2.10.3 UL. Fans shall conform to the requirements of Underwriters Laboratories Inc. (UL) Standard No. UL 507.

3.3 Materials. Materials not definitely specified herein shall be of the quality specified by the manufacturer and shall conform to the manufacturer's own drawings, specifications, standards, and quality assurance procedures.

3.3.1 Finish and color. The fans shall be finished according to the manufacturer's standard commercial practice.

3.4 Performance. The fans shall conform to performance requirements expressed in paragraphs 3.4.1 through 3.4.3.

3.4.1 Operating speed. The low speed position shall provide 60 to 80 percent of the maximum speed when operating at rated voltage and frequency. The fan shall be operated at both low and maximum speed settings and speed (r.p.m.) shall be measured stroboscopically or with a counter which imposes no appreciable load on the fan motor. The sensitivity and accuracy of the test apparatus shall be such that differences of 20 r.p.m. may be detected.

3.4.2 CFM air delivery. The airflow rate shall be calculated using the Thrust Method in accordance with paragraphs 6.2 through 10 of AMCA standard 230-96, "Laboratory Methods of Testing Air Circulator Fans For Rating". The minimum CFM air delivery shall be as specified in paragraph 2.1 for the type and blade diameter as specified in the contract or order.

3.4.3 Vibration limits. Rotating components of fans shall be balanced to the extent that total vibration will not exceed .009 times the distance in inches between an upward extension of a vertical line running through the approximate center of the motor support and the point of measurement.

3.5 Fan assembly. For shipping purposes, the fan may be partially disassembled into no more than five parts consisting of the motor, adjustable column, blade assembly, guard and base. Re-assembling the fan shall not require special tools(s) or skill(s).

3.6 Order of precedence. In the event of a conflict between the text of this CID, and the referenced documents cited herein. The text of this CID shall take precedence. No reference in this CID, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3.7 Data. In addition to the safety and installation instructions required by UL Standard No. 507, the contractor shall furnish with each fan a copy of the manufacturer's standard "owner/operator manual" applicable to the machine. The manual shall include instructions for operating the machine, safety precautions, commercial repair instructions which shall include a complete list of all replaceable parts, and preventative/routine maintenance instructions. This data shall be the same information that is provided with similar machines sold in the commercial market.

3.8 Metric product. Product manufactured to metric (SI) dimensions shall be considered on an equal basis with those manufactured using inch-pound units of measure, provided they fall within the specified tolerances using conversion tables contained in the latest revision of ASTM E 380, Standard Practice for Use of the International System of Units (SI), and all other requirements of this Commercial Item Description are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

4. REGULATORY REQUIREMENTS

4.1 Occupational Safety. Fans shall conform to Occupational Safety and Health Act (OSHA), 29 CFR 1910).

4.2 Recovered materials. The offeror/contractor is encouraged to use recovered materials according to Public Law 94-580 to the maximum practical extent. Recycled or reclaimed materials may be used in the construction of the equipment described herein. Recycled and reclaimed materials shall consist of previously used material that has been reprocessed to become a source of new raw materials. Under no conditions or circumstances shall the contractor submit to the Government for acceptance reconditioned or rebuilt components as a part of the equipment described herein.

5. QUALITY ASSURANCE PROVISIONS

5.1 Product conformance. The product offered shall meet the salient characteristics of this Commercial Item Description, and conform to the producer's own drawings, specifications, standards, and quality assurance practices and be the same as the product offered for sale in the commercial marketplace. When specific quality assurance provisions are specified for any commercial characteristic the contractor shall maintain records resulting from his inspection(s) conducted according to the specific quality assurance provisions. The government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided under the provisions of the contract. The government reserves the right to audit the contractor's quality assurance records.

5.2 Successful commercial operation. No item of equipment offered under this CID shall be acceptable unless the manufacturer has marketed equipment of the same size and type in a commercial environment for a minimum period of one year. Equipment installed for test purposes in a manufacturer's plant or test laboratory shall not be considered as complying with this requirement.

5.3 Place and date of manufacture. Each fan shall bear an alpha-numeric code to indicate the manufacturer's plant where produced and the date that production occurred. This encoded information shall be permanently stamped or affixed to the fan.

5.4 Warranty. Unless otherwise specified in the contract, the manufacturer's standard commercial warranty terms shall apply. The warranty shall become effective from the date of the startup of the fan.

6. PACKAGING

6.1 Packaging. Requirements for preservation, packing, packaging, and marking of packages shall be as specified in the contract or order.

7. NOTES

7.1 Commercial item certification. The commercial item certification clause must appear in the solicitation when this CID is used for procurement.

7.2 Ordering Data. The following information is required when ordering items covered in this CID:

a. Title, number, and date of this document.
b. Blade diameter (see 2.1).
c. Packaging required (see 6.1).
d. National Stock Number (see 7.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

7.3 National Stock Numbers (NSNs). Table 2 is a list of NSNs assigned that correspond to this CID. The list may not indicate all possible NSNs associated with the CID.

Table 2.

PLUG STYLE	BLADE DIAMETER	NSN
North America	24 Inches	4140-01-278-3874
North America	30 Inches	4140-01-278-1527

7.4 Referenced documents. Copies of referenced documents are available from the following sources:

7.4.1 Government Documents.

Federal Supply Service Bureau
Specification Section
Suite 8100, 470 L'Enfant Plaza, SW
Washington, DC 20407.

US Department of Labor
Occupational Safety and Health Act (OSHA)
200 Constitutional Avenue, N.W.
Washington, D.C. 20210

7.4.2 Non-government documents.

National Electrical Manufacturers Association (NEMA)

National Electrical Manufacturers Association
2101 L Street, NW Suite 300
Washington, DC 20037

National Fire Protection Association (NFPA)

National Fire Protection Association
One Batterymarch Park
Quincy, MA 02269-9101

Underwriters Laboratories Incorporation

333 Pfingsten Road
Northbrook, IL 60062-2096

American Society for Testing & Materials (ASTM)

American Society for Testing & Materials (ASTM)
100 Barr Harbor Drive
West Conshohocken, PA 19428-2959

Air Movement and Control Association (AMCA)

Air Movement and Control Association International, Inc.
30 West University Drive
Arlington Heights, IL 60004-1893

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

7.5 Source of supply. A partial list of manufacturers of two speed pedestal mounted oscillating fans for 24 and 30 inch diameter blade assemblies described herein is as follows:

Airmaster Fan Company

Airmaster Fan Co.
1300 Falahee Rd.
Jackson, MI 49204

MILITARY INTERESTS:
NONE: DoD has no registered interest in revisions and amendments to this Commercial Item Description until further notice.

Preparing Activity:

GSA-FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.