[INCH-POUND]
A-A-3017
June 25, 1996
SUPERSEDING
GGG-B-481A
February 16, 1954

COMMERCIAL ITEM DESCRIPTION

BLOCK, DOLLY, SHEET METAL

The General Services Administration has authorized the use of this Commercial Item Description for procurement of GGG-B-481 for all federal agencies.

1. SCOPE.

1.1 Scope. This commercial item description covers dolly blocks for use in straightening, swaging, and finishing by hand, sheet metal bodies and fenders of automobiles and other motor vehicles.

2. CLASSIFICATION.

2.1 Classification. Dolly blocks shall be of the following types and styles:

Type I	-	General purpose	Type VI	-	Body
Style A	-	High crown	Type VII	-	Finger
Style B	-	Low crown	Type VIII	-	Shrinking
Style C	-	Anvil	Style A	-	With trenching grooves
Style D	-	Rail	Style B	-	Without trenching grooves
Type II	-	Bead	Type IX	-	Fender
Type III	-	Heel	Type X	-	Angle
Type IV	-	Toe	Type XI	-	Roughing
Type V	-	Wedge	Type XII	-	Thin high crown

3. SALIENT CHARACTERISTICS.

3.1 Design. Strength and other essential physical properties shall be adequate throughout the dolly blocks for the purpose intended. Materials used in the construction of dolly blocks shall be as hereinafter specified. Type VIII style A and B dolly blocks shall be made of steel or malleable iron; steel having a Rockwell C hardness of 40 to 58 HRC, and malleable iron having a hardness of 20 to 35 HRC, when tested in accordance with ASTM E 18. All other types and styles shall be of forged steel having a Rockwell C hardness of 40 to 58 HRC, when tested in accordance with ASTM E 18. All radii and contours shall be blended and shall be free of burrs and sharp edges. Surfaces usually ground, buffed, or otherwise finished shall have a surface finish equivalent to the finish produced by 80-grit or finer abrasive. The dolly blocks shall be coated with a lacquer or equivalent finish. All types and styles of dolly blocks shall conform to Table I, as applicable.

3.2 Hardness test. A hardness test shall be performed in accordance with ASTM E 18 to ensure the hardness is as specified in 3.1.

Beneficial comments, recommendations, additions, deletions, clarifications, etc., and any other data which may improve this document should be sent to: General Services Administration, Federal Supply Service, Tools and Appliances Commodity Center, Washington, DC 20406.

Distribution Statement A. Approved for public release; distribution is unlimited. FSC 5120

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

TABLE I. Dimensions for dolly blocks

Type	Style	Length Approximate (Inches)	Width Approximate (Inches)	Thickness Approximate (Inches)	Weight Approximate (Pounds)
I	A	3	2-1/2	2	2-1/2
	B	3	2-1/2	2	2-1/2
	C	4	2-3/4	2-1/2	2-1/2
	D	3	2-1/2	2-1/2	2-1/2
II		4-1/2	2-1/2	1-3/4	2-1/2
III		3	2-1/2	1-1/2	2-1/2
IV		4-1/2	2-1/2	1	2-1/2
V		5	2-1/4	1-3/4	2-1/2
VI		4-1/2	2-1/4	1-1/2	2-1/2
VII		3-5/8	2-3/4	2-1/2	2-1/2
VIII	A	3	2-1/2	1-3/4	2-1/2
	B	3-1/4	3	1-1/4	2-1/2
IX		3-1/2	3	1-1/4	2-1/2
X		3-3/4	2-1/2	1-3/4	5-1/2
XI		4	4-1/4	2-3/4	2-1/2
XII		4	2-1/2	1	

3.2 Type I, general purpose.

3.2.1 Style A, high crown. The style A, high-crown dolly blocks shall provide suitable working surfaces for use on high-crown fenders, panels, and hoods, and shall be similar to Figure 1.




Figure 1. Type I, style A, general purpose, high-crown dolly block.

3.2.2 Style B, low crown. The style B, low-crown dolly blocks shall provide suitable working surfaces for use on low-crown panels and flat portions of the body, and shall be similar to Figure 2.




Figure 2. Type I, style A, general purpose, low-crown dolly block.

3.2.3 Style C, anvil. Anvil dolly blocks shall provide working surfaces suitable for various curves and contours of the body, door panels, and deep-skirted fenders, and shall be similar to Figure 3.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:28Z
Check the source to verify that this is the current version before use.




Figure 3. Type I, style C, general purpose, anvil dolly block.

3.2.4 Style D, rail. The rail dolly blocks shall be suitable for bumping, dinging, straightening, and finishing various portions of the body, door panels, and fenders. The block shall also be provided with two beading and flanging lips, and shall be similar to Figure 4.




Figure 4. Type I, style D, general purpose, rail dolly block.

3.3 Type II, bead. The bead dolly blocks shall be similar to Figure 5. The working surfaces shall be suitable for use on long curved fenders, beads, and flanges.




Figure 5. Type II, bead dolly block.

3.4 Type III, heal. The heel dolly blocks shall be similar to Figure 6. The working surface shall be adaptable for use in sharp corners and wide radii portions of body and panels.




Figure 6. Type III, heel dolly block.

3.5 Type IV, toe. The toe dolly blocks shall be similar to Figure 7. The toe block shall be provided with a flat face and flat edge for use in dinging flat surfaces and edges of the lower portion of the hood and other flat panels. The crowned and curved portion of the block shall be suitable for use in odd crowns and contours of the body and panels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.




Figure 7. Type IV, toe dolly block.

3.6 Type V, wedge. The wedge dolly blocks shall be similar to Figure 8. The shape of the block shall be suitable for use behind brackets, braces, and other reinforcements of the roof, body, fenders, and panels.



Figure 8. Type V, wedge dolly block.

3.7 Type VI, body. The body dolly blocks shall be similar to Figure 9. The crowns and radii shall be suitable for use on various curves and contours of the body.




Figure 9. Type VI, body dolly block.

3.8 Type VII, finger. The finger dolly blocks shall be similar to Figure 10. The block shall be adaptable for bump hammering on portions of the body where space is limited due to inner construction and adjoining metals.




Figure 10. Type VII, finger dolly block.

3.9 Type VIII shrinking.

3.9.1 Style A, with trenching grooves. Style A with trenching grooves dolly blocks shall be provided with high and low crowns suitable for hot shrinking, raising beads, and molding, and shall be similar to Figure 11. Wide and narrow trenching grooves shall be provided for setting in welded seams for paddle soldering.




Figure 11. Type VII, style A, shrinking,
with trenching grooves dolly block.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.

3.9.2 Style B, without trenching grooves. Style B without trenching grooves dolly blocks shall be provided with a low crown suitable for shrinking body metal, raising beads and molding, and shall be similar to Figure 12.



Figure 12. Type VII, style B, shrinking, without trenching grooves dolly block.

3.10 Type IX, fender. Fender dolly blocks shall be similar to Figure 13. The radii and contours of the block shall be suitable for rolled edges and fender beads.



Figure 13. Type IX, fender dolly block.

3.11 Type X, angle. The angle dolly blocks shall be similar to Figure 14. The angle blocks shall be suitable for use on various angles, creases, and curves in the body panels and fenders.




Figure 14. Type X, angle dolly block.

3.12 Type XI, roughing. Roughing dolly blocks shall be similar to Figure 15. The outside contour and side surfaces shall be suitable for roughing out deep and shallow dents with a lip provided at one end of the working surface for reshaping turned-under flanges.



Figure 15. Type XI, roughing dolly block.

3.13 Type XII, thin high crown. Thin high-crown dolly blocks shall be similar to Figure 16. The thin high-crown dolly blocks shall be adaptable for work where space is limited due to inner construction and adjoining metals.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.




Figure 16. Type XII, thin high-crown dolly block.

3.14 Identification marking. The tool shall be marked with the manufacturer's name or identifying symbol, and the state or country of manufacture, unless otherwise specified. All identification markings shall be engraved, etched, molded, or indented directly on the item's surface in such a manner that it remains clearly legible throughout the life of the item.

3.15 Workmanship. Details of workmanship shall be in accordance with the best commercial practice. Paints, coatings, platings, and finishes shall be smooth, adherent, continuous, and not stained or discolored. External surfaces shall be free of tool and gouge marks, nicks, or other surface imperfections. The item shall be free from manufacturing workmanship defects (e.g., sharp or rough external edges, corners, or surfaces) and material workmanship defects (e.g., pits, rips, fins, burrs, tears, nodules, cracks, blisters) which may adversely impact the item's serviceability, durability, safety, or appearance.

4. REGULATORY REQUIREMENTS.

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

4.2 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within the tolerances specified (using conversion tables contained in the latest revision of Federal Standard 376) and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

5. QUALITY ASSURANCE PROVISIONS.

5.1 Product conformance. The product provided to the Government shall conform to the contractually specified requirements. For product characteristics and requirements which are not contractually specified, the provided product shall conform to the producer's own drawings, standards, specifications, and quality assurance practices for the highest quality product commercially offered by the producer. If the product is not commercially offered by the producer, the best commercial practices shall apply. The Government reserves the right to require proof of such conformances prior to first delivery and thereafter as provided for under the provisions of the contract.

5.2 Responsibility for inspection. Unless otherwise specified, the contractor is responsible for the performance of all inspection requirements and may use any commercial facilities (including the contractor's own facilities) suitable for performance of the inspection requirements, unless disapproved by the Government. The Government reserves the right to perform any inspections deemed necessary to assure the item conforms to the specified requirements.

5.3 Bid sample(s). When a bid sample requirement is specified in the solicitation, the bid sample(s) shall be inspected for all salient characteristics by the Government. A failure of any bid sample to meet the salient characteristics shall be cause for rejection.

5.4 First article sample(s). When a first article requirement is specified in the contract, the first article sample(s) shall be inspected for all salient characteristics. A failure of any first article sample to meet the salient characteristics shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:28Z
Check the source to verify that this is the current version before use.

6. PACKAGING.

6.1 Packaging. Requirements of preservation, packing, packaging, and marking of packages shall be as specified in the contract or order.

7. NOTES.

(This section contains information of a general or explanatory nature that is not mandatory.)

7.1 Addresses for obtaining copies of referenced documents:

Federal Specifications and Standards: Federal Supply Service Bureau, Specification Section, Suite 8100, 470 L'Enfant Plaza, SW, Washington, DC 20407.

Federal Acquisition Regulations (FAR): Government Printing Office, Superintendent of Documents, Washington, DC 20402-9371.

ASTM E18: American Society for Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and should include the following information in procurement documents:

(a) Title, number, and date of this Commercial Item Description.
(b) When applicable, the appropriate NSN(s).
(c) When applicable, the specific types and styles, as specified in the Commercial Item Description.
(d) If bid samples are required and the number of samples required.
(e) If first article samples are required and the number of samples required.
(f) If lot sampling inspection is required and the applicable lot sampling requirements.

For example, the following typical lot sampling requirements would be specified in the contract:

Sampling for inspection. Sampling for inspection (both examinations and testing) shall be in accordance with ANSI/ASQC Z1.4.

Inspection. Each sample dolly block shall be examined and tested for all salient characteristics. The Inspection Level shall be S-2 with an Acceptable Quality Level of 4.0, expressed in terms of defects per hundred units.

(g) What preservation, packing, packaging, and marking of packages are required.

7.3 National Stock Numbers (NSNs). The following list of NSNs corresponds to the types, classes, and sizes specified in this CID. This list may not be indicative of all possible NSNs associated with this CID.

NSN	
5120-00-221-1637	Type I - General Purpose, Style D - Rail

MILITARY INTERESTS:

NONE: DoD has no registered interest in revisions or notices to this Commercial Item Description until further notice.

PREPARING ACTIVITY:

GSA - FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:28Z
Check the source to verify that this is the current version before use.