A-A-687
December 17, 1979

COMMERCIAL ITEM DESCRIPTION

STRAPPING, NONMETALLIC (AND CONNECTORS)

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification PPP-S-760.

Salient characteristics.

This description covers cord and flat nonmetallic strapping, and connectors of the following kinds: (A) Cord strapping, regular duty and heavy duty; (B) Plastic strapping, polyolefin and polyester, flat and embossed; (C) Plastic strapping, nylon, flat; (D) Buckles, metallic and plastic, regular duty and heavy duty; (E) Seals, mechanically installed and tensioned, with the following designations: open, closed, and double. The principal characteristics of nonmetallic strapping are the physical dimensions (width, thickness, and length), tensile breaking strength in pounds, core size, coil length, and joint efficiency (see tables I, II, III, IV, V, and VI).

All strapping, no matter how it is sealed (buckles, seals, or welds), shall have a minimum seal strength of 40 percent of required strap breaking strength.

TABLE I. Cord strapping breaking strength

Nominal width of strapping (inches)	Grade (Duty)	Minimum breaking strength (lb)
1/4	A (regular)	234
3/8	A	350
1/2	A	467
5/8	A	585
5/8	B (heavy)	750
3/4	A	700
3/4	B	875

TABLE II. Polyolefin and polyester plastic flat strapping breaking strength

Nominal width of strapping (inches	Nominal thickness 1/ (inches)	Minimum breaking strength (lb)
7/32	0.014	120
7/32	.018	160
1/4	.014	145
1/4	.015	180
1/4	.019	200
1/4	.027	290
3/8	.015	290
3/8	.018	250
3/8	.020	390
3/8	.024	350
7/16	.019	300
7/16	.025	450
7/16	.030	550
1/2	.0125	300
1/2	.015	390
1/2	.017	350
1/2	.020	530
1/2	.022	450
1/2	A/A 2/	500
1/2	A/A	600
1/2	.020	650
1/2	.025	660
1/2	.030	810
5/8	.015	500
5/8	.020	680
5/8	.025	850
5/8	.030	1,030
3/4	.028	1,050
1-1/4	.035	2,350

1/ Nominal thickness for embossed strapping shall be no more than twice the figures shown hereinunder.

2/ A/A is any thickness acceptable.

TABLE III. Nylon flat strapping breaking strength

Nominal width of strapping (inches)	Nominal thickness (inches)	Minimum breaking strength (lb)
7/16	0.017	420
7/16	.023	560
7/16	.029	700
1/2	.015	420
1/2	.020	560
1/2	.025	700
1/2	.030	900

TABLE IV. Core requirements for cord strapping

Approximate weight of spool (lb)	Length of core (inches)	Inside diameter of core (inches)	Thickness of core wall (inches)
15 to 25	5-1/2 ± 1/4	3 + 1/8 - 0	0.060 ± 0.005
25 to 50	5-1/2 ± 1/4	3 + 1/8 - 0	.250 ± .005
over 50	10 ± 1/4	3 + 1/8 - 0	.250 ± .005

Source: https://assist.dla.mil -- Downloaded: 202640-26T08:09Z
Check the source to verify that this is the current version before use.

TABLE V. Types of spools, and yards per spool of cord strapping

Nominal width of strapping	Grade	Types of spool	Yards per spool
1/4	A	Regular	2,600
		Quad	10,400
3/8	A	Regular	1,750
		Quad	7,000
1/2	A	Regular	1,300
		Quad	5,200
5/8	A	Regular	1,000
		Quad	4,000
5/8	B	Regular	1,400
		Quad	2,800
3/4	A	Regular	700
		Quad	2,800
3/4	B	Regular	1,134
		Quad	2,268

TABLE VI. Coil yardage 1/ of polyolefin and nylon flat strapping

Width, inch	Thickness, inch	Min. yards per 3" wide oscillated wound coil	Min. yards per 5-3/4" wide oscillated wound coil	Min. yds per 6" wide oscillated wound coil
7/32	0.014			2,500
7/32	.018			1,360
1/4	.014		6,500 2/	
1/4	.015	3,150		
1/4	.019		5,000 3/	
1/4	.022			6,000
1/4	.027		3,300	5,000
3/8	.015	2,166		
3/8	.018		3,000	4,000
3/8	.020	1,600		
3/8	.024		2,500	3,000
7/16	.017			3,175
7/16	.023			2,350
7/16	.025			2,600
7/16	.029			1,860
7/16	.030			2,150
1/2	.0125	2,000		
1/2	.015	1,500		2,950
1/2	.017		1,000 4/	3,500
1/2	.020	1,200 or 3,600		2,360
1/2	.025	1,000		1,890
1/2	.030	750		1,575
5/8	.015	1,166		
5/8	.020	866		
5/8	.025	700		
5/8	.030	600		
3/4	.028 5/			
1-1/4	.035 6/			

1/ Contractor may furnish more yards per coil than the minimum required unless otherwise specified.
2/ 2,300 yards in self-contained dispensing carton.
3/ 1,830 yards in self-contained dispensing carton.
4/ 1,000 yards in self-contained dispensing carton.
5/ 1,500 yards per 8-inch wide coil.
6/ 167 yards per 1-1/4-inch wide ribbon wound coil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packing. The packaged nonmetallic strapping shall be packed in fiberboard boxes to insure delivery at destination, to provide for redistribution by the initial receiving activity, and shall be acceptable by common carrier under National Motor Freight Classification and Uniform Freight Classification.

Palletization. The shipping containers shall be palletized on expendable wooden pallets, 2- or 4-way design, to facilitate handling in accordance with normal commercial practice. The palletized load shall not exceed, 2,500 lb in weight, 63 inches in height, 56 inches in length, and 45 inches in width. Less-than-half pallet loads need not be palletized.

Ordering information. Kind, width, thickness, length, breaking strength, duty, buckle material and design, and seal design.

Cross reference. The commercial item description and specification types and grades relate to each other as follows:

A-A-687	PPP-S-760B
Cord strapping	Type I - Strapping, cord
Regular duty	Grade - regular duty
Heavy duty	Grade - heavy duty
Polyolefin	Type II
Polyester	----------
Nylon	Type III
Buckles	Buckles
Plastic regular duty	----------
Metallic heavy duty	----------
Seals	Seals
Open	----------
Closed	----------
Double	----------

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.