MILITARY SPECIFICATION

INDICATOR, PRESSURE, HYDRAULIC, 0-4000 PSI

This amendment forms a part of Military Specification MIL-I-7084A dated 17 Nov 1968, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Add to bottom of page:

"Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: the Engineering Division, San Antonio ALC/MMEDO, Kelly AFB, TX 78241 by using the self addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter."

1.1, delete in its entirety and substitute the following:

"1.1 Scope. This specification covers hermetically,sealed, remote indicating, synchro-type, 0-4,000 psi, MS28010-5 hydraulic pressure indicators."

2.1, delete in its entirety and substitute the following paragraph 2.1 and add paragraph 2.1.1.

"2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein."

Under SPECIFICATIONS, Federal, delete the following:

"PPP-B-601 - Boxes, Wood, Cleated - Plywood
PPP-B-636 - Box, Fiberboard
PPP-B-676 - Box, Setup"

PAGE 2

Under STANDARDS, Federal, delete "Federal Standard No. 595 Colors" and substitute "FED-STD-595 - Colors."

Under STANDARDS, Military:

Delete "MIL-STD-100" and substitute "DOD-STD-100, same title.

FSC 6685

Source: https://assist.dla.mil -- Downloaded: 202640-17T08:03Z
Check the source to verify that this is the current version before use.

Delete title for MIL-STD-143 and substitute "MIL-STD-143 Standards and Specifications, order of Precedence for the Selection of."

Delete title for MIL-STD-461 and substitute "MIL-STD-461 Electromagnetic Emission and Susceptability Requirements for the Control of Electromagnetic Interference."

Delete title for MIL-STD-781 and substitute "Reliability Design Qualification and Production Acceptance Tests: Exponential Distribution."

Delete title for MIL-STD-785 and substitute "MIL-STD-785 Reliability Program for Systems and Equipment Development and Production."

Delete "MS33586 Metals, Definition of Dissimilar" and substitute "MIL-STD-889 Dissimilar Metals."

Under STANDARDS, MILITARY, add the following:

"MIL-STD-794 Parts and Equipment, Procedures for Packaging of."

Delete parenthetical source statement and substitute the following:

"(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)"

2.2, delete in its entirety and substitute the following:

"2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable."

Add the following industry document and parenthetical source statement:

"AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D3951 - 82 Standard Practice for Commercial Packaging

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania 19103.)

Add the following new paragraph:

"2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence."

PAGE 3

3.3.4, line 3, delete "MS33586" and substitute "MIL-STD-889."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:03Z
Check the source to verify that this is the current version before use.

testing in accordance with the applicable requirements of 4.6.

PAGE 4

3.4.2.1, line 2, delete "Federal Standard No. 595" and substitute "FED-STD-595."

3.4.3.1, line 2, delete "Federal Standard No. 595" and substitute "FED-STD-595."

3.4.3.1.1, line 4 and 5 delete "Federal Standard No. 595"and substitute "FED-STD-595."

PAGE 9

3.6, line 3, delete "MIL-STD-100" and substitute "DOD-STD-100."

PAGE 10

4.1, delete in its entirety and substitute the following:

"4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

PAGE 15

4.6.14, delete in its entirety and substitute the following:

"4.6.14 Temperature altitude. The indicator shall be subjected to an absolute pressure equivalent to an altitude of 100,000 feet for a period of one hour at a temperature of - 55°C ± 2°C. While at this pressure and temperature, the indicator shall be subjected to the scale error tests specified in Table II. There shall be no damage to the indicator as a result of this test. The test can be performed concurrently with the low temperature exposure test."

PAGE 17

Delete paragraph 5, 5.1, 5.1.1 and 5.1.2 in their entirety and substitute the following:

"5. PACKAGING

5.1 Preservation. Preservation shall be level A, C, or industrial as specified (see 6.2).

5.1.1 Level A. Unless otherwise specified (see 6.2), each indicator shall be individually unit packed in accordance with the methods of MIL-P-116 designated herein insuring compliance with the applicable requirements of that specification.

5.1.2 Level C. The level C preservation for indicators shall conform to the MIL-STD-794 requirements for this level. OR

Source: https://assist.dla.mil -- Downloaded: 202640-17T08:03Z
Check the source to verify that this is the currentversion before use.

5.1.3 Commercial packaging - Shall be in accordance with ASTM D 3951."

PAGE 18

Delete paragraphs 5.2, 5.2.1, 5.2.2 and 5.2.3 in their entirety and substitute the following:

"5.2 Packing. Packing shall be level A, B, C, or Commercial, as specified (see 6.2).

5.2.1 Level A. The packaged indicators shall be packed in containers as specified in MIL-STD-794 for level A protection.

5.2.2 Level B. The packaged indicators shall be packed in containers as specified in MIL-STD-794 for level B protection.

5.2.3 Level C. The packaged indicators shall be packed in containers as specified in MIL-STD-794 for level C protection. OR

5.2.4 Commercial packaging - Shall be in accordance with ASTM D 3951."

Delete 5.4 in its entirety and substitute the following new paragraphs 5.4, 5.4.1 and 5.4.2:

"5.4 Marking.

5.4.1 Levels A, B, and C. In addition to any special or other identification marking required by the contract (see 6.2), each unit pack, intermediate and exterior container and unitized load shall be marked in accordance with MIL-STD-129.

5.4.2 Commercial marking - Shall be in accordance with the requirements of ASTM D 3951."

PAGE 19

6.3, line 9 and 10, delete "Aeronautical Systems Division (ASD), Wright Patterson Air Force Base, Ohio 45433" and substitute "the Engineering Division, SA-ALC/MMEDC, Kelly AFB, TX 78241."

Custodians:
Army - AV
Navy - AS
Air Force - 99

Review activity:
DLA - GS

Preparing activity:
Air Force - 82

(Project 6685-0731)

FSC 6685

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:03Z
Check the source to verify that this is the current version before use.