MIL-I-7086B
AMENDMENT 3
23 MAY 86
SUPERSEDING
AMENDMENT 2
15 OCTOBER 1978

MILITARY SPECIFICATION

INDICATOR, PRESSURE, OIL, 0-100 PSI

This amendment forms a part of MIL-I-7086B, dated 15 November 1968, and is approved for use by all Department and Agencies of the Department of Defense.

PAGE 1

* 1.1 Add title "Scope".

* Delete "2.1" and add "2.1 Government documents".

* Add:
"2.1.1 Specifications standards, and handbooks. The following specifications, standard, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation."

* Under SPECIFICATION, Federal delete: "L-P-378 and PPP-C-834", and add: "PPP-B-601, Boxes Wood, Cleated Plywood and PPP-B-636, Box, Shipping, Fiberboard".

2.1 Under SPECIFICATONS, Military, add: "MIL-L-25142 Luminescent Material, Flourescent".

* Add boxed paragraph to bottom center of page.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/MMEDO, Tinker AFB OK 73145-5990 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

PAGE 2

2.1 Under STANDARDS, Military delete "MS 33586" and add: "MIL-STD-889 Dissimilar Metals".

* Delete source paragraph and add:

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

AMSC N/A FSC 6620

DISTRIBUTION STATEMENT. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:04Z
Check the source to verify that this is the current version before use.

* Add:
"2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified , the issue of the documents not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation."

ASTM-D-3951-82 Packaging, Commercial - 29 January 1982.

(Application for copies should be addressed to: ASTM, 1916 Race St, Philadelphia PA 19103.)

(Nongovernment standards and other publications are normally available from the organizations which prepare of which distribute the documents. These documents also may be available in or through libraries or other informational services.)"

* Add:
" 3.3.2.1 Recovered materials. Recovered materials shall be used to the maximum extent possible without jeopardizing the end use of the item."

PAGE 3

3.3.4 Line 3, delete "MS 33586" and add "MIL-STD-889".

3.4.2.1 Delete and add:
"3.4.2.1 Pointer finish. The shaded portion of the pointer shall be finished as follows:

MS 28010-2 Fluorescent Luminenscent Material in accordance with MIL-L-25142.

MS 28010-8 Lusterless white color number 37875 in accordance with FED-STD-595."

PAGE 5

3.4.3.1 Delete and add:
3.4.3.1 Dial markings. Dial marking dimensions shall be as specified in Table I and shall be finished as follows:

MS 28010-2 Fluorescent Luminescent Material in accordance with MIL-L-25142.

MS 28010-8 Lusterless white color number 37875 in accordance with FED-STD-595."

PAGE 6

* 3.4.10.1 Add title "Synchro electrical characteristics".

PAGE 13

4.6.4 Line 2, delete reference to "Table III" and substitute "Table II".

* 4.6.7 Vibration; line 2, change to read: "Method 514.2, equipment catagory (b.1), procedure 1, curve B. Use curve B from 5 (Hz) and then vertically down the 500 (Hz) line to the horizontal axis".

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:04Z
Check the source to verify that this is the currentversion before use.

* 4.6.14 Delete "504" and add: "504.1".

* 4.6.18 Delete "509" and add: "509.1".

* Delete Section 5 and add:
"5 PACKAGING

5.1 Preservation-packaging. Preservation-packaging shall be level A, C, or Industrial, as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Cleaning. Indicators shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Indicators shall be dried in accordance with process D-4 of MIL-P-116.

5.1.1.3 Preservation application. Not applicable.

5.1.1.4 Unit packaging. Unless otherwise specified by the contracting activity, each indicator shall be packaged in quantity unit packs of one each in accordance with Method ICI of MIL-P-116. Overbox completed pack in PPP-B-636 container. Apply sufficient cushioning material between bag and unit container of a type, density, and thickness to insure shock transmission does not exceed peak values in G5 established for the indicator when completed packs are subjected to the rough handling drop tests of MIL-P-116.

5.1.2 Level C. Indicators shall be clean, dry, and individually packaged in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from supply source to the first receiving activity.

5.1.3 Industrial. The industrial preservation of indicators shall be in accordance with ASTM-D-3951-82.

5.2 Packing. Packing shall be level A, B, C, or Industrial as specified (see 6.2).

5.2.1 Level A. Indicators packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-601, Styles A or B, Class overseas, unless otherwise specified by the contracting activity. Insofar as practical, exterior shipping container shall be of uniform shape, size, minimum tare and cube consistent with the protection required.

5.2.2 Level B. Indicators packaged as specified in 5.1.1 shall be packed in shipping containers conforming to PPP-B-636, class weather-resistant, unless otherwise specified by the contracting activity. Other requirements as specified in 5.2.1 apply.

Source: https://assist.dla.mil -- Downloaded: 202640-17T08:04Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. Pakcing shall be applied which affords adequate protection during domestic shipment from the supply source to the first receiving activity for immediate use. This level shall conform to applicable carrier rules and regulations.

5.2.4 Industrial. The packaged indicators shall be packed in accordance with ASTM-D-3951-82.

5.3 Marking. In addition to any other markings required by the contract or order (see 6.2), interior and exterior containers shall be marked in accordance with MIL-STD-129."

Indicator, Pressure, Oil, 0-100 PSI, M528010-2.

Indicator, Pressure, Oil, 0-100 PSI, M528010-8.

PAGE 17

* Delete paragraph "6.6".

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) From the previous amendment were made. This was done as a conveninece only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Navy - AS
Air Force - 99

Preparing Activity:
Air Force - 71

Project Number:
6620 - 0386

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:04Z
Check the source to verify that this is the currentversion before use.