INCH-POUND
MIL-I-7086C
30 DECEMBER 1994
SUPERSEDING
MIL-I-7086B
15 NOVEMBER 1968

MILITARY SPECIFICATION

INDICATOR, PRESSURE, OIL 0-100 PSI

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers two types of hermetically sealed, remote indicating, MS28010-2, and -8, synchro-style oil pressure indicator.

1.2 Classification. The indicators shall be classed as follows:

a. MS28010-2 Fluorescent-Luminescent material in accordance with Air Force P/N 8988994.

b. MS28010-8 Lusterless white color number 37875 in accordance with FED-STD-595.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standard's (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

PPP-B-636 Box, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Oklahoma City Air Logistics Center/TICLA, Tinker AFB, OK 73145-5990 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 6620

DISTRIBUTION STATEMENT A. Approved for public release: distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:04Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116	Preservation, Methods Of
MIL-B-131	Barrier Materials, Watervaporproof, Greaseproof, Flexible, Heat Sealable
MIL-S-007742	Screw Threads, Standard, Optimum Selected Series: General Specification For
MIL-T-7748	Transmitters, Pressure, Synchro, Aircraft, 320 Degree Movement, High Temperature, (177 Degree C.)
MIL-T-5796	Transmitter, Pressure, Oil, 0-100 PSI
MIL-A-8625	Anodic Coatings, For Aluminum And Aluminum Alloys
MIL-S-20708	Synchros, General Specification For
MIL-T-25624	Transmitter, Pressure TRU-80/A, Oil Engine-Mounted, 0-100 PSI
MIL-B-27497	Bearing, Jewel, Sapphire, Or Ruby, Synthetic

STANDARDS

FEDERAL

FED-STD-595	Colors

MILITARY

MIL-STD-100	Engineering Drawing Practices
MIL-STD-129	Marking For Shipment And Storage
MIL-STD-130	Identification Marking Of US Military Property
MIL-STD-454	Standard General Requirement For Electronic Equipment
MIL-STD-461	Electromagnetic Emission And Susceptibility Requirements For The Control Of Electromagnetic Interference
MIL-STD-462	Electromagnetic Interference Characteristics, Measurement Of
MIL-STD-781	Reliability Testing For Engineering Development, Qualification And Production
MIL-STD-785	Requirements Program For Systems And Equipments Development And Production
MIL-STD-810	Environmental Test Methods & Engineering Guidelines
MIL-STD-889	Dissimilar Metals
MIL-STD-970	Standards And Specifications, Order Of Preference For The Selection Of
MIL-STD-2073-1	DOD Material Procedures For Development & Application Of Packaging Requirements
MS28005	Transmitter, Pressure, Synchro, Aircraft
MS28010	Indicators, Pressure-Synchro, Single, 2-Inch Size
MS33558	Numerals And Letters, Aircraft Instrument Dial, Standard Form Of
MS33585	Pointer, Dial, Standard Design Of Aircraft Instrument
MS33678	Connector, Receptacle, Electric, Integral Mounting

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:04Z
Check the source to verify that this is the current version before use.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available form the Standardization Document Order Desk, 700 Robbins Ave, Building #4, Section D, Philadelphia, PA 19111-5094).

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

AF Drawing P/N 8988994

(Copies of this drawing are available from OC-ALC/TILDOE, Tinker Air Force Base, OK 73145-5990).

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Qualification. The indicators furnished under this specification shall be products which are qualified for listing on the applicable Qualified Products List at the time set for opening of bids (see 4.4 and 6.3).

3.2 Selection of specifications and standards. Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-970.

3.3 Materials.

3.3.1 Nonmagnetic materials. Nonmagnetic materials shall be used for all parts of the indicator except where magnetic materials are essential.

3.3.2 Nonferrous materials. Nonferrous materials shall be used for all parts of the indicator except where ferrous materials are essential.

3.3.3 Recovered materials. Recovered materials shall be used to the maximum extent possible without jeopardizing the end use of the item.

3.3.4 Metals. Metals shall be corrosion-resistant or suitably treated to resist corrosion due to fuels, salt fog, or atmospheric conditions likely to be met in storage or normal service.

3.3.5 Dissimilar metals. Unless suitably protected against electrolytic corrosion, dissimilar metals shall not be used in intimate contact with each other. Dissimilar metals are defined in MIL-STD-889.

3.3.6 Toxic and corrosive fumes. The indicator shall be of such material and construction that, when burned, corrosive, deleterious or toxic fumes and gases that combine with the atmosphere to form acid or corrosive alkali will not be liberated.

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:04Z
Check the source to verify that this is the currentversion before use.

3.3.7 Protective treatment. When materials are used in the construction of the indicator that are subject to deterioration when exposed to climatic and environmental conditions likely to occur during service usage, they shall be protected against such deterioration in a manner that will in no way prevent compliance with the requirements of this specification. The use of any protective coating that will crack, chip, or scale with age or extremes of climatic and environmental conditions shall be avoided.

3.3.8 Bearing, synthetic. When sapphire or ruby synthetic bearings are used, they shall be in accordance with MIL-B-27497.

3.4. Design and construction. The indicator shall be designed for use with a TRU-80/A transmitter in accordance with MIL-T-25624, MIL-T-7748, or MS28005 transmitter in accordance with MIL-T-5796.

3.4.1 Case. The case shall be hermetically sealed and the dimensions shall conform to MS28010.

3.4.1.1 Cap. A separate nonhermetically sealed cap may be used on the back of the case for installing the electrical receptacle. The cap shall be made of nonferrous, low-density metal.

3.4.1.2 Case to cover glass distance. The distance between the outer surface of the cover glass and the front edge of the case shall be minimum practicable and shall not exceed 0.031 inch.

3.4.1.3 Filling medium. The filling medium shall be of at least 98 percent purity, free of dust particles, and shall contain no more than 0.006 milligram of water vapor per liter (dewpoint -65°C) at the filling pressure. The absolute pressure of the filling medium in the case shall be 12 to 14.7 psi. A absolute other concentrations of filling medium shall not be used except with prior approval of the procuring activity. The filling medium shall be of 88 to 92 percent nitrogen and the remainder helium (refer to the previous revision of this MIL-SPEC).

3.4.2 Pointer. The pointer shall be in accordance with MS33585, except that the length of the pointer shall be such that the tip will extend into the scale a distance equal to one to two-thirds the length of the shortest graduation.

3.4.2.1 Pointer finish. The shaded portion of the pointer shall be finished as follows:

MS28010-2 Fluorescent Luminescent Material in accordance with AF8988994.

MS28010-8 Lusterless white color number 37875 in accordance with FED-STD-595.

3.4.3 Dial. The dial shall conform to FIGURE 1. A minimum diameter of 1.75 inches shall be maintained across the outside ends of the graduations. The 30 pounds per square inch (psi) graduation shall be located on the horizontal centerline at the left side of the dial.

3.4.3.1 Dial markings. Dial marking dimensions shall be as specified in TABLE I and shall be finished as follows:

MS28010-2 Fluorescent luminescent material in accordance with AF8988994.

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:04Z
Check the source to verify that this is the current version before use.




FIGURE 1. Dial.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:04Z
Check the source to verify that this is the current version before use.

MS28010-8 Lusterless white color number 37875 in accordance with FED-STD-595.

3.4.3.1.1 MS part number and dial background. The applicable MS part number shall be permanently and legible marked on the dial in letters 0.06 inch high. Location is optional. Unless otherwise specified, these markings and the background of the dial shall be finished in color No. 37038 of FED-STD-595.

TABLE I. Dial markings.

	Height or length (inch ±/64)	Width of line or graduation (inch ±0.005)
Numerals 0, 20, 40, 60, 80, and 100	0.16	0.025
10-pound graduations	0.19	.031
Graduation at 50 psi	0.14	.031
Lettering OIL PRESS.	0.12	.025
Lettering PSI 0.12		.025
5-pound graduations	0.93	.020

3.4.3.2 Dial visibility. Portions of the minor graduations on the dial shall be visible when viewed from any position within the frustum of a cone the side of which intersects the outer edge of the cover glass and which makes an angle of 30 degrees with the perpendicular through the center of the dial.

3.4.3.3 Dial to cover glass distance. The distance between the indicator dial and the inside of the cover glass shall be the minimum practicable and shall not exceed 0.125 inch.

3.4.4 Filler tube. A tube or other facility for evacuating and filling the case shall be provided at the rear of the case and shall be recessed beneath the level of the back plate surface. If a tube is used it shall be of such length as to permit three refillings of the case.

3.4.5 Cover glass. The cover glass shall be clear, flat, and free from flaws that would interfere with the normal reading of the instrument. The thickness of the cover glass shall be the minimum practicable and entirely suitable for the purpose.

3.4.6 Fasteners. The dial shall be securely fastened to the frame of the mechanism in such a manner that it will not loosen or turn when the indicator is vibrated. If screws are used for attaching the dial, they shall be so located in the proper position.

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:04Z
Check the source to verify that this is the current version before use.

3.4.7 Electrical zero reference mark. The dial shall be provided with an electrical zero reference mark on the scale portion equidistant in angular degrees between the first and last dial graduations.

3.4.8 Electrical connector. The indicator shall be provided with an electrical connector conforming to MS33678-14S-2P, or equal, and shall be hermetically sealed. The electrical connector shall have the polarizing key at the top.

3.4.9 Electrical wiring. The external wiring of the indicator shall be in accordance with FIGURE 2.

3.4.10 Indicator synchro. The indicator synchro shall consist of a salient two-pole wound rotor used as the primary and shall be designed for 26V, 400 Hz, as required, single-phase power, with wye-connected stators as the secondaries. The stators shall be so would that the amplitudes of the induced voltages measured between any two stator leads will vary approximately sinusoidally with the angular positions of the rotor. Pivots, bearings, and gears shall not bind nor shake and shall be as nearly frictionless as possible.

3.4.10.1 Synchro electrical characteristics. The synchro receiver used shall have electrical characteristics compatible with those in MIL-S-20708.

3.4.10.2 Secondary voltage. The maximum open-circuit voltage measured between any two secondary leads shall be 11.8V ±3 percent.

3.4.11 Voltage and frequency variations. The indicator shall with stand voltage and frequency variations from 22V to 30V and 380 Hz to 420 Hz, without exceeding the scale error and friction tolerances (see 3.5.1 ad 3.5.2).

3.4.12 Electromagnetic interference. The indicator shall meet the radiated and conducted electromagnetic interference requirements of MIL-STD-461 for class ID equipment.

3.4.13 Reliability program. The contractor shall establish a reliability program in accordance with MIL-STD-785.

3.4.13.1 Reliability. The indicator shall have a minimum acceptable mean-time-between-failures (MTBF) of 2,000 hours based upon a discrimination ratio of 1.5 and a confidence factor of 90 percent.

3.4.14 Longevity. The indicator shall have an operating life span of 3,000 hours.

3.5 Performance. The indicator shall operate satisfactorily after subjection to the following conditions:

a. Temperatures - temperatures ranging from -65° to +71°C

b. Vibration - vibration of 2g's from 5 to 500 Hz

c. Temperature - altitude-pressure altitude of 100,000 feet at -55°C

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:04Z
Check the source to verify that this is the currentversion before use.

d. Thermal shock - eight cycles of alternate immersions in tap water at 85° ± 2°C and 5° ± 2°C

e. Salt fog - exposure to salt sea atmosphere for 48 hours without evidence of corrosion of deterioration.

3.5.1 Scale error. Scale error shall not exceed the tolerances specified in TABLES II and III.

TABLE II. Tolerances - scale error.

PSI	Tolerances ± psi
0	1.0
20	1.0
40	1.0
60	1.0
80	1.0
100	1.0

TABLE III. Test tolerances.

Test	Tolerance ± psi
Position error at midscale	1.0
Friction	
Room temperature	1.0
High temperature	1.0
Low temperature	1.0
Vibration	
Pointer oscillation	1.0
Pointer variation	1.0
Scale error	
Low temperature	1.0
High temperature	

3.5.2 Friction error. Friction error shall not exceed the tolerances specified in TABLE III.

3.5.3 Position error. Position error shall not exceed the tolerance specified in TABLE III.

3.5.4 Dielectric strength. The indicator shall withstand 200V rms at a commercial frequency for a period of 5 seconds.

3.5.5 Case leakage. Case leakage shall not exceed 0.1 micron cubic foot per hour.

3.5.6 Fogging. There shall be no evidence of moisture or fogging of the cover glass when the

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:04Z
Check the source to verify that this is the current version before use.

indicator is subjected to a temperature of 85° ±5°C for a minimum period of 2 hours and then the face of the cover glass immediately immersed in an ice bath for 3 minutes.

3.5.7 Effect of lead length. When the lead length between the indicator and transmitter is changed from 5 to 500 feet, the indicator shall not change more that 1 degree of arc. The ground lead shall be kept short.

3.5.8 Magnetic effect. Compass deflection shall not exceed 3 degrees of arc when the indicator is positioned 5.5 inches from the compass and the horizontal magnetic field intensity at the indicator is 0.17 to 0.19 oersted.

3.5.9 Unit torque gradient. The unit torque gradient shall be a minimum of 2,000 milligram-millimeters per angular degree of rotation.

3.6 Part numbering of interchangeable parts. All parts have the same manufacturer's part number shall be functionally and dimensionally interchangeable. The item identification and part number requirements of MIL-STD-100 shall govern the manufacturer's part numbers and changes thereto.

3.7 Numerals and letters. Numerals and letter shall conform to MS33558.

3.8 Finishes and protective coatings.

3.8.1 Aluminum alloy parts. Aluminum alloy parts shall be coated with anodic film conforming to MIL-A-8625 except that small holes, straight threads, and case inserts need not be anodized.

3.9 Weight. The weight of the indicator shall not exceed 0.60 pound.

3.10 Screw threads. Unless otherwise specified, the threads of all machine screws shall conform to MIL-S-007742.

3.11 Identification of product. Equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130.

3.11.1 Nameplate. A nameplate shall be permanently attached to the rear of the case. Where applicable, the information marked thereon shall conform to MIL-STD-130. The nameplate shall not be glued or cemented to the case nor shall metal decals be used.

3.12 Workmanship. The indicator shall be constructed and finished in a thoroughly workman like manner in accordance with MIL-STD-454. Particular attention shall be given to neatness and thoroughness of soldering, wiring, impregnation of coils, welding, riveting, brazing, plating, painting, machine screw assemblies, and freedom of parts from burrs and sharp edges. Gears shall be of high quality and shall provide a minimum of backlash necessary for smooth operation. Where necessary, antibacklash techniques shall be used.

4. QUALITY ASSURANCE PROVISIONS

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:04Z
Check the source to verify that this is the current version before use.

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contract may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system of quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Qualification inspection (4.4)
(b) Quality conformance inspection (4.5)

4.3 Inspection conditions. Unless otherwise specified, all inspection shall be performed in accordance with the test conditions specified in 4.3.1 in the specification.

4.3.1 Standard atmospheric conditions. Wherever the pressure and temperature existing at the time of the test are not specified definitely, it is understood that the test is to be made at atmospheric pressure (approximately 29.92 inches Hg.) and at room temperature (approximately 25°C). When tests are made with atmospheric pressure or room temperature differing materially from the above values, proper allowance shall be made for the difference from the specified condition.

4.3.2 Attitude. Unless otherwise specified, the indicator shall be tested in the normal operation position with the plane of the dial vertical.

4.3.3 Electrical power. Unless otherwise specified, the indicator shall be tested with 26+1V, single-phase, 400+5 Hz, or any combination thereof.

4.3.4 Voltage and frequency variation. When performing the scale and friction error tests specified in 4.6.4, the voltage and frequency variation shall be from 22V to 30V and 380 Hz to 420 Hz, or any combination thereof.

4.3.5 Tapping. Unless otherwise specified, the indicator shall be lightly tapped or vibrated before each reading.

4.3.6 Test tolerances. The indicator shall be operated within the tolerances specified in TABLES II and III.

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:04Z
Check the source to verify that this is the currentversion before use.

4.4 Qualification inspection. The qualification inspection shall consist of the examination and tests specified in 4.6.

4.4.1 Test samples. The test samples shall consist of 10 indicators representative of the production equipment. The samples shall be identified with the manufacturer's part number and such other information as required (see 6.2 and 6.3. Seven of the samples shall be subjected to the individual tests (see 4.5.1) and the reliability test (see 4.6.21), and the other three shall be subjected to all the tests except reliability.

4.4.2 Nonstandard parts data approval. When nonstandard electronic parts are used in the construction of the indicator, nonstandard parts data approval shall be a prerequisite to qualification approval.

4.5 Quality conformance inspection. Quality conformance inspection shall consist of the following:

(a) Individual tests	(4.5.1)
(b) Sampling tests	(4.5.2)

4.5.1 Individual tests. Each indicator shall be subjected to the following examination and tests:

(a) Examination of product	(4.6.1)
(b) Dielectric strength	(4.6.2)
(c) Electrical zero	(4.6.3)
(d) Scale and friction error	(4.6.4)
(e) Position error	(4.6.5)
(f) Sealing	(4.6.6)

4.5.2 Sampling tests.

4.5.2.1 Sampling plan A. One indicator shall be selected at random, from each 100 or less produced on the contract or order, and subjected to the following tests:

(a) Individual tests	(4.5.1)
(b) Vibration	(4.6.7)
(c) Low temperature	(4.6.8)
(d) High temperature	(4.6.9)
(e) Fogging	(4.6.10)

4.5.2.2 Sampling plan B. Unless otherwise specified (see 6.2), three indicators shall be selected at random from the first 15 on the contract or order and subjected to the following tests:

(a) Sampling plan A tests	(4.5.2.1)
(b) Secondary voltage	(4.6.11)
(c) Magnetic effect	(4.6.12)
(d) Effect of lead length	(4.6.13)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:04Z
Check the source to verify that this is the current version before use.

(e) Temperature-altitude	(4.6.14)
(f) Low temperature exposure	(4.6.15)
(g) High temperature exposure	(4.6.16)
(h) Thermal shock	(4.6.17)
(i) Salt fog	(4.6.18)
(j) Electromagnetic interference	(4.6.19)
(k) Unit torque gradient	(4.6.20)

4.5.2.3 Rejection and retest. When one item selected from a production run fails to meet the specification, no items still on hand or later produced shall be accepted until the extent and cause of the failure have been determined and appropriately corrected.

4.5.2.4 Individual tests may continue. For operational reasons, individual tests may be continued pending the investigation of a sampling test failure. But final acceptance of items shall meet all the requirements of the specification.

4.5.3 Defects in items already accepted. The investigation of a test failure could indicate that defects may exist in items already accepted. If so, the contractor shall fully advise the procuring activity of all defects likely to be found and methods of correcting them.

4.6 Test methods.

4.6.1 Examination of product. The indicator shall be inspected to determine compliance with this specification with respect to materials, workmanship, and dimensions. Prior to assembly, dials, pointers, and synchros shall be inspected as to markings, dimensions, and finishes.

4.6.2 Dielectric strength. A potential of 200V at a commercial frequency shall be applied between any pin of the electrical receptacle and the case of the indicator for a minimum period of 5 seconds. There shall be no breakdown of the insulation.

4.6.3 Electrical zero. The electrical zero test and the verification of leads shall be accomplished on the completed indicator with the case removed. A voltage of 26+1V single phase shall be applied to the rotor of the synchro with leads designated R_1 and R_2. R_2 shall be connected to the ground or low potential side of the power input. With a lead designated S_2 connected to R_2, the following conditions shall exist at electrical zero:

(a) The voltage between the remaining stator terminals designated S_1 and S_3 shall be minimum.
(b) The voltage between R_1 and S_3 shall be near the low null and shall reach the low null when rotor is rotated clockwise approximately 30 degrees from electrical zero.

4.6.4 Scale and friction error. The indicator shall be tested for scale error at ambient temperature at the test points specified in TABLE II. The indicator shall be lightly tapped or vibrated before each reading to remove normal instrument friction. The scale error shall not exceed the tolerances specified in TABLE III. The friction error test may be conducted in conjunction with the scale error test. The difference

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:04Z
Check the source to verify that this is the current version before use.

between the readings before and after the indictor is tapped or vibrated shall constitute friction error. The friction error shall not exceed the tolerances specified in TABLE III. This procedure shall be accomplished both up-scale and down-scale at the test points specified.

4.6.5 Position error. The indicator pointer shall be positioned at the electrical zero reference mark with power applied. The change in pointer position when the indicator is held in any position shall not exceed the value specified in TABLE III.

4.6.6 Sealing. The indicator case shall be tested for leaks by means of a mass-spectrometer-type helium leak detector. The detected leak rate shall not exceed 0.1 micron cubic foot per hour at a pressure differential of 1 atmosphere.

4.6.7 Vibration. The indicator shall be subjected to a vibration test in accordance with MIL-STD-810, Method 514.2, equipment category b.1, procedure 1, curve B. Use curve B from 5(HZ) line to the horizontal axis. A synchro signal shall be maintained on the stators of the indicator synchro to provide an indication of 45 psi. The pointer oscillation shall not exceed ±1 psi and pointer variation shall not exceed ±1 psi (see TABLE III. Upon completion of this test, the indicator shall be subjected to the scale error test at room temperature. The scale errors shall not exceed the tolerances specified in TABLE III.

4.6.8 Low temperature. The indicator shall be subjected to a temperature of -55° ±2°C for a period of 4 hours. While at this temperature, it shall be checked for friction and scale errors and shall not exceed those specified in TABLE III. In every case, the indicator shall not require more than 3 seconds to come within the tolerance specified.

4.6.9 High temperature. The indicator shall be subjected to a temperature of 71°C for a period of 4 hours. While at this temperature, it shall be checked for friction and scale errors. The scale and friction error tolerances shall not exceed the values specified in TABLE III. In every case, the indicator shall not require more than 3 seconds to come within the tolerance specified.

4.6.10 Fogging. The indicator shall be placed in a controlled ambient temperature of 85° ±5°C for a minimum period of 2 hours. Within 10 seconds after removal from the chamber, the indicator shall be immersed to a depth of 0.25 inch in an ice water bath maintained at 0° to 7°C. After 3 minutes, the indicator shall be removed from the fluid bath and quickly wiped dry (compressed air shall not be used). The cover glass and dial shall immediately be inspected and any evidence of fogging or damage shall be cause for rejection.

4.6.11 Secondary voltage. The maximum open-circuit voltage shall be measured between any two secondary leads and shall be 11.8V +3 percent. The variation between the three maximum secondary voltages on the indicator synchro as measured between any two stator leads shall not exceed 0.2V.

4.6.12 Magnetic effect. The indicator, first, not operating and second, operating on rated voltage, shall be rotated in a vertical plane about a short bar magnet compass with the nearest part of the indicator 5.5 inches from and magnetically east or west of the center of the compass. Starting directly under the compass, the indicator shall be held in positions 0, 45, 90, 135, 180, 225, 270, and 315 degrees from the initial position. At each of these positions, the indicator shall be rotated on its own horizontal axis until it

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:04Z
Check the source to verify that this is the current version before use.

is in its normal upright position. The horizontal magnetic field intensity shall be 0.17 to 0.19 oersted. Deflection of the compass at any of the specified positions shall not exceed 3 degrees.

4.6.13 Effect of lead length. The indicator shall not change more than 1 degree of arc when the lead length between the indicator and transmitter is changed from 5 to 500 feet of No. 20 AWG gage wire. Equivalent resistances may be substituted for the added wire length. The ground lead shall be kept short.

4.6.14 Temperature-altitude. The temperature-altitude test shall be performed in accordance with MIL-STD-810, Method 504.1, Procedure I (except the temperature shall be -55°C with a chamber pressure equivalent to an altitude of 100,000 feet. The rate of pressure change shall not exceed an average of 3 psi per second while under these conditions. At the end of a 1-hour period, the scale and friction error test shall be performed. The errors shall not exceed the tolerances specified in TABLE III. This test may be performed concurrently with the low temperature exposure test (see 4.6.15).

4.6.15 Low temperature exposure. The indicator shall be subjected to a temperature of -65° ±2° for a period of 48 hours. While at this temperature, the indicator shall be operated to assure that the pointer moves over the entire scale range without exhibiting sticky or erratic characteristics. The temperature shall then be raised to -55° ±2C and held for a period of 24 hours. While at this temperature, the indicator shall be subjected to the scale error an friction test, except that in every case, the indicator shall not require more than 4 seconds to come within the tolerances of TABLE III. All parts of the indicator shall then be maintained at room temperature for a period of not less than 4 hours and the indicator again subjected to the scale error and friction test. The scale errors shall not exceed the tolerances specified in TABLE II. There shall be no damage or deterioration that will affect subsequent operation.

4.6.16 High temperature exposure. The indicator shall be subjected to a temperature of 70° ±2°C for a period of 24 hours and then tested at this temperature for scale errors as specified in 4.6.4. The scale error and friction shall not exceed the tolerance specified in TABLE III. All parts of the indicator shall then be maintained at room temperature for a period of not less than 4 hours and the indicator again subjected to the scale error and friction test. The scale errors observed shall not exceed the tolerances specified in TABLE III. There shall be no damage or deterioration that might affect subsequent operation.

4.6.17 Thermal shock. The indicator shall be subjected to eight cycles of immersion in water at a temperature of 85° ±2C and then in water at a temperature of 5° ±2°C without evidence of moisture penetration or damage to the coating or the case. The length of time for each immersion shall be 30 minutes, with not more than 5 seconds between immersions. After eight continuous cycles have been completed, the indicator shall be subjected to the test specified in 4.6.6.

4.6.18 Salt fog. The indicator shall be subjected to a salt fog test for a period of 48 hours in accordance with MIL-STD-810, Method 509.1, Procedure I. There shall be no corrosion or deterioration that might affect subsequent operation. After exposure to salt fog, the indicator shall be subjected to the tests specified in 4.6.4 and 4.6.6.

4.6.19 Electromagnetic interference. The indicator shall be subjected to an electromagnetic interference test in accordance with MIL-STD-462. The test methods shall be as specified in MIL-STD-461 for class ID equipment.

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:04Z
Check the source to verify that this is the current version before use.

4.6.20 Unit torque gradient. The indicator shall be connected to the master transmitter synchro and the master transmitter locked in the electrical zero position. The synchro rotors shall then be energized with rated voltage and frequency ±1 percent. Weights shall be applied to a torque pulley which is positioned on the rotor shaft to rotate the shaft in a counterclockwise direction through an angle of 5 degrees of use. The torque tending to return the shaft to its original position shall be computed and shall be no less than 2,000 milligram-millimeters per degree of displacement.

4.6.21 Reliability. Seven indicators shall be tested for reliability. Acceptance permitting production and total test time shall be in accordance with MIL-STD-781, test plan I. Recording, data handling, and reporting shall also be in accordance with MIL-STD-781.

4.6.21.1 Test. The equipment and fixtures shall include provisions for vibration and temperature cycling at the periodic intervals specific herein. During this test, input signals shall be applied to the indicator at a rate of 2 to 3 cycles (minimum and maximum) per minute from 0 to 85 percent of full scale and return. The test shall begin when rated power is applied. After completion of 4 hours of operation with rated power on, which shall include at least 480 cycles of operation, the power shall be turned off and shall remain off for a period of 10 minutes. For at least 10 minutes out of every hour of On time, the indicator shall be vibrated in accordance with test level J of MIL-STD-781. The temperature cycles shall be performed in the following sequence: 4 hours at -20°C, 14 minutes for temperature change to ±50°C at a minimum rate of 5°C per minute; 4 hours at ±50°C, 14 minutes for temperature change to -20°C and 4 hours at 20°C. In case of malfunction, the malfunction shall be recorded and the test interrupted while repairs are made. Upon completion of each 250 hours of cycling, the indicator shall be checked for scale error. The scale error reading shall not exceed 150 percent of the room temperature tolerance in TABLE III. No recalibration shall be performed on the units during this test. The test may be interrupted for weekend shutdown. The contractor shall prepare a report in accordance with MIL-STD-781 which shall contain test procedures, details of any malfunctions, and corrective actions taken.

4.6.22 Longevity. At the completion of the reliability test, testing of three of the indicators shall be continued for a total of 3,000 hours each. The test time accumulated during the reliability test shall be applied to this test. The accept-reject criteria is not applicable.

4.7 Inspection of packaging. Except when commercial packaging is specified, the sampling and inspection of the preservation and interior package marking shall be in accordance with groups A and B quality conformance inspection requirements of MIL-P-116. The sampling and inspection of the packing for shipment and storage shall be in accordance with the quality assurance provisions of the applicable container specification shown in section 5. The inspection of marking for shipment and storage shall be in accordance with MIL-STD-129. The inspection of commercial packaging shall be as specified in the contract (see 6.2).

5. PACKAGING.

5.1 Preservation. Preservation shall be level "A" or "C", as specified. (see 6.2)

5.1.1 Preservation-packaging. Unless otherwise specified by the contracting activity, item shall be packaged in quantity unit pack (QUP) of one each. Each item will be provided a preservation method IA-8 IAW MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:04Z
Check the source to verify that this is the current version before use.

5.1.2 Cleaning. Item shall be cleaned IAW MIL-P-116 C-1 process.

5.1.3 Drying. Immediately after cleaning, the item shall be dried following any one of combination of the drying procedures listed in MIL-P-116. The drying procedures employed shall not be injurious to the item.

5.1.4 Level A. Item shall be preserved IAW MIL-P-116 and MIL-STD-2073-1 to provide a method IA-8.

5.1.5 Level C. Item shall be individually preserved in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from the supply source to the first activity as specified in MIL-P-116 and MIL-STD-2073-1.

5.2 Packing. Packing shall be level "A", "B", or "C", as specified (see 6.2).

5.2.1 Container-cushioning. Unit container requirements shall conform to MIL-B-131, barrier material, unless otherwise specified by the contracting activity. Unit containers shall be large enough to allow for application of sufficient cushioning/wrap material between the item and unit container to protect the unit container from punctures. Intermediate container requirements shall conform to PPP-B-636, weather-resistant, unless otherwise specified by the contracting activity. Intermediate containers shall be large enough to allow for application of sufficient cushioning material, between the unit container and intermediate container. Cushioning material shall be of sufficient density and thickness to insure shock transmission does not exceed peak values in G's established for the item.

5.2.2 Level A. Item will be preserved as specified in 5.1 and shall be packed in exterior containers conforming to PPP-B-636, weather-resistant, unless otherwise specified by the contracting activity. Exterior container shall be uniform shape, size and minimum tare and cube, consistent with the protection required. Closure shall be in accordance with appropriate PPP-B-636 procedures, as specified by the contractor, special packaging instructions (SPI), and contracting activity.

5.2.3 Level B. Same as Level "A" unless otherwise specified by special packaging instructions (SPI) or the contracting activity.

5.2.4 Level C. Item will be packed in containers in such a manner as to afford adequate protection against physical damage during direct domestic shipment from the supply source to the first receiving activity. These packs shall conform to MIL-STD-2073-1.

5.3 Marking. Unit, intermediate, and exterior containers shall be marked IAW special markings required by the contractor, special packaging instructions (SPI) and MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The indicator covered by this specification is intended for use in conjunction with the

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:04Z
Check the source to verify that this is the current version before use.

TRU-80/A or an MS28005 oil pressure transmitter in indicating remotely the oil pressure in aircraft systems which require integrally lighted instruments.

6.2 Acquisition requirements. Acquisition documents must specify the following:

(a) Title, number, and date of this specification.

(b) Information, if any, to be submitted with qualification samples (4.4.1).

(c) When sampling plan B tests will not be conducted (4.5.2.2).

(d) Levels of packaging and packing required, and reinspection date markings (see section 5).

(e) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1).

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are at the time set for opening of bids, qualified for inclusion in the applicable Qualified Products List whether or not such products have actually been so listed by that date. The attention of the suppliers is called to this requirement, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. The activity responsible for the Qualified Products List is Oklahoma Air Logistics Center/TICLA, Tinker Air Force Base, OK, 73145-5990, and information pertaining to qualification of products may be obtained from that activity.

6.4 Subject term (key word) listing.

Hermetically sealed
Oil Pressure
Indicator synchro-style.

6.5 International standardization agreement. Certain provisions (3.3.3 and FIGURE 1) of this specification are the subject of international standardization agreement ASSCC 10/2B. When amendment, revision, or cancellation of this specification is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
AIR FORCE -99
ARMY -AV
NAVY -AS

Preparing Activity:
AIR FORCE -71

Project number:
6620-0498

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-I-7086C	2. DOCUMENT DATE (YYMMDD) 94/12/30

3. DOCUMENT TITLE
INDICATOR, PRESSURE, OIL, 0-100PSI

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME OC-ALC/TICLA	b. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON 336-5980
c. ADDRESS (Include Zip Code) 3001 Staff Dr Tinker AFB, OK 73145-5990	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

Source: https://assist.dla.mil -- Downloaded: 2026-04-17T08:04Z
Check the source to verify that this is the current version before use.