INCH-POUND

MIL-I-7087A
AMENDMENT 3
30 MARCH 1994
SUPERSEDING
AMENDMENT 2
7 NOVEMBER 1986

MILITARY SPECIFICATION

INDICATOR, PRESSURE, OIL, 0-200 PSI

This amendment forms part of MIL-I-7087A, dated 15 November 1968, and is approved by all Departments and Agencies of the Department of Defense.

PAGE 1

Delete "2.1" entirely and add: "2.1 Government documents."

Add "2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards(DODISS) and supplement thereto, cited in the solicitation(see 6.2)."

* Under SPECIFICATIONS, Federal, delete "L-P-378", "PPP-B-676": "PPP-C-843" entirely and addd: "PPP-B-1672 Boxes, Shipping, Reusable with Cushioning".

* Under SPECIFICATIONS, Military, add: "MIL-B-121 Barrier Material, Greaseproofed Waterproofed, Flexible".

* Under STANDARDS, Federal, delete "FED.STD.595 Colors" and add: "FED-STD-101 Preservation, Packaging and Packing Materials: Test Procedures" and "FED-STD-595 Colors".

Under STANDARDS, Military change "DOD-STD-100" to "MIL-STD-100". Change "MIL-STD-143" to "MIL-STD-143".

Add boxed paragraph at bottom of page one:

Benificial comments(recommendations, additions, deletions) and any pertinent data which may be of use in improving the document should be addressed to Oklahoma City Air Logistics Center/TICLA, Tinker AFB, OK 73145-5990 by using the Standardization Document Improvement Proposal(DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENTA. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:05Z
Check the source to verify that this is the current version before use.

PAGE 2

* Under STANDARDS, Military delete: "MIL-STD-794", "MIL-STD-831", "MS33586" entirely and add: "MIL-STD-889 Dissimilar Metals" and "MIL-STD-0073-1 DOD Material Procedure For Development And Application Of Packaging Requirements."

* Delete the following parenthetical source statement entirely and add new:

"(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Stadardization Document Order Desk, 700 Robbins AVE, Building #4 , Section D, Philadelphia, PA 19111-5094)."

* Add: "2.2. *Order of precedence. In the event of a conflict between the text of this document and the* references cited herein (except for related associated detail specifications, specification sheets, or MS standards), the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a spceific exemption has been obtained."

* 3.2 Line 3 delete "MIL-STD-143" and add: "MIL-STD-970".

Add: "3.3.2.1 Recovered materials. Recovered materials shall be used to the maximum extent possible without jeopardizing the end use item."

* Add: "3.3.2.1 Cadmium. Cadmium is not to be used in the indicator unless appproved by the preparing activity. There shall be no cadmium used on the outside case of the indicator.

* 3.3.4 Line 3 delete "MS33586" and add: "MIL-STD-889".

PAGE 3

* 3.4.1.2 Line 3 delete "1/32" and add: "0.0313".

* 3.4.2.1 Line 2 delete "Federal Standard No. 595" and add: "FED-STD-595".

* Under TABLE I. Height or lenght delete "1/64", "5/32", "3/16", "9/64", "3/32", "1/8", "1/8" , and add: "0.16", "0.156", "0.188", "0.141", "0.094", "0.125" and "0.125".

* 3.4.3.1.1 Line 2 delete "1/16" and "0.0625". Line 4 delete "Federal Standard No. 595" and add: "FED-STD-595".

PAGE 6

* FIGURE 2 Label wires corresponding to pins B, C , D, and A: "(S1)", "(S3)", "(R1)" and "S2, R2)". Add: "NOTES:"

Source: https://assist.dla.mil -- Downloaded: 202610-17T08:05Z
Check the source to verify that this is the current version before use.

1. Pin C-A-D Phase Sequence Produces CW Indicator Rotation.
2. Transmitter AT Electrical Zero Per MIL-T 5350 = INDICATOR AT MID - SCALE.

PAGE 8

* 3.5.8 Line 2 delete "5-1/2" and add: "5.5".

PAGE 9

* Delete "4.1" entirely and add new:

4.1 Responsiblity for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and test) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

Add: "4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of know defective material, either indicated or actual, nor does it commit the Government to accept defective material."

* 4.4.2 Delete entirely.

* 4.5.1 Line 5 delete entirely.

* 4.6.13 Line 3 delete "sustained" and add: "substituted".

* 4.6.21 Line 3 delete " test Plan I" and add: test plan 1C".

* 4.6.21.1 Line 9 delete "with level J o MIL-STD-781" and add: with Table I (For transport, Bomber application) of MIL-STD-781."

* Delete section "5" entirely and add new:

"5". PACKAGING

5.1 Preservation. Preservation shall be level "A" or "C" as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:05Z
Check the source to verify that this is the current version before use.

5.1.1 Preservation-packaging. Unless otherwise specified by the contracting activity, item shall be packaged in Quantity Unit Pack (QUP) of one each. Each item shall be provided a preservation method IC-1 In Accordance With (IAW) MIL-P-116.

5.1.2 Cleaning. Item shall be cleaned IAW MIL-P-116 C-1 process.

5.1.3 Drying. Immediately after cleaning , the item shall be dried following any one or combination of the dryong procedures listed in MIL-P-116. The drying procedures employed shall not be injurious to the item.

5.1.4 Level A. Item shall be preserved IAW MIL-P-116 and MIL-STD-2073-1 to provide a method IC-1.

5.1.5 Level c. Item shall be individually preserved in a manner that will afford adequate protection against corrosion, deterioration, and physical damage during shipment from the supply source to the first receiving activity as specified in MIL-P-116 and MIL-STD-2073-1.

5.2 Packing. Packing shall be level "A", "B", or "C", as specified (see 6.2).

5.2.1 Container-cushioning. Unit container requirements shall conform to MIL-B-121, barrier material , unless otherwise specified by the contracting activity. Unit containers shall be large enough to allow for application of sufficient cushioning/wrap material, between the item and unit container. Item cushioning / wrap material shall be of sufficient density and thickness to protect the unit container from punctures. Intermediate / shipping containers shall be large enough to allow for application of sufficient cushioning material, between the unit container and intermediate/shipping container. Cushioning material shall be of sufficient density and thickness to insure shock transmission does not exceed peak vlues in G's established for the item.

5.2.2 Level A. Fiberboard containers do not meet Level "A" container criteria.

5.2.3 Level B. Item will be preserved as specified in 5.1 and shall be packed in exterior containers conforming to PPP-B-1672, weather-resistant unless otherwise specified by the contracting activity. Exterior container shall be uniform shape, size and minimum tare and cube, consistent with the protection required. Closure shall be in accordance with appropriate PPP-B-1672 procedures, as specified by Special Packaging Instructions(SPI), and contracting activity.

5.2.4 Level C. Item will be packed in such a manner that will afford adequate protection against physical damage during direct domestic shipment from the source of supply to the first receiving activity. These packs shall conform to MIL-STD-2073-1.

5.3. Marking. Unit, intermediate, and exterior containers shall be marked IAW special markings required by the contracting activity, SPI and MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:05Z
Check the source to verify that this is the current version before use.

5.4 Inspection and test. Test of methods of preservation shall be accomplished in accordance with section 4 of MIL-P-116 to insure compliance with section 5 of this specification. Packaging test shall be conducted IAW rough handling as specified in FED-STD-101."

6.3 Lines 8 and 9 delete "the Aeronautical Systems Division, Wright-Patterson Air Force Base, OH 45433" and add: "OC-ALC/TICLA, TINKER AFFB, OK 73145-5990".

Delete "6.4" entirely.

The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convience only and the Government assumes no liablity whatsoever for any inacurracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal nitations and relationship to the last previous amendment.

Custodians:
Air Force-99
Army -Av
Navy -AS

Preparing Activity:
Air Force-71
Project Number:
6620-0516

Source: https://assist.dla.mil -- Downloaded: 202640-17T08:05Z
Check the source to verify that this is the currentversion before use.