INCH-POUND

MIL-T-7099E
AMENDMENT 1
9 October 1998

MILITARY SPECIFICATION

TERMINAL, LUG AND SPLICE, CRIMP STYLE
ALUMINUM, FOR ALUMINUM AIRCRAFT WIRE

This amendment forms a part of MIL-T-7099E, dated 23 February 1979, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1: Delete “RR-S-366 Sieve, Test,” “MIL-P-116 Preservation, Methods of,” “MIL-W-7072 Wire, Electric, 600 Volt, Aluminum, Aircraft, General Specification For,” “FED-STD-151 Metals; Test Methods,” “MIL-STD-105 Sampling Procedures And Tables For Inspection By Attributes,” “MIL-STD-794 Part And Equipment, Procedures For Packaging Of.”

PAGE 3

Add as new paragraph:

2.3 Non-Government Publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the DoDISS cited in the solicitation. Unless otherwise specified, the issues of the documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR QUALITY CONTROL (ASQC)

ASQC-Z1.4 - Sampling Procedures and Tables for Inspection by Attributes. (DoD adopted)

(Application for copies should be addressed to the American Society For Quality Control, P.O. Box 3005, 611 East Wisconsin Avenue, Milwaukee, WI 53201-4606.)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:06Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-E11	-	Sieves, Wire Cloth, for Testing Purposes. (DoD adopted)
ASTM-B117	-	Salt Spray (Fog) Testing, Standard Test Method for. (DoD adopted)
ASTM-E323	-	Sieves, Perforated-Plate, for Testing Purposes. (DoD adopted)

(Application for copies should be addressed to the American Society For Testing and Materials, 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959.)

3.3 First sentence: Delete “Conforming to MIL-W-7072.”

3.3.3 Fourth sentence: Delete “RR-S-366” and substitute “ASTM-E11 and ASTM-E323.” Fifth sentence, delete “MIL-7072 wire.”

4.4.2.1: Delete and substitute:

4.4.2.1 Sampling for Examination. A random sample shall be selected from each inspection lot in accordance with table I, Inspection Level II, of ASQC-Z1.4 and subjected to the test specified in 4.6.1.

4.4.3.1: Delete and substitute:

4.4.3.1 Sampling for tests. A random sample shall be selected in accordance with table I of ASQC-Z1.4, once every 18 months from each lot of a given wire size and type. The inspection level shall be S-2. All provisions of ASQC-Z1.4 shall apply including acceptance numbers of one as specified in tables II-A and II-B.

4. 5.1: Third Sentence: Delete.

4.7.4.1: Delete and substitute:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:06Z
Check the source to verify that this is the current version before use.

4.7.4.1 Vibration. One end of the test specimen shall be mounted by clamping the terminal tongue not more than 1 inch above the vibrating member with a stable clamping device. The other end of the specimen shall be secured to a stable support external to the vibrating table with all slack or tension removed from the wire. Each test specimen shall be subjected to the test specified in 4.7.3 to determine the initial voltage drop prior to performance of this test. The specimens shall be vibrated in accordance with method 204A, condition B of MIL-STD-202 except that the cycle shall be performed 12 times in each of the two axis mutually perpendicular to each other and to the axis of the wire (a total of 24 times). Following this test, the specimens shall be tested for voltage drop (see 4.7.3).

4.7.4.4: First Sentence: Delete "Method 811 of Federal Standard No. 151" and substitute "ASTM-B117."

PAGE 14

5.1.1, 5.1.1.1, 5.1.1.2, 5.2, 5.2.1, 5.2.2, 5.3: Delete and substitute:

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of material is to be performed by DoD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the inventory control points packaging activity within the military department or defense agency, or within the military department's system command. Packaging data retrieval is available from the managing military department's or defense agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

PAGE 15

6.1: First sentence: Delete "Conforming to MIL-W-7072."

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:06Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - AS
Air Force - 85

Review Activities
Army - AV
Air Force - 11, 99
DLA - GS

Preparing activity:
Navy - AS

(Project 5940-1266)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T08:06Z
Check the source to verify that this is the current version before use.