MIL-C-11071D(ME)
25 February 1983
SUPERSEDING
MIL-C-11071C
26 November 1965

MILITARY SPECIFICATION

CLEANING MACHINE, FUEL CAN, DRUM

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a gasoline engine driven, portable cleaning machine used for removing contamination from the interior of 5 gallon cans and 55 gallon drums.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

P-D-680	- Dry-Cleaning Solvent.
QQ-S-781	- Strapping, Steel and Seals.
TT-E-529	- Enamel, Alkyd, Semigloss.
TT-P-636	- Primer Coating, Alkyd Wood and Ferrous Metal.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

FSC 4940

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

PPP-C-843	- Cushioning Material, Cellulosic.
PPP-C-1797	- Cushioning Material, Resilient, Low Density, Unicellular, Polypropylene Foam.
PPP-T-45	- Tape, Gummer, Paper, Reinforced and Plain for Sealing and Securing.

MILITARY

MIL-P-116	- Preservation, Methods of.
MIL-H-370	- Hose and Hose Assemblies, Nonmetallic Rubber, Liquid Fuel, Noncollapsible.
MIL-T-704	- Treatment and Painting of Materiel.
MIL-C-1283	- Can, Gasoline, Military, 5-Gallon.
MIL-P-3230	- Pumping Assembly, Flammable Liquid, Bulk Transfer, Centrifugal, 50 GPM - 100 Foot Head, Diesel Engine Driven.
MIL-E-10062	- Engines; Preparation for Shipment and Storage of.
MIL-T-22085	- Tape, Pressure-Sensitive, Adhesive, Preservation and Sealing.
MIL-P-23377	- Primer Coating, Epoxy Polyamide, Chemical and Solvent Resistant.
MIL-B-26195	- Box, Wood-Cleated, Skidded, Load-Bearing Base.
MIL-S-81733	- Sealing and Coating Compound, Corrosion Inhibitive.

STANDARDS

FEDERAL

FED-STD-595	- Colors.
FED-STD-H28/2	- Screw-Thread Standards for Federal Services, Unified Thread Form and Thread Series for Bolts, Screws, Nuts, Tapped Holes and General Applications.

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of U.S. Military Property.
MIL-STD-781	- Reliability Tests Exponential Distribution.
MIL-STD-889	- Dissimilar Metals.
MIL-STD-1186	- Cushioning, Anchoring, Bracing, Blocking and Waterproofing; with Appropriate Test Methods.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

MIL-STD-1188 - Commercial Packaging of Supplies and Equipment.

MIL-STD-1472 - Human Engineering Design Criteria for Military Systems, Equipment and Facilities.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

ME

TA13226E1250 - Cleaning Machine Assembly, Fuel Can and Drum.

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

J429 - Mechanical and Material Requirements for Externally Threaded Fasteners.
J492 - Rivets and Riveting.
J925 - Minimum Access Dimensions for Construction and Industrial Machinery.

(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.)

AMERICAN WELDING SOCIETY, INC. (AWS)

D1.1 - Structural Welding Code, Section 5, Qualification.

(Application for copies should be addressed to the American Welding Society, Inc., 2501 N.W. 7th Street, Miami, FL 33125.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

(Industry association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Description. The fuel can and drum cleaning machine shall consist of a 50 gpm pumping assembly, appropriate hose assemblies, sediment tanks, frame assembly and all other components needed to make a complete cleaning machine unit. The cleaning machine shall be in accordance with TA13226E1250 and as specified herein.

3.2 First article. When specified (see 6.2), the contractor shall furnish sample unit(s) for first article inspection and approval (see 4.3 and 6.4).

3.3 Materials. Material shall conform to the applicable specifications, drawings and requirements specified herein. Material not definitely specified shall be selected by the contractor and shall be subject to all the provisions of this specification. All materials shall be free from defects or imperfections which might affect the serviceability or appearance of the finished product (see 6.7).

3.3.1 Materiel deterioration and control. The cleaning machine shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the item may be exposed.

3.3.2 Dissimilar metals. Dissimilar metals, as defined in MIL-STD-889 shall be electrically insulated from one another to minimize galvanic corrosion. Insulation may be provided by a barrier such as a coat of epoxy primer conforming to MIL-P-23377 or corrosion inhibiting sealant conforming to MIL-S-81733 protection against any galvanic corrosion could also be obtained by exclusion of the electrolyte if feasible.

3.3.3 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with components and sub-components, and shall make information available, upon request, to the contracting officer or his/her designated representative.

3.4 Identical items. All cleaning machine units furnished under a specific contract shall be physically and mechanically identical, in that all parts, components, accessories, and subassemblies shall be interchangeable on all cleaning machine units. No deviation shall be acceptable without prior written approval from the contracting officer.

3.5 Reliability. The specified mean-time-between-failure (MTBF) shall be 114 hours when the cleaning machine is tested as specified in 4.5.2.6.

3.6 Maintenance ratio. The cleaning machine shall have a maintenance ratio of not more than 0.06. Maintenance ratio is defined as the ratio of the total

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

active maintenance man-hours required (scheduled and unscheduled) to the total operating time. Man-hours for repair of replaced components and scheduled before-and-after operation checks are excluded.

3.7 Components.

3.7.1 Pumping assembly, 50 gpm - 100-foot head. The 50 gpm - 100-foot head pumping assembly shall conform to MIL-P-3230.

3.7.2 Hoses, assemblies.

3.7.2.1 Hose, suction. Suction hose shall be type II, class 1, style A of MIL-H-370 in the size and length specified on the applicable drawings.

3.7.2.2 Hose, discharge. Discharge hose shall be type I, class 1, style A, of MIL-H-370 in the size and length specified on the applicable drawings.

3.7.2.3 Couplings, caps and plugs. The coupling halves, caps and plugs shall be of the type, size and class shown on the applicable drawings.

3.7.3 Fire extinguisher. Two fire extinguishers shall be provided for each cleaning machine. The fire extinguishers shall conform to and shall be mounted and secured in accordance with the applicable drawings.

3.8 Construction. Construction shall conform to the design, details, dimensions, material, classification, and sizes specified herein and as indicated on the applicable drawings.

3.8.1 Cradle valve. The ducts within the cradle valve shall permit free passage of a 5/16 inch diameter ball and shall not leak when subjected to 10 psig air pressure when tested in accordance with 4.5.2.2.

3.8.2 Supply line assembly (right and left). All threaded connections shall have American National pipe threads (NPT) and shall be made up with a nonhardening pipe joint compound suitable for use with petroleum solvents conforming to type II of P-D-680. Supply line assemblies shall show no evidence of leakage at seams, joints, or connections when tested in accordance with 4.5.2.1.

3.8.3 Baffles and strainers.

3.8.3.1 Baffles. The large baffle plate shall be continuously welded to the ends of the tank and the small baffle plate shall be continuously welded to the bottom and ends of the tank so that passage of solvent from one compartment to the other will be obtained by under flowing the large baffle and overflowing the small baffle.

3.8.3.2 Strainers. The strainers shall be securely fabricated and free from any escape holes other than the mesh of the screen. The mesh of the screens for the strainers shall be commercial size 40 by 40.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

3.8.4 Valve assembly. The valve assembly shall operate in the discharge position and suction position with no evidence of leakage when tested in accordance with 4.5.2.3.

3.8.5 Cradles. The cradle bottom shall be smooth to form a tight joint with the cradle clamp. The cradle interior shall not be painted.

3.8.6 55-gallon drum washer. All orifices shall be of the size specified and clear of obstructions. All pipe threads shall be of the American National Standard and all joints made up with a suitable non-hardening pipe joint compound suitable for use with petroleum solvents conforming to type I of P-D-680. The fluid shall discharge from all orifices with a flat trajectory for a distance of 14 to 18 inches and the suction tube shall drain in 8 to 12 seconds when tested as specified in 4.5.2.5.

3.8.7 Screw threads. Screw threads shall be in accordance with FED-STD-H28/2 and shall be class 2 fit unless otherwise specified (see 6.2).

3.8.8 Securing threaded parts. Threaded parts shall be properly secured to withstand vibration and shock without loosening. Except where disassembly will not be necessary during field operations or general maintenance of equipment, threaded parts shall be capable of repeated disassembly. Wherever practicable, each threaded part shall be secured by one or more of the following means: (a) lockwasher; (b) locknut; (c) self-locking nut; (d) cotter pin; (e) safety wire; or (f) staking. Staking shall not be used where disassembly is required.

3.8.9 Leakage. Before finishing in accordance with 3.9.1, 3.9.2 and 3.9.3 the completely assembled cleaning machine shall show no evidence of leakage when tested in accordance with 4.5.2.4.

3.9 Finish. Unless otherwise specified (see 6.2), all exterior surfaces of the cleaning machine, including brass or copper fittings shall be finished in the following manner:

3.9.1 Treatment and painting of exterior surfaces. Surface shall be treated and painted in accordance with MIL-T-704, Type F Color 34987.

3.10 Plate, identification. Each cleaning machine assembly shall have an identification plate made of corrosion-resistant metal, approximately 5 inches wide by 4-1/2 inches high. The letter "R" shall follow the serial number on the identification plates on the right-hand cleaning assembly, and the letter "L" shall follow the serial number on the identification plates of the left-hand cleaning assembly. Nameplate for the pumping assembly shall be as required by MIL-P-3230. The identification plates shall be mounted as shown by the applicable drawings. The size of the lettering shall not be less than 1/8 of an inch. Identification shall be in accordance with MIL-STD-130.

3.11 Safety and human factors.

3.11.1 Safety. Nonfunctional sharp edges, projecting points, and excessive lengths of fastening devices shall be avoided.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

3.11.2 Human factors. The cleaning machine shall be operable and maintained by the 5th (small woman) through 95th (large man) percentile personnel wearing combat or arctic clothing. The cleaning machine shall conform to the applicable human factors engineering criteria specified in J925 and MIL-STD-1472.

3.12 Workmanship. The cleaning machine shall be clean and free from sand, dirt, fins, pits, scale, rust, burrs, sharp edges, cracks, poor or unsound welds, or any other defect that could impair its performance or serviceability.

3.12.1 Metal fabrication. Metal used in fabrication shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the material. Corners shall be square and true. Flame cutting, using tips suitable for the thickness of the steel may be employed instead of shearing and sawing. All bends shall be made with controlled means to insure uniformity of size and shape. Precaution shall be taken to avoid overheating. Heated steel shall be allowed to cool slowly. External surfaces shall be free of burrs, sharp edges and corners, except when sharp edges or corners are required or where they are not detrimental to safety.

3.12.2 Bolted connections. Boltholes shall be accurately formed and shall have the burrs removed. Washers or lockwashers shall be provided where necessary. Matching thread areas securing bolts conforming to SAE J429 or capscrews shall be of sufficient strength to withstand the tensile strength of the bolt. All fasteners shall be correctly torqued and shall have full thread engagement. Bolts shall protrude not more than 2 full threads.

3.12.3 Riveted connections. Rivets shall fill the holes completely. The upset rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member, and shall be in accordance with SAE J492.

3.12.4 Welding. The surfaces of parts to be welded shall be free from rust, scale, paint, grease, mill scale that can be removed by chipping and wire brushing, and other foreign matter. Parent materials, weld filler metals, and fabrication techniques shall be as required to enable the cleaning machine to conform to the examination and test requirements specified in Section 4. Parts to be joined by fillet welds shall be brought into as close contact as possible and in no event shall be separated by more than 3/4 inch unless appropriate bridging techniques are used. Unless otherwise specified (see 6.2), the welding process used in fabrication of the cleaning machine shall be at the option of the contractor.

3.12.5 Welders. Before assigning any welder to manual welding work covered by this specification the contractor shall provide the contracting officer with certification that the welder has passed qualification tests as prescribed by either of the following listed codes for the type of welding operations to be performed and that such qualification is effective as defined by the particular code:

Structural Welding, AWS D1.1, Qualification, Section 5.
Welding Qualification of the ASME, Section IX.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

Contractors who only make horizontal welds need not qualify welders for "all position welding". Subject to approval by the Government, the contractor's standard welder qualification may be substituted in lieu of the above codes provided that the contractor's procedure is equivalent to the above codes. The contractor shall be responsible for determining that automatic welding equipment operators are capable of producing quality welds in accordance with AWS and ASME codes.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Component and material inspection. The contractor is responsible for insuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications, standards and drawings as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (See 4.4).
c. Inspection comparison (see 4.6).
d. Inspection of packaging (see 4.7).

4.3 First article inspection. First article inspection shall be performed on one or more units (see 6.2). The inspection will be performed by the Government at a site selected by the Government. Failure of the first article to pass the examination and tests shall be cause for rejection.

4.3.1 Examination. The first article cleaning machine shall be examined as specified in 4.4.4 and 4.4.5. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article cleaning machine shall be tested as specified in 4.5.2. Failure of any test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination shall be in accordance with MIL-STD-105, except as otherwise hereinafter specified (see 4.4.4 and 4.4.5).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

4.4.2 In-process testing. Before assembly, each cradle valve, valve assembly and supply line assembly shall be tested in accordance with 4.5.2.1, 4.5.2.2 and 4.5.2.3.

4.4.3 Inspection lot for end item testing. The inspection lot shall consist of all complete cleaning machines offered for inspection at one time.

4.4.4 Visual examination. The cleaning machine shall be visually examined as specified in table I. AQL shall be 4.0 percent defective for major defects and 6.5 percent defective for minor defects.

TABLE 1. Classification defects.

Examine	Defect	Classification	
		Major	Minor
Finish	Not plated or coated when required.	X	
	Color of finish not as specified.		X
	Blistered, peeled, chipped, or area of no film.		X
	Color separation, stained, or foreign matter imbedded in finish.		X
Construction and workmanship General (applicable to all components and assemblies)	Part missing or not specified type.	X	
	Fractured, split, dented, deteriorated, bowed, sprung, malformed, miscast.	X	
	Part missisng, loose, or not in proper alignment.		X
	Sharp burr, sliver or edge.	X	
	Valve, switch or gage not mounted in a manner that affords protection against accidental damage.		X
	Dissimilar metals as defined in MIL-STD-889 are not effectively, insulated from each other.	X	
	Contractor does not have documentation available for identification of material finishes or treatments.	X	
Materials	Materials not as specified or not corrosion resistant, or treated to be made corrosion resistant.	X	
Welding and brazing (where applicable)	Not type specified, missing, incomplete, through burn holes, fractured, or not fused.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

TABLE 1. Classification defects. (continued)

Examine	Defect	Classification	
		Major	Minor
	Slag inclusion, slight undercut, not smooth and uniform, or deposits of scale and flux not removed.		X
Soldering	Missing, not adherent, or incomplete	X	
	Not clean (flux or flux residue not removed), pinholes in solder.		X
Bolts, nuts, screws, studs, and other threaded component	Missing, not type specified, broken, stripped, fractured, or loose.		X
Rivets (when applicable)	Missing, not approved type, broken, not peened, or insufficiently peened.		X
Pipe, tubing, fittings and valves	Improperly connected or installed, will not provide seal where required, stripped, creased, restricting, or partially restricting interior flow.	X	
	Permanent crease or wrinkle, patched, cover blister.		X
Strainers	Not specified size mesh.	X	
	Torn or punctured.	X	
	Mesh clogged.		X
Interior of fuel or solvent tanks	Any foreign matter, loose metal chips, rust or scale.		X
Frame assembly	Skid and channel not cut out to receive frame tubing.	X	
	Skid not cut out to provide for nesting.		X
	Tank does not rest on skids and channel.	X	
Nameplate	Missing, not specified type, data omitted, incomplete, or illegible or marking not permanent.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

4.4.5 Dimensional examination. Examination shall be made of the cleaning machine to determine compliance with the specifications and applicable drawings. Any dimension that is not within the specified tolerances shall be classified a defect. The inspection level shall be S-2 with an AQL of 4.0 defects.

4.4.6 End item testing. Each completely assembled cleaning machine shall be tested as specified in 4.5.2.4 and 4.5.2.5. Failure of either test shall be cause for rejection.

4.5 Inspection procedure.

4.5.1 Examination. The cleaning machine shall be examined as specified in 4.4.4 and 4.4.5.

4.5.2 Tests.

4.5.2.1 Supply line assembly. Each supply line assembly shall be tested by a hydrostatic pressure test of 50 psig for a 5-minute period to determine conformance with 3.8.2.

4.5.2.2 Cradle valve. A 5/16 inch diameter steel ball shall be passed through the coved ducts in each valve body and the ducts shall be pressurized with air to 10 psig for a period of five minutes to determine compliance with 3.8.1.

4.5.2.3 Valve assembly. Each valve assembly shall be tested by introducing water through the valve inlet at the flow rate of 5 to 7 gpm and at a pressure of 17 to 19 psig. In the 5 degree position, the stream shall be of sufficient volume, velocity and direction to completely cover the bottom of the 5-gallon gasoline can conforming to MIL-C-1283. After 20 seconds in the 5 degree position, move the can to the 20 degree position. The discharge shall be completely stopped and the fluid removed by suction in 5 to 7 seconds. The valve shall rotate under these conditions with a torque ranging from 22 to 40 feet-pounds.

4.5.2.4 Leakage. Using ten 5 gallon gasoline cans (MIL-C-1283) the cleaning machines, with tanks filled to 18 inches with Stoddards solvent (type I of P-D-680) shall be operated in the normal manner through 25 cycles to determine compliance with 3.8.9.

4.5.2.5 55-gallon drum washer. After test in 4.5.2.4 five 55-gallon drums shall be cleaned in the normal manner to determine compliance with 3.8.6.

4.5.2.6 Reliability. The cleaning machine shall be tested for "accept" or "reject" criteria in accordance with MIL-STD-781, test plan IVC (see 3.5). A failure is defined as any malfunction which cannot be corrected within 30 minutes (all waiting periods are excluded) by adjustment, repair, or replacement action using controls and on-equipment tools or parts available to the using element. A failure may be one or more of the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

1. Failure to commence operation, cessation of operation, or degradation of performance below specified levels.
2. Damage to the cleaning machine by continued operation.
3. Safety hazards to personnel.

4.5.2.7 Maintenance support evaluation. Maintenance operations required during testing shall be accomplished to determine conformance to 3.6. Failure of the support elements to maintain the cleaning machine as specified herein shall constitute failure of this test. Errors or inadequacies in the manuals shall not be considered in assessing the maintenance ratio or the MTBF.

4.5.2.8 Safety and human factors. The safety and human factors requirements shall be evaluated during testing. Nonconformance to 3.11.1 and 3.11.2 shall constitute failure of this test.

4.5.2.9 Pumping assembly. Each pumping assembly shall be tested in accordance with MIL-P-3230.

4.6 Inspection comparison. The Government may select cleaning machines at any time during the contract production period and subject these cleaning machines to the examination specified in 4.5.1 and the tests specified in 4.5.2 to determine conformance to the requirement of this specification. The inspection will be performed by the Government, at a site selected by the Government, on cleaning machines selected at random from those which have been accepted by the Government and will not include the previously inspected first article cleaning machine. In addition to any test specified as part of the inspection comparison, the Government reserves the right to conduct any and all other tests contained in this specification as part of the inspection comparison, and failure of such additional tests shall have the same effect as failure of those tests specified as inspection comparison.

4.6.1 Inspection failure. Failure of an inspection comparison cleaning machine to meet any requirement specified herein during and as a result of the examination and tests specified in 4.6 shall be cause for rejection of the inspection comparison cleaning machine and shall be cause for refusal by the Government to continue acceptance of production cleaning machines until evidence has been provided by the contractor that corrective action has been taken to eliminate the deficiencies. Correction of such deficiencies shall be accomplished by the contractor at no cost to the Government on cleaning machines previously accepted and produced under the contract. Any deficiencies found as a result of the inspection comparison will be considered prima facie evidence that all cleaning machines accepted prior to the completion of inspection comparison are similarly deficient unless evidence to the contrary is furnished by the contractor and such evidence is acceptable to the contracting officer.

4.7 Inspection of packaging.

4.7.1 Preproduction pack inspection. The preproduction pack shall be examined for defects specified in 4.7.2.3. Presence of one or more defects shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

4.7.2 Quality conformance inspection of pack.

4.7.2.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.7.2.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.7.2.3 Examination. Samples selected in accordance with 4.7.2.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

101.	Materials, methods, or containers not as specified for level A.	Each incorrect material, method or container shall constitute one defect.
102.	Pumping assembly not preserved in accordance with the referenced document for level A.	
103.	Unprotected surfaces not coated as specified for level A.	
104.	Cradles not disassembled, wrapped, placed, and secured as specified for level A.	
105.	Float assembly not immobilized as specified for level A.	
106.	Drum washer assemblies not placed and secured as specified for level A.	
107.	Fire extinguishers not placed and secured as specified for level A.	
108.	Suction hose not coiled, ends wrapped, and placed and secured as specified for level A.	
109.	Y-suction hose not wrapped and placed as specified for level A.	
110.	Sealing of openings not performed as specified for level A.	
111.	Other components not preserved as specified for level A.	
112.	Engine and engine accessories of the pumping assembly not preserved as specified for level A.	
113.	Preservation and packing of the cleaning machine not in accordance with the referenced document as specified for commercial.	
114.	Packing not as specified for level A or level B.	
115.	Marking missing, illegible, incorrect, or incomplete for level A or commercial.	

5. PACKAGING

5.1 Preproduction pack. The contractor shall furnish a preproduction pack for examination within the time frame specified (see 6.2), to prove prior to starting production packaging that the applied preservation, packing and marking comply with the packaging requirements of this specification. Examination shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government (see 6.5). The preproduction pack may be accomplished utilizing either the first article cleaning machine or a production cleaning machine. If the first article cleaning machine is utilized, any preservation and packing shall be removed by the contractor at no expense to the Government, when requested by the Government to facilitate comparison between the first article cleaning machine and production cleaning machine.

5.2 Preservation. Preservation shall be level A or commercial as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

5.2.1 Level A.

5.2.1.1 Pumping assembly. The pumping assembly shall be preserved in accordance with the level A requirements of MIL-P-3230.

5.2.1.2 Tank assemblies and related components.

5.2.1.2.1 Unprotected surfaces. All exposed uncoated ferrous metal surfaces of each tank assembly or related components shall be coated with type P-7 preservative. The preservative shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116.

5.2.1.2.2 Cradles. The cradles shall be disassembled from the cleaning machine and individually wrapped in cushioning material conforming to PPP-C-1797 or Type II, Class B of PPP-C-843. The wrap shall be secured with tape, conforming to PPP-T-45, Type III, Class 2. Five wrapped cradles shall be placed in the compartment of each right and left tank assembly. Fiberboard inserts shall be provided to prevent damage to the float assembly and the strainer, and to prevent movement of the cradles. The float assembly shall be immobilized to prevent movement in transit.

5.2.1.2.3 Drum washer assemblies. Drum washer assemblies shall have the hose coiled and the complete assembly placed and secured in the rack provided for this purpose. One drum washer shall be secured on each right and left tank assembly.

5.2.1.2.4 Fire extinguisher. The fire extinguishers shall be secured in place with the clamps provided on each right and left tank assembly.

5.2.1.2.5 Suction hose. One 25-foot section of suction hose shall be coiled and secured in the compartment of the left tank assembly. The fittings on ends of hose shall be wrapped in cushioning material conforming to PPP-C-1797 or Type II, Class B of PPP-C-843. The wrap shall conform to PPP-T-45, Type III, Class 2.

5.2.1.2.6 Y-suction hose attachment. Each Y-suction hose attachment shall be wrapped in cushioning material conforming to PPP-C-1797 or Type II, Class B of PPP-C-843. The wrap shall be secured with tape conforming to PPP-T-45, Type III, Class 2. The wrapped hose attachment shall be secured with the coil of suction hose placed in the left tank assembly.

5.2.1.2.7 Operator's manual. The operator's manual shall be preserved in accordance with MIL-P-116, Method IC-1 or IC-3 and placed and secured in the tool box provided.

5.2.1.2.8 Sealing. All openings into the major assemblies, including openings and seams around tank hatches and tool compartment doors, shall be sealed with tape conforming to MIL-T-22085, Type II. Openings of hoses shall be closed with the fittings provided.

5.2.1.2.9 Other components. Other components not specifically mentioned herein requiring protection from corrosion or physical or mechanical damage shall be preserved as specified for components of similar design and

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

construction. Those components that can be placed in the tank, tool box, or compartment and cushioned and secured to prevent movement or damage, shall be so placed. Those components that can not, shall be placed together in one or more close fitting boxes conforming to PPP-B-601, domestic type, style optional. The boxes shall be of a size and configuration most convenient for accomplishing the packing specified in 5.3. Strapping of the boxes shall not be required.

5.2.2 Commercial. The engine and engine accessories of the pumping assembly shall be preserved in accordance with the level C requirements of MIL-E-10062. All other components of the cleaning machine shall be preserved in accordance with MIL-STD-1188.

5.3 Packing. Packing shall be level A, B or commercial as specified (see 6.2).

5.3.1 Level A. The components comprising a complete cleaning machine, preserved as specified in 5.1, shall be packed in a close fitting box conforming to MIL-B-26195, Type II, Style Optional, Class 2, with rubbing strips and plywood superstructure. Blocking, bracing, anchoring, closure and strapping shall be in accordance with the appendix to the box specification and in accordance with MIL-STD-1186. Strapping shall conform to QQ-S-781, Class 1, Type I or IV, size as applicable. Unless otherwise specified (see 6.2), strapping shall be finish B. When specified (see 6.2), strapping shall be finish A.

5.3.2 Level B. Level B shall be as specified in 5.3.1 except that the box shall be type I (domestic).

5.3.3 Commercial. Each complete cleaning machine shall be packed in accordance with MIL-STD-1188.

5.4 Marking.

5.4.1 Military. Marking for military levels of protection (level A) shall be in accordance with MIL-STD-129.

5.4.2 Commercial. Marking for commercial packaging shall be in accordance with MIL-STD-1188.

6. NOTES

6.1 Intended use. The fuel can and drum cleaning machine is designed to remove sand, mud, loose rust, and sediment from 5-gallon gasoline cans and 55-gallon drums.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification (see 2.1.1).
b. When sample units will be required for first article inspection and number of units required (see 3.2, 4.3 and 6.4).
c. When color will be other than as specified (see 3.3.2).
d. When screw threads will be other than as specified (see 3.8.7).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

e. When exterior surface finish of the cleaning machine will be other than as specified (see 3.9).
f. When welding process will not be at the option of the contractor (see 3.12.4).
g. Time frame required for submission of preproduction pack (see 5.1).
h. Degree of preservation and degree of packing required (see 5.2 and 5.3).
i. When other than finish B strapping is required (see 5.3.1).

6.3 Contract data requirements. When this specification is used in a procurement which incorporates a DD Form 1423 and invokes the provisions of paragraph 7-104.9(n) of the DAR, the data requirements will be developed as specified by an approved Data Item Description (DD Form 1664) and delivered in accordance with the Contract Data Requirements List (DD Form 1423) incorporated into the contract. When the provisions of DAR 7-104.9(n) are not invoked, the data shall be delivered in accordance with the contract requirements.

6.3.1 Data. The contracting officer should make provisions in the contract that the manufacturer provide a detailed operator's manual with each unit which includes installation, maintenance and operational instructions and safety precautions. The contracting officer should also assure that the manufacturer provides a detailed parts list, applicable to the model furnished, with each unit which includes parts numbers and the supply source for each component.

6.4 First article. When a first article is required, it will be tested and approved under the appropriate provisions of paragraph 7-104.55 of the Defense Acquisition Regulation (DAR). The first article may be a standard production item from the contractor's current inventory as specified in 4.3. The first article should consist of the number of units specified (see 6.2). The contracting officer should include specific instructions in all procurement instruments, regarding arrangements for examinations, test and approval of the first article.

6.5 Preproduction pack. Any changes or deviations of production packs from the approved preproduction pack will be subject to the approval of the contracting officer. Approval of the preproduction pack will not relieve the supplier of his obligation to preserve, pack and mark the cleaning machines in accordance with this specification.

6.6 Provisioning. The contracting officer should include provisioning requirements for repair parts and maintenance tools as necessary (including any special tools), and instructions on shipment of cleaning machines.

6.7 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the specification (see 3.3).

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 4940-A439

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-11071D(ME) Cleaning Machine, Fuel Can, Drum

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:04Z
Check the source to verify that this is the current version before use.