MIL-C-11085D
14 March 1986
SUPERSEDING
MIL-C-11085C
3 February 1969

MILITARY SPECIFICATION

CONVEYOR, BELT; (FLAT, SKID-MOUNTED, ELECTRIC-MOTOR-DRIVEN, 24-INCH-WIDE BELT, 50-FOOT-LONG FRAME; CAPACITY, 25 POUNDS PER FOOT, 75 TONS PER HOUR)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a flat belt, electric-motor-driven, skid-mounted, materials-handling conveyor. The conveyor may be used as a single unit or two to thirty units connected in a continuous line.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

QQ-S-781	- Steel, Strapping, Flat.
UU-T-81	- Tags, Shipping and Stock.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3910

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock Corner.
PPP-P-40 - Packing and Packaging of Hand Tools.

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-B-121 - Barrier Material, Greaseproofed, Waterproofed, Flexible.
MIL-V-173 - Varnish, Moisture-and-Fungus-Resistant, (for the Treatment of Communications, Electronic, and Associated Electrical Equipment).
MIL-P-514 - Plates, Identification, Instruction and Marking, Blank.
MIL-T-704 - Treatment and Painting of Materiel.
MIL-T-22085 - Tape, Adhesive, Preservation and Sealing.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-130 - Identification Marking of U.S. Military Property.
MIL-STD-209 - Slinging Eyes and Attachments for Lifting and Tying Down Military Equipment.
MIL-STD-461 - Electromagnetic Interference Characteristics Requirements for Equipment.
MIL-STD-889 - Dissimilar Metals.
MIL-STD-1474 - Noise Limits for Army Materiel.

(Copies of specifications, standards, handbooks, drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DoDISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DoDISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN NATIONAL STANDARDS INSTITUTE, INC., (ANSI).

B20.1 - Conveyors and Related Equipment, Safety Standard for.
C80.1 - Rigid Steel Conduit, Zinc Coated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 3951 - Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

SOCIETY OF NONDESTRUCTIVE TESTING

Handbook, Vol. II.

(Application for copies shall be addressed to the Society of Nondestructive Testing, 914 Chicago Avenue, Evanston, IL 60202.)

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

ICS-1 - General Standard for Industrial Control and Systems.
ICS-6 - Enclosures for Industrial Controls and Systems.
KS-1 - Enclosed Switches.
MG-1 - Motors and Generators.
SG-3 - Low-Voltage Power Circuit Breakers.
WC-3 - Rubber-Insulated Wire and Cable.
WC-8 - Ethylene-Propylene-Rubber-Insulated Wire and Cable.

(Application for copies should be addressed to the National Electrical Manufacturers Association, 155 East 44th Street, New York, NY 10017.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE Handbook (J492, J534 & J754)

(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.)

AMERICAN WELDING SOCIETY (AWS)

AWS B3.0 Welding Procedure and Performance Qualification.

(Application for copies should be addressed to the American Welding Society, Inc., 2501 N.W. Seventh Street, Miami, FL 33125.)

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Welding and Brazing Qualifications, Section IX.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

Source: https://assist.dla.mil -- Downloaded: 20260-17T15:05Z
Check the source to verify that this is the current version before use.

UNDERWRITERS LABORATORIES, INC.

ANSI/UL-583 - Standards for Safety (Power-Operated Industrial Trucks).

(Application for copies should be addressed to Underwriters Laboratories, Inc., 161 Avenue of the Americas, New York, NY 10013; 207 East Ohio Street, Chicago, IL 60611; or 1655 Scott Lane, Santa Clara, CA 95050).

(Nongovernment standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, (except for associated detail specifications, specifications sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The portable conveyor shall consist of an electric-motor-driven unit of steel-truss frame construction, equipped with a power jumper cable, a control jumper cable, a conveyor belt, and skids. The conveyor shall perform as an individual unit or in tandem, using from two to thirty conveyor units. The conveyor shall also operate as a gravity conveyor. The conveyor shall transfer crated or boxed material weighing not more than 25 pounds per linear foot of belt, at a rate of 75 tons per hour (tph) at a belt speed of 100 feet per minute (fpm) up a 15 percent grade.

3.1.1 Dimensions and weight. The conveyor shall conform to the dimensions and weight as follows:

	Dimensions				Weight	
	Max.		Min.		Max.	Min.
	Ft.	Ins.	Ft.	Ins.	Lbs.	Lbs.
Frame width, not including lifting attachments.	3	0	2	11-7/8	---	---
Conveyor length, overall.	50	0	49	11	---	---
Conveyor height, overall.	2	7-1/2	2	7-1/4	---	---
Conveyor weight including belt.	--	---	--	---	---	---

3.1.2 Towing conditions. The conveyor shall withstand the effects of skidding or dragging by truck or tractor over rough ground and through sand and water, and shall withstand the hard usage encountered in military service.

3.2 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 4.3 and 6.3). Any changes or

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:05Z
Check the source to verify that this is the current version before use.

deviations of conveyor belts from the approved first article during production will be subject to the approval of the contracting officer. Approval of the first article will not relieve the contractor of his obligation to furnish conveyor belts conforming to this specification.

3.3 Materials. Materials shall be as specified herein. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3.1 Material deterioration and control. The conveyor belt shall be fabricated from compatible materials, inherently corrosion and deterioration resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable storage and operating environments to which the hasps may be exposed.

3.3.2 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.3.3 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.3.4 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the conveyor belt may be newly fabricated from recovered materials to the maximum extent practicable, provided the conveyor belt produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the conveyor belt.

3.4 Safety. All exposed parts which are energized electrically shall be insulated, fully enclosed, or adequately guarded and grounded to protect all persons or objects from electrical shock hazard. All moving parts which are of such nature or so located as to be a hazard to operating or maintenance personnel shall be fully enclosed or properly guarded. Protective devices shall not impair the operating functions. All metallic members shall be so assembled and bonded as to provide a continuous electrical path for grounding purposes. The conveyor shall conform to the applicable safety requirements for ANSI B 20.1.

3.5 Maintainability. All assemblies and accessory installations shall permit ready accessibility to all parts for maintenance and repair without removal of other elements of the unit. Maintenance and repairs shall be accomplished using conventional general-purpose tools and a minimum number of personnel. Covers or plates which must be removed for component adjustments, replacement, or other maintenance shall be equipped with quick-disconnect fastenings. All subassemblies shall be matchmarked for ease of assembly and replacement. All lubrication fittings and conveyor adjustments shall be accessible without removal of other components.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

3.6 Frame. All framework shall be constructed of formed or rolled structural-steel shapes. The top and bottom chord members shall be not larger than 2-1/2- by 2-1/2- by 1/4-inch angles; the side vertical legs, diagonals, and side ties shall be not larger than 2- by 2- by 1/4-inch angles; the top and bottom diagonals shall be not larger than 2- by 2- by 1/4-inch angles. The top cord angles shall be drilled or punched for top belt-idler rollers not more than 6 inches on centers. The rollers shall project not less than 1/8 inch above the frame. Provisions shall be made for locating the bottom belt-idler rollers at not more than 4 feet on centers, and to support the driving mechansim and take-up adjustment for the driving unit which shall be placed near the center of the conveyor frame. All frame members shall be braced so that no frame member shall be stressed beyond 60 percent of the yield value of the steel when the conveyor is subjected to a uniformly distributed load of 37-1/2 pounds per linear foot. The frame members shall be joined by welding, bolting, or riveting.

3.7 Skids. Three pairs of skids shall be provided. The skids shall extend not less than 6 inches below the frame, and shall each be 2 feet wide by 4 feet long with the ends and sides turned up approximately 45 degrees for a distance of 6 inches in from the edges. Skids shall be made of steel plates not less than 0.25 inch in thickness. The skids shall be spaced approximately 14 feet on centers and secured to the underside of the conveyor frame.

3.8 Connectors. Connectors shall be provided on the head (receiving) and the tail (discharge) ends of the frame, so that the head end of the conveyor frame can be distinguishable from the tail end by sight or touch, and so that when assembled with other conveyors, all conveyor belts will move in the same direction. The connectors shall be accessible and shall be provided with a locking arrangement which shall allow for slight variation both vertically and horizontally when they are connected to another conveyor.

3.9 Towing attachments. Four towing eyes or hooks (two at each end) made of forged heat-treated steel shall be bolted to the conveyor frame. Each hook shall withstand a force in pounds equal to twice the weight of the conveyor including belt. The towing attachments may also be used for tie-down devices when meeting the requirements specified in 3.19. When towing attachments are mounted under a frame member, they shall be of the eye type and shall be not less than 3 inches inside diameter. Towing attachments shall be accessible for attaching cable or chain.

3.10 Rollers.

3.10.1 Belt-idler rollers. The belt-idler rollers shall be metal tubing having a wall thickness of not less than 0.083 inch, with swaged ends, with 2-1/2-inch outside diameter ±1/32-inch, by not less than 30 inches long. The rollers shall be mounted on free-running antifriction bearings, carried on shafts of a size so as not to be damaged when tested in accordance with 4.5.2. The top and bottom belt-idler rollers shall be interchangeable and spaced as specified in 3.6.

3.10.2 End-transfer rollers. The end-transfer rollers shall be metal tubing having a wall thickness of not less than 0.187 inch, with 2-9/16-inch ±1/32-inch diameter by not less than 30 inches long, and shall be mounted as specified in

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

3.10.1. Not less than one transfer roller shall be placed at one end of the conveyor in the space between the end of the frame and the belt return rollers at the head or tail so that material can be supported on the transfer roller as it is transferred from one conveyor to another.

3.10.3 Belt-guide rollers. The belt-guide rollers shall be metal tubing having a wall thickness of not less than 0.187 inch, with 2-9/16-inch ±1/32-inch outside diameter by not less than 6 inches long, and shall be mounted as specified in 3.10.1. At least four rollers shall be placed vertically against each side of the return belt and spaced so as to prevent the belt from tracking against the sides of the the frame.

3.10.4 Belt return, takeup, and drive rollers. The rollers at the head and tail ends of the conveyor and the takeup rollers shall be interchangeable and shall be of steel with 12-inch ±1/32-inch outside diameter and 28-inch machined crown face. The drive roller shall be of steel, with 12-inch ±1/32-inch outside diameter and not less than 26-inch machine crown face, and shall be positioned midway between the two ends of the conveyor frame. All rollers shall be mounted on the shafts as specified in 3.10.1. The drive roller shall be keyed on its shaft, but the head and tail return rollers and takeup rollers may be clamped on their shafts. The return belt takeup roller shall be provided with an automatic spring-tension device that operates over the range of stretch and shrink of the conveyor belt. The spring-tension device shall have a screw adjustment accessible for servicing, and shall be protected from damage while being towed.

3.11 Shafting. The shafting for all conveyor belt return, takeup, and drive rollers shall be made from cold-finished steel of adequate strength and size so as not to be damaged when tested in accordance with 4.5.2.

3.12 Takeup adjustment. A takeup adjustment shall be provided for each takeup bearing. The takeup adjustment shall consist of a threaded rod of cold-rolled steel not less than 1 inch in diameter by not less than 36-1/2-inches in length, with a nut to fit the takeup box, a helical steel compression spring, and spring guide bushings. The spring shall be made of 3/8-inch-nominal-diameter spring-steel wire, 2-3/4-inch, minimum outside diameter by 14 inches minimum free length. The spring shall compress to a working length of not less than 11 inches by a working load of 350 pounds, and shall compress to a working length of not less than 8 inches by a working load of 750 pounds. One guide bushing of the spring and rod assembly shall be welded to a plate secured to the frame of the conveyor, and the other guide bushing shall compress the spring by means of a nut and locknut on the rod so as to obtain the desired tension in the belt. The nuts and bushings shall be made of hot-rolled, mild steel.

3.13 Drive. The conveyor drive shall be a steel roller chain with a 1-inch pitch operating over a cut tooth steel sprocket on the gear-motor output shaft, and a cut-tooth steel sprocket mounted on the pulley drive shaft. Chain and drive sprocket shall be fully enclosed.

3.14 Conveyor belt. An idustrial type conveyor belt shall be furnished as integral part of the conveyor. The belt shall be 24 inches wide and shall be laced with metal fasteners having a pin joint to facilitate dismantling. The belting shall have a smooth rubber compound cover on both the pulley and

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:05Z
Check the source to verify that this is the current version before use.

carrying side. The rubber cover on the carrying side shall extend around the edge and down to the pulley side. Unless otherwise specified, the thickness of the rubber cover shall be at least 0.060 inches on carrying side and at least 0.030 inches on pulley side. The fabric used in the manufacture of commercial conveyor belting shall be made of cotton, synthetic, or a combination of cotton and synthetic yarns. The belting shall be fungus-resistant. The belting shall have at least four plies of fabric. Each of the four plies shall have a minimum breaking strength of 375 pounds per inch of width in the warp direction and shall be given a coat of latex prior to final assembly. The belting shall perform as specified in this specification.

3.15 Electrical equipment. The conveyor shall be equipped with an electric motor, a system of electrical wiring and controls in watertight conduit and fittings, and power-supply cables with magnetic starter. The electrical equipment shall permit, by means of power and control jumper cables, connection of up to fifteen conveyor units into one group, and operation of two such from a common source of power. A "start-stop" pushbutton switch shall be mounted adjacent to the motor and be accessible to an operator in a standing position beside the conveyor. When the conveyor units are connected in a group, the controls shall require individual starting of each motor and simultaneous stopping of all motors from any "start-stop" pushbutton. In addition, it shall be possible to stop the group of motors from a remote control stop-button station located in a magnetic contactor at a source of power not less than 300 feet from the conveyor line. A suitable ground terminal shall be provided.

3.15.1 Electric motor. The conveyor belt shall be driven by an industrial type electric motor conforming to NEMA MG 1, fractional and integral horsepower, alternating-current polyphase, squirrel-cage induction, totally-enclosed, fan-cooled, guarded, rated for 460 volt, 60 hertz, 3 phase.

3.15.2 Conduit. Conduit shall conform to ANSI C80.1. A 1-1/2-inch conduit containing the power, control, and ground wires shall connect a receptacle box at each end of the conveyor to a junction box at the center. An expansion joint shall be located in each section of the 1-1/2-inch conduit near the junction box. A 1-inch conduit shall connect the junction box to the magnetic starter, and a 3/4-inch conduit shall connect the magnetic starter with the "start-stop" pushbutton switch.

3.15.2.1 Junction box. A steel or cast iron, watertight, junction box with gasket and cover shall be furnished. The junction box shall have at each end an outlet opening with 1-1/2-inch pipe threads, and on one side an outlet opening with 1-inch pipe threads.

3.15.2.2 Receptacles. Two polarized watertight receptacles with caps shall be mounted on each of the receptacle boxes located at the ends of the conveyor frame; one receptacle shall be for the power cable and the other for the control cable. The power receptacle shall be 60 ampere, 600 volt, alternating-current, 3 wire, 4 pole; and the control receptacle shall be 30 ampere, 600 volt, alternating-current, 3 wire, 3 pole. Each receptacle box shall be provided with one 60- or 30-ampere receptacle mounting adapter plate and shall be labeled "Power" and "Control", respectively.

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:05Z
Check the source to verify that this is the current version before use.

3.15.3 Controls. Each control shall be mounted in an enclosure conforming to NEMA Standard No. KS-1, type 3R.

3.15.3.1 Magnetic starter. The magnetic starter shall be in accordance with NEMA Standard ICS-1, across-the-line, magnetic operated, low voltage protection, size 1, enclosed type, 460 volt, 3 phase operation with thermal overload. The across-the-line starters shall connect the motor directly across the line and shall operate by means of 2-wire or 3-wire, start-stop, push button.

3.15.3.2 Pushbutton switch. The pushbutton switch shall be of the 2-button "start-stop" type with momentary contact, normally open and normally closed, double break contacts. The start button shall be green and labeled "start" and the stop button shall be red and labeled "stop".

3.15.3.3 Circuit breaker. The circuit breaker shall be a 3-pole, non-automatic type, frame size 225-ampere, conforming to NEMA Standard SG3, and shall be provided with a shunt tripping device rated at 460 volts, 60 cycles. The circuit breaker enclosure shall be of a weather-resistant and dusttight construction conforming to NEMA Standard ICS-6, type 3S. The circuit breakers shall be provided with an external handle. ON and OFF positions shall be clearly indicated. The circuit breaker shall be furnished unmounted.

3.15.4 Wires and cables. Electric wires on each conveyor shall conform to ANSI/UL583 C1, and all power cables shall conform to NEMA WC8 or WC3.

3.15.5 Ground-rod assembly. The conveyor shall be equipped with an auger-type ground-rod assembly. The ground-rod assemblies shall be in accordance with ANSI/UL583 and as specified herein.

3.15.5.1 Rod. The rod shall be 8 feet long ±1 inch, shall be not less than 5/8 inch in diameter and shall consist of a steel rod with an auger tip for ground insertion on one end and a "T" handle on the other end. The rod shall be of steel. The auger tip shall be of steel with a right-hand thread not less than 9 inches in length. The tip shall be heat-treated to a minimum hardness of 45 Rockwell C.

3.15.5.2 Clamp. The clamp shall permit installation on the ground rod before or after the rod is inserted into the ground. Clamp body and parts shall have material compatible with the class of rod to preclude electrolytic corrosion. The minimum thickness of the clamp body shall be 1/8 inch.

3.15.5.3 Ground cable. Unless otherwise specified, the overall cable length shall be 6 feet ±1 inch. Grounding cable shall consist of No. 10 AWG, rope stranded (7 strands), extra flexible bare copper wire or a strap of braided or woven copper wire equivalent to No. 6 AWG. The wire or braid shall be coated with tin, lead, or lead-alloy, one end being soldered or brazed to the yoke of the U-clamp and the opposite end attached to the power clip.

3.15.6 Fungus and moisture resistance. The electrical circuitry, including all components and connections, except as specified below, shall be protected from the effects of fungus growth and moisture by an overall treatment with a varnish conforming to MIL-V-173, except that 1 percent copper 8-quinolinolate

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

(by weight) based on the nonvolatile content of the varnish shall be used in lieu of salicylanilide, the specified fungitoxicant:

a. Components or circuit elements which are inherently fungus and moisture resistant or which are hermetically sealed need not be treated.
b. Components or circuit elements whose functions will be adversely affected by the varnish coating shall not be treated.

When used, the varnish shall be applied by spray, brush, or a combination of both to give a minimum dry film thickness of 1 mil to component or element surfaces previously cleaned and prepared so that the surfaces are free from all foreign matter which would interfere with the adherence or function of the varnish.

3.16 Electromagnetic interference. The electromagnetic interference emission of the conveyors shall be in accordance with MIL-STD-461.

3.17 Lubrication. Lubrication means shall be provided for all moving parts that require lubrication, except where sealed permanent lubrication is provided. The types of lubricants shall be selected from, and in accordance with, SAE J 754. All initial fills of lubricants shall be limited to the types approved by the component manufacturers. Grease lube fittings shall conform to SAE J 534

3.18 Slinging eyes. When specified (see 6.2), conveyors shall be equipped with slinging eyes in accordance with MIL-STD-209 for type III equipment. The working load for the eyes shall be based on the fully serviced weight of the conveyor without load. Multipurpose eyes are acceptable. Slinging eyes shall show no evidence of permanent deformation, damage, or failure when tested as specified in 4.5.4.

3.19 Tiedown eyes. When specified (see 6.2), conveyors shall be equipped with tiedown eyes in accordance with MIL-STD-209 for type III equipment. The weight of the conveyor shall be based on the fully serviced weight, without load. Multipurpose eyes are acceptable. Tiedown eyes shall show no evidence of permanent deformation, damage, or failure when tested as specified in 4.5.5.

3.20 Identificaton marking. The conveyor shall be identified in accordance with MIL-STD-130. The marking shall be applied to the conveyor on plates conforming to MIL-P-514, type I, style 1, composition C of type I, grade A, class 1 material. Plates shall be attached by screws, bolts, or rivets in a conspicuous protected location.

3.21 Shipping data plate. A shipping data plate shall conform to MIL-P-514, type III, composition C, of type I, grade A, class 1 material and in addition, shall show the silhouette of the conveyor in transport position indicating the center of gravity and the location and capacity of the lifting and the tiedown attachments. Plates shall be attached by screws, bolts, or rivets in a conspicuous protected location.

3.22 Instruction plates. Each conveyor shall be equipped with instruction plates or diagrams, including warnings and cautions, describing any special or important procedures to be followed in assembling, operating, or servicing the

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:05Z
Check the source to verify that this is the currentversion before use.

conveyor. Instruction plates shall conform to MIL-P-514, type III, composition C, of type I, grade A, class 1 material. Plates shall be attached by screws, bolts, or rivets in a conspicuous protected location.

3.23 Treatment and painting. All parts of the equipment normally painted shall be cleaned, treated, and painted in accordance with MIL-T-704, type A unless otherwise specified (see 6.2). When specified (see 6.2), treatment and painting shall be in accordance with MIL-T-704, type F or type G as applicable.

3.24 Stenciling. The gross weight of each unit of equipment shall be stenciled on each side of the unit in such a manner as to be discernible. Unless otherwise specified, stenciling shall conform to MIL-T-704.

3.25 Toolbox. The equipment shall be provided with a toolbox made of metal 0.073-inch minimum nominal thickness. The toolbox shall be sufficiently large to contain all the tools required for general maintenance and operation of the conveyor. The box shall be closed by a hinged lid secured by not less than two fasteners. A hasp shall be suitably located to secure the lid to the box and accommodate a lock having a 3/8-inch shackle. The toolbox shall be securely mounted in an accessible proteced location permitting the lid to be opened through an arc of not less than 90 degrees. The lid shall be held fully open by its weight or a suitable fastener. Adequate drainage of the toolbox shall be provided.

3.26 Workmanship. All parts, components, and assemblies of the conveyor including castings, forgings, molded parts, stampings, bearings, seals, machined surfaces, and welded parts shall be clean and free from sand, dirt, fins, pits, sprues, scale, flux, and other harmful, extraneous material. External surfaces shall be free from burrs, sharp edges, and corners except when sharp edges and corners are required.

3.26.1 Aluminum and steel fabrication. Aluminum and steel used in the fabrication of the conveyor shall provide original quality surface finish and shall be free from kinks and sharp bends. Aluminim and steel having eroded surface is not acceptable. The forming of the material shall be done by methods that will not cause damage to the metal. Shearing, punching, and chipping shall be done uniformly, neatly, and accurately. Corners shall be square and true, and all sharp edges and burrs shall be removed. The surfaces shall be free of burrs, slag, and sharp edges. All bends of a major character shall be made with precise, unyielding dies or jig fixtures to insure uniformity of size and shape.

3.26.2 Welders and welding.

3.26.2.1 Welders. Before assigning any welder to manual welding work covered by this specification, the contractor shall obtain certification that the welder has passed qualification tests as prescribed by any of the following listed codes for the type of welding operation to be performed and that such qualification is effective as defined by the particular code:

American Welding Society AWS B3.0 Welding Procedure and Performance Qualification.
ASME Boiler and Pressure Vessel Code, Welding and Brazing Qualifications, Section IX.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

The certification shall be made available for review by the contracting officer or the contracting officer's representative.

3.26.2.2 Welding. The surfaces or parts to be welded shall be free from rust, scale, paint, grease, and other foreign matter. Welds shall transmit stress without permanent deformation or failure when the parts connected by the welds are tested as specified herein.

3.26.3 Bolted connections. Bolt holes shall be accurately formed or drilled and shall have burrs removed. Washers or lockwashers shall be provided. Self-locking nuts are acceptable in lieu of standard nuts and lock washers. All capscrews, bolts, and nuts shall be tight and correctly torqued. Matching thread areas securing bolts or capscrews shall be of sufficient strength to withstand the tensile strength of the bolt.

3.26.4 Riveted connections. Riveted connections shall be in accordance with SAE J492. Rivet holes shall be accurately punched or drilled and shall have the burrs removed. Rivets shall completely fill the holes. The upset rivet heads shall be full, neatly made, concentric with the rivet holes, and in full contact with the surface of the member.

3.27 Noise Limits. The noise produced by the conveyor shall conform with MIL-STD-1474 requirements when tested in accordance with specification, 4.5.9. The provisions of MIL-STD-1474, 4.3 and 4.4 shall be provided if and only if MIL-STD-1474, 5.1.1.2 procedures have been pursued and documented to the satisfaction of procuring activity and written permission to exceed the 85dB(A) limit is obtained from the procuring activity. Hazard signs shall conform with MIL-STD-1474, 4.3 and be readable at the distance indicated on the sign.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article conveyor shall be examined for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.3.2 Tests. The first article conveyor shall be tested as specified in 4.5.2.1 thru 4.5.8. Failure of any test shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Examination. Each conveyor shall be examined as specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4.2 Tests. Each conveyor shall be tested as specified in 4.5.8. Failure of test shall be cause for rejection.

4.5 Inspection procedure.

4.5.1 Examination. Conveyors shall be examined as specified herein for the following defects:

101. Dimensions and tolerance not as specified.
102. Weight of conveyor with belt not as specified.
103. Frame not as specified.
104. Part or components missing, damaged, do not function, or not as specified.
105. Assemblies incomplete or incorrect.
106. Materials not as specified.
107. Safety devices and guards missing or inadequate.
108. Bonding of metallic members not as specified.
109. Maintainability not as specified.
110. Rollers not as specified.
111. Shaft misalinement.
112. Belt not as specified.
113. Electrical equipment not as specified, do not function, or are damaged.
114. Fungus and moisture resistant coating (as applicable) omitted on electrical circuitry, or applied where it will adversely affect circuitry.
115. Electromagnetic interference suppression components and network not identical with approved model.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

116. Lubrication devices are missing, not accessible, or not as specified.
117. Identification or other marking missing, illegible, incomplete, or not as specified.
118. Treatment and painting not as specified.
119. Technical publications not as specified or missing.
120. Workmanship not as specified.
121. Exposed parts (as applicable) not insulated, enclosed, or guarded.
122. Welding and welders not as specified.
123. Welders certification not as specified.
124. Riveted and bolted connections not as specified.
125. Materials are not resistant to corrosion and deterioration or treated to be resistant to corrosion and deterioration for the applicable storage and operating environments.
126. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other.
127. Contractor does not have documentation available for identification of material, material finishes, or treatments.
128. Used, rebuilt, or remanufactured components, pieces or parts incorporated in the conveyor belt.
129. Aluminum and steel fabrication not as specified.

4.5.2 Tests.

4.5.2.1 Towing. The assembled conveyor shall be dragged at not less than 2 mph over rough cross-country terrain, and through sand and water not less than 6-inches deep, for a period of not less than 1 hour. The belt shall then be removed and the conveyor examined. Evidence of distortion, misalinement, or malfunction of any part shall constitute failure of this test.

4.5.2.2 Operational load. The assembled conveyor shall be operated at maximum capacity for a period of 2 hours, transporting the load upgrade on not less than 15 percent slope. The conveyor belt shall be removed and the conveyor shall be operated as a gravity conveyor on a downgrade at maximum capacity for a period of 1 hour. Evidence of overheating, excessive wear, or malfunctioning of any part shall constitute failure of this test.

4.5.2.3 Static load. The conveyor shall be placed on a level surface. Strain gages shall be in accordance with section 54, Resistance Strain Gage Testing of the Nondestructive Testing Handbook, and shall be used for measuring the stresses of the frame members. After installation of the strain gages in locations as specified herein, the conveyor shall be uniformly loaded with 37-1/2 pounds per linear foot. The recording instruments shall then be read and the data recorded. Any strain gage reading exceeding 60 percent of the yield point for any frame member shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:05Z
Check the source to verify that this is the current version before use.

4.5.2.3.1 Installation of gages. The strain gages shall be installed in accordance with section 54, Resistance Strain Gage Testing, Nondestructive Testing Handbook, and as specified herein. Any residual stresses in the structural members due to dead loading shall be relieved prior to zeroing the strain-recording instrument.

4.5.2.3.2 Location of gages. The strain gages shall be located approximately as follows:

a. Bottom point or leg of each longitudinal lower chord member of the side trusses at a point midway between each skid.
b. Top point or leg of each longitudinal upper chord member of the side trusses at a point midway between the end of the unit and the nearest skid.
c. Where directions of principal stress are questionable, two or more gages or strain gage rosettes may be employed. During test operations or visual inspection, any points which show visual evidence of weakness due to design or paint checking shall be gage tested in addition to those points listed in a. and b.

4.5.2.3.3 Instrumentation operation. Operation of strain gage recording or indicating apparatus shall be in accordance with the instrument manufacturer's recommended procedure. Standard commercial instruments specifically designed for resistance strain gages shall be considered acceptable provided the instruments are accurate to within ±10 microinches at a scale reading of 600 microinches.

4.5.2.3.4 Recording. In order to provide uniform records, data shall be recorded as shown in table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

TABLE I. Maximum working stress.

Contract order No. _____ Place _____
Recording instruments _____ Date _____
Gage type _____ Recorder _____
Gage factor _____
Gage resistance _____

Gage No.	Compo-nent	Gage	Loca-tion	Material 1/	Opera-tion	Recorded strain micro-inches			Maximum 2/ stress psi 3/
						Test 1 (a) Zero Reading (b) Test Reading (b-a) Strain	Test 2 (a) Zero Reading (b) Test Reading (b-a) Strain	Test 3 (a) Zero Reading (b) Test Reading (b-a) Strain	

1/ E-Modulus of elasticity.
2/ Where rosette gages are used, see manufacturer's instruction for exact strain.
3/ Maximum stress = actual strain.

4.5.3 Towing attachment test. A force in pounds equal to twice the weight of the conveyor, with belt as specified in 3.1.1, shall be applied to each towing hook or eye. Distortion of the hook or eye, evidence of failure or permanent deformation of the attachment, or evidence of failure or permanent deformation of the structural members shall constitute failure of this test.

4.5.4 Slinging eyes. When slinging eyes are furnished, lift the conveyor in its normal travel attitude. Determine the force at the angle of application for each attachment. Apply static working load as specified in MIL-STD-209 to each attachment in the direction determined. Load shall be applied for not less than 90 seconds. Release the load and examine the conveyor, weldment, and eye. Nonconformance to the requirements of MIL-STD-209, evidence of permanent deformation, or damage shall constitute failure of this test.

4.5.5 Tiedown eyes. When tiedown eyes are furnished, anchor the conveyor using the tiedown other than the eye being tested. Apply static load as specified in MIL-STD-209 to each eye for a minimum of 90 seconds. Release the load and examine the conveyor, weldment, and eye. Nonconformance to the requirements of MIL-STD-209, evidence of permanent deformation, or damage shall constitute failure of this test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

4.5.6 Electromagnetic interference. The preproduction model shall be tested to determine conformance with 3.16. The supplier shall furnish the contracting officer a report of tests required by MIL-STD-461. Disapproval of the report shall constitute failure of this test.

4.5.7 Performance test. Each conveyor submitted for acceptance shall be operated at the rate specified in 3.1, and at no load for a period of 30 minutes each to demonstrate performance and function of all components and to allow for any necessary adjustments to be made prior to shipment. Inability of the conveyor to perform as specified in 3.1 or nonfunction of any component shall constitute failure of this test.

4.5.8 Noise level test. Noise levels shall be measured in accordance with MIL-STD-1474 requirements and reported in the format indicated by MIL-STD-1474, figure 7. As a minimum: noise levels shall be measured when equipment is operating under full load. MIL-STD-1474, 5.1.2.1.4 contours shall be taken at not fewer than 12 equal (horizontal) arc increments; one increment shall include data from the noisiest position. Additionally, the noise level at the typical operating position shall be provided as dB(A) level. Failure to comply with MIL-STD-1474 provisions shall constitute failure of this test.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 2.5 percent defective.

No.	Defect	A	B	Comm.
130.	Components not disassembled as required.	5.1.1.1.1		
131.	Bolts, nuts, washers and pins not secured to mating parts as specified.	5.1.1.1.1		
132.	Components not matchmarked with tags as specified.	5.1.1.1.2		
133.	Preservation and preservatives not as specified.	5.1.1.2		5.1.2
134.	Unprotected surfaces not preserved as specifiecd.	5.1.1.3		
135.	Bearings not preserved as specified.	5.1.1.4		
136.	Drive chains not preserved as specified.	5.1.1.5		

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:05Z
Check the source to verify that this is the currentversion before use.

137.	Conveyor belt not preserved as specified.	5.1.1.6		
138.	Openings into electrical equipment not sealed as specified.	5.1.1.7.1		
139.	Circut breaker not preserved as specified.	5.1.1.7.2		
140.	Electric power cables not coiled, secured and ends sealed as specified.	5.1.1.7.3		
141.	Ground rod not preserved and attached to conveyor frame as specified.	5.1.1.7.4		
142.	Technical publications not preserved as specified.	5.1.1.8		
143.	Repair parts not preserved as specified.	5.1.1.9		
144.	Maintenance tool not preserved and placed in tool box as specified.	5.1.1.10		
145.	Tool box not strapped closed with strapping specified.	5.1.1.10		
146.	Specified components not positioned in consolidation container as specified.	5.1.1.11		
147.	Consolidation container not as specified.	5.1.1.11		
148.	Consolidation container not closed and strapped as specified.	5.1.1.11		
149.	Consolidation container not secured within conveyor frame as specified.	5.2.1.1	5.2.2	
150.	Electric motor not protected with housing as specified.	5.2.1.2	5.2.2	
151.	Electric motor housing not secured to conveyor frame as specified.	5.2.1.2	5.2.2	
152.	Conveyor belt not packed as specified.	5.2.1.3	5.2.2	
153.	Commercial packing not as specified.			5.2.3
154.	Marking not as specified.	5.3.1	5.3.1	5.3.2

5. PACKAGING

5.1 Preservation. Preservation shall be level A, or commercial as specified (see 6.2).

5.1.1 Level A.

5.1.1.1 Disassembly and matchmarking.

Source: https://assist.dla.mil -- Downloaded: 20261-17T15:05Z
Check the source to verify that this is the current version before use.

5.1.1.1.1. Disassembly. The conveyor belt, idler rollers, transfer rollers, guide idler, and roller chain shall be removed from the conveyor frame. Bolts, nuts, washers, and pins involved shall be placed in mating parts and secured to prevent their loss.

5.1.1.1.2 Matchmarking. Removed parts and their mating parts on the unit shall be matchmarked when necessary to facilitate reassembly, with cloth tags conforming to UU-T-81, type A, or with metal tags. The cloth tags shall be waterproofed in accordance with MIL-STD-129.

5.1.1.2 Preservatives. Preservatives specified herein by "P" numbers shall conform to the applicable specification listed in MIL-P-116 and shall be applied in accordance with MIL-P-116.

5.1.1.3 Unprotected surfaces. Unpainted metal surfaces of components such as bolts, nuts, rollers, pulleys, shafting, takeup adjusting rods, coil springs, nonprecision chains, spring guide bushings, coupling pins, sprockets, towing hooks, and any other unpainted exterior metal surface requiring the application of a preservative in accordance with MIL-P-116 shall be coated with type P-1 preservative.

5.1.1.4 Bearings and pillow blocks. After lubrication of the bearings, the pillow blocks and shaft ends shall be wrapped or covered with barrier material conforming to MIL-B-121, type I, grade A, class 2, secured in place with tape conforming to MIL-T-22085, type II.

5.1.1.5 Drive chain. The drive chain shall be coated with enough type P-3 or P-9 preservative to assure penetration of the preservative to the inner surface of the rollers, pins, and bushings. After draining the excess type P-3 or P-9 preservative, the entire chain shall be coated with type P-1 preservative. The chain shall be coiled, and the coil shall be secured with soft annealed wire and wrapped with barrier material conforming to MIL-B-121, type I, grade A, class 2, secured in place with tape conforming to MIL-T-22085, type II.

5.1.1.6 Conveyor belt. The belt shall be compactly rolled and the roll secured with two equally spaced metal straps conforming to QQ-S-781, type I, finish B, placed circumferentially on the roll and the straps tensioned so as not to damage the belt.

5.1.1.7 Electrical equipment.

5.1.1.7.1 Openings. Openings into the motor and the enclosure of controls of the magnetic starter, magnetic contactor, push button switch, and junction box shall be sealed with tape conforming to MIL-T-22085, type II.

5.1.1.7.2 Circuit breaker. The circuit breaker shall be preserved in accordance with MIL-P-116, method III.

5.1.1.7.3 Electric power cables. The contact plugs and connectors on the power cables shall be sealed with tape conforming to MIL-T-22085, type II. Each cable shall be coiled to not less than 10 times its diameter with the connectors placed inside the coil and the coil secured with evenly spaced ties of cotton tape or twine.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

5.1.1.7.4 Ground rod assembly. The ground rod rigid-type handle shall be removed or, if of the folding type, the handle shall be folded. The handle shall be secured to the rod with ties of soft annealed steel wire. The auger shall be coated with type P-1 preservative. The cable shall be coiled and the coil secured with cotton tape or twine. The ground rod shall be secured inside the conveyor frame with soft annealed steel wire.

5.1.1.8 Technical publications. Technical publications for each conveyor shall be preserved in accordance with MIL-P-116, method IC-1 or IC-3.

5.1.1.9 Repair parts. Repair parts shall be preserved in accordance with the preservative application criteria and applicable method(s) of preservation of MIL-P-116.

5.1.1.10 Maintenance tools. Maintenance tools shall be preserved in accordance with the level A requirements of PPP-P-40 and placed in the tool box. The tool box lid shall be secured in the closed position with strapping conforming to QQ-S-781, type I, finish B.

5.1.1.11 Consolidation. Disassembled components of each conveyor, excluding the ground rod (see 5.1.1.7.4) and the conveyor belt (see 5.2.1.3), shall be consolidated together in close-fitting boxes conforming to PPP-B-601, overseas type, style optional or PPP-B-621, class 2, style optional. Such boxes shall be of a size to fit within the conveyor frame (see 5.2.1.1) and shall be closed and strapped in accordance to the applicable box specification or the appendix thereto except that the strapping shall be flat and the finish B.

5.1.2 Commercial. Each complete conveyor with repair parts, tools and technical publications shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or commercial as specified (see 6.2).

5.2.1 Level A.

5.2.1.1 Conveyor frame. The conveyor frame shall be shipped unboxed. Components consolidated in boxes as specified in 5.1.1.11 shall be placed and secured within the conveyor frame. The boxes shall be secured to the frame with strapping conforming to QQ-S-781, type I, finish B.

5.2.1.2 Electric motor. The electric motor shall be protected by a housing consisting of two sides and two ends and a top, constructed in accordance with applicable requirements of PPP-B-601, overseas type, style optional. The housing shall be of such dimension as to provide clearance between its inner surfaces and the motor, to eliminate direct shock to the motor. The housing shall be secured to the conveyor frame by bolting or with strapping specified herein.

5.2.1.3 Conveyor belt. The rolled and secured conveyor belt shall be packed in a close-fitting box conforming to PPP-B-601, overseas type, style optional. Closure and strapping shall be in accordance with the appendix to the box specification. Strapping shall be zinc coated. The belts shall be shipped separately from, but at the same time, as the conveyor frame.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. Packing shall be as specified for level A except that the consolidation container, the box containing the conveyor belt and the housing over the electric motor shall be domestic type and strapping used shall not be required to be zinc coated.

5.2.3 Commercial. Each complete conveyor, preserved as specified in 5.1 shall be packed in accordance with ASTM D 3951.

5.3 Marking.

5.3.1 Military. In addition to any special marking required by the contract or purchase order, levels A and B marking shall be in accordance with MIL-STD-129.

5.3.2 Commercial. Commercial marking shall be in accordance with ASTM D 3951. Additionally, the weight and cube shall be marked on each boxed or unboxed item offered for transportation.

6. NOTES

6.1 Intended use. The conveyor is intended for use in beaching operations for loading and unloading boxed materials, and for transferring supplies a distance of 1,500 feet when 30 conveyors are used in tandem.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number and date of this specification.
b. When a first article is not required for inspection and approval, (see 3.2 and 6.3).
c. When slinging devices are required (see 3.18).
d. When tiedowns are required (see 3.19).
e. When type F or G treatment and painting is required (see 3.23).
f. Degree of preservation and degree of packing required (see 5.1 and 5.2).

6.3 First article. When a first article inspection is required, the items should be a preproduction model. The first article should consist of one conveyor. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, tests, and approval of the first article test results and disposition of the document's first article(s).

Custodians:
Army - ME
Navy - SA
Air Force - 84

User activities:
Navy - MC, YD, SH

Review activity:
DLA - CS

Preparing activity:
Army - ME

Project 3910-0067

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-11085D	Conveyor, Belt; (Flat, Skid-Mounted, Electric-Motor-Driven, 24-Inch-Wide Belt, 50-Foot-Long Frame; Capacity, 25 Pounds Per Foot, 75 Tons per Hour)

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.