MILITARY SPECIFICATION

GENERATOR, HYDROGEN

(HYDROGEN GENERATOR ML-303( )/TM)

This amendment forms a part of Military Specification MIL-G-11127B(EL), 29 October 1963.

1. Paragraph 2.1 - Replace applicable documents listed under Specifications, Federal and Military with the following:

SPECIFICATIONS

FEDERAL

QQ-S-571	Solder, Lead Alloy, Tin Lead Alloy, and Tin Alloy, Flux Cored Ribbon and Wire, and Solid Form
UU-B-36	Bag, Paper
PPP-B-566	Boxes, Folding, Paperboard
PPP-B-636	Box, Fiberboard
PPP-P-291	Paperboard, Wrapping, Cushioning
PPP-T-45	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing
PPP-T-76	Tape, Pressure-Sensitive Adhesive Paper, Water Resistant (For Carton Sealing)
PPP-T-97	Tape, Pressure Sensitive Adhesive, Filament Reinforced

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:07Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS (con't)

MILITARY

MIL-P-116	Preservation, Methods Of
MIL-M-13231	Marking of Electronic Items
MIL-F-14072	Finishes for Ground Signal Equipment
MIL-B-43291	Box, Fiberboard, Corrugated, Double-Wall, Weather Resistant

2. Delete Section 5 (Preparation for Delivery) in its entirety and insert the following:

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. - Preservation and packaging shall be level A or C as specified (see 6.1.b).

5.1.1 Level A. -

5.1.1.1 Cleaning. - Hydrogen Generator ML-303( )/TM shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. - Hydrogen Generator ML-303( )/TM shall be dried in accordance with the applicable procedure of MIL-P-116.

5.1.1.3 Preservation application. - None required.

5.1.1.4 Unit packaging. - Unit packaging shall be in accordance with the methods prescribed in MIL-P-116 as specified herein.

5.1.1.4.1 Technical Manual. - Each technical manual shall be packaged method 1C-1.

5.1.1.4.2 Prepackaging. - Place and firmly secure the outlet tube gasket, required for initial operation, inside the outlet tube. Secure one each punch to the body cylinder by means of pressure-sensitive tape conforming to PPP-T-76.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:07Z
Check the source to verify that this is the current version before use.

5.1.1.4.3 Outlet tube (spare). - Each outlet tube shall be packaged method III. Cushion tube by wrapping in flexible paperboard conforming to PPP-P-291, type I. Secure the cushioning with tape conforming to PPP-T-45, type III, grade B. Place the cushioned tube within a close-fitting box conforming to PPP-B-566. Close the box in accordance with the appendix of the box specification.

5.1.1.4.4 Body cylinder. - No packaging required. Secure the outlet tube, required for initial operation, to the body cylinder.

5.1.1.4.5 Gaskets, outlet tube (spares). - Package gaskets method III by inclosing within a close-fitting bag conforming to UU-B-36. Close bag by stapling.

5.1.1.4.6 Consolidated package. - Place the items packaged as specified in 5.1.1.4.2 through 5.1.1.4.5 within a close-fitting fiberboard box conforming to PPP-B-636, W5c. Place the technical manuals, packaged as specified in 5.1.1.4.1, on top of the items, directly under the lid of the box. Fill all voids with paperboard conforming to PPP-P-291 to prevent movement. Closure shall be in accordance with the appendix of the box specification. In addition, seal all seams and joints with tape, not less than two inches wide, conforming to PPP-T-76.

5.1.2 Level C. - Each Hydrogen Generator ML-303( )/TM shall be preserved and packaged in a manner that will afford protection against corrosion, deterioration and damage during shipment from the supply source to the first receiving activity.

5.2 Packing. - Packing shall be level A, B or C as specified (see 6.1.b).

5.2.1 Level A. - A quantity of Hydrogen Generator ML-303( )/TM packaged as specified in 5.1, shall be packed within a close-fitting fiberboard box conforming to PPP-B-636, type CF, class weather-resistant, special requirements or MIL-B-43291. Closure shall be in accordance with the appendix of the applicable box specification. The shipping containers shall be reinforced by pressure-sensitive filament tape banding conforming to PPP-T-97, type IV in accordance with the appendix of the applicable box specification.

5.2.2 Level B. - A quantity of Hydrogen Generator ML-303( )/TM, packaged as specified in 5.1, shall be packed within a close-fitting fiberboard box conforming to PPP-B-636, type CF, class domestic, special requirements. Closure shall be in accordance with the appendix of the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:07Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. - Hydrogen Generator ML-303( )/TM, packaged as specified in 5.1, shall be packed in shipping containers in a manner that will afford adequate protection against damage to the package and its contents during shipment from the supply source to the first receiving activity. Shipping containers shall comply with the rules and regulations of the common carrier as applicable to the mode of transportation.

5.3 Marking. - In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

3. *Delete: Paragraph 6.1.b in its entirety.*

Insert: Paragraph 6.1.b Levels of preservation, packaging, and packing (see section 5).

CUSTODIAN
ARMY-EL

PREPARING ACTIVITY
ARMY-EL
PROJECT NO. 3655-A031

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:07Z
Check the source to verify that this is the current version before use.