MIL-P-11082C

30 April 1969
SUPERSEDING
MIL-P-11082B
1 October 1965

MILITARY SPECIFICATION

PLOTTING SHEET, PLANETABLE (UNMOUNTED, WHITE, SMOOTH SURFACE, HEAVY, GRIDDED)

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of gridded planetable plotting paper.

1.2 Classification.- The planetable plotting paper shall be furnished in the following sizes, as specified, with a tolerance of ± 1/16 inch in each direction (see 6.2):

Size A	-	18 by 24 inches.
Size B	-	22 by 30 inches.

* 2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

UU-P-223	-	Paper, Drawing.
UU-P-268	-	Paper, Kraft, Untreated, Wrapping.
PPP-B-26	-	Bag, Plastic, polyethylene.
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock Corner.
PPP-B-636	-	Box, Fiberboard.
PPP-B-1055	-	Barrier Material, Waterproof, Flexible.
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.
PPP-T-45	-	Tape, Gummed, Paper, Reinforced and Plain, for Sealing and Securing.
PPP-T-60	-	Tape, Pressure-Sensitive, Adhesive, Waterproof, For Packaging.
PPP-T-76	-	Tape, Pressure Sensitive, Adhesive Paper (For Carton Sealing).

FSC 7530

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking for Shipment and Storage.
MIL-STD-147	-	Palletized and Containerized Unit Loads, 40" x 48" Pallets, Skids, Runners, or Pallet-Type Base.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications.- The following publications, of the issues in effect on date of invitation for bids, form a part of this specification:

AMERICAN TRUCKING ASSOCIATIONS, INC.

National Motor Freight Classification

(Application for copies should be addressed to the American Trucking Associations, Inc., 1616 P Street, Washington, D.C. 20036.)

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification

(Application for copies shall be addressed to the Uniform Classification Committee, 202 Union Station, Chicago, Ill. 60606.)

3. REQUIREMENTS

3.1 Description.- The planetable sheet shall consist of a sheet of heavy paper with a rectangular grid printed on one surface.

* 3.2 Paper.- The grid shall be printed on drawing paper conforming to type I, class 1, style A basis weight 70 pounds (17 x 22 - 500) of UU-P-223 and shall be white in color.

* 3.3 Printing and inks.- The ink used for printing the grid lines and markings shall be a waterproof black. The grid lines shall be clean cut with uniform width and ink coverage throughout, and there shall be no skipped areas, spreading, smearing or feathering of the ink.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

* 3.4 Grid.- The grid system shall be furnished in 1,000 yard grids with 1/25,000 scale or in 1,000 meter grids with 1/25,000 scale, as specified (see 6.2), and shall conform to the applicable requirements in table I. The grid rectangle shall be parallel to the edges of the base sheet and centered thereon. Grid lines shall be between 0.007 and 0.010 inch in width, and shall extend only to the edges of the grid system, not to the edge of the base sheet. The distance between centers of any two grid lines and the diagonal measurement of the square shall be accurate to ± 0.01 inch (0.26 mm) when measured as specified in 4.4.2.2.

TABLE I.- Grid requirements

Grid	Scale	Spacing of grid lines	Diagonal measurement	Number of grid lines Size A Vert	Size A Horiz	Size B Vert	Size B Horiz	Markings
1,000 yard	1/25,000	1.44 in.	2.04 in.	17	13	21	16	1,000-YARD GRID SCALE 1/25,000
1,000 meter	1/25,000	40 mm	56.57 mm	--	--	19	14	1,000-METER GRID SCALE 1/25,000

3.5 Markings.-

* 3.5.1 Markings for 1,000-yard grid, size A and 1,000-meter grid, size B.- Applicable markings, shown in table I, shall be printed near the bottom of each sheet, not less than 0.1 inch from the lower edge, equidistant from the ends, and outside the grid rectangle. The letters shall be 0.15 inch ± 0.05 inch high and shall be clear and distinct.

* 3.5.2 Markings for 1,000-yard grid, size B.- Applicable markings, shown in table I, shall be printed near the bottom of each sheet, not less than 1/16 inch (.0625 inch) from the lower edge equidistant from the ends and outside the grid rectangle. The letters shall be 0.063 ± 0.016 inch high and shall be outside the grid rectangle and shall be clear and distinct.

3.6 Workmanship.- The planetable plotting paper covered by this specification shall be free from dirt, tears, cuts, folds or wrinkles and shall be clean cut without nicks or ragged edges within the levels of quality established herein.

* 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Inspection.- Sampling for inspection shall be performed in accordance with MIL-STD-105, except where otherwise indicated.

4.2 Component and material inspection.- In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings, and standards unless otherwise excluded, amended, modified or qualified in this specification or applicable purchase documents.

4.3 Inspection of the end item.-

4.3.1 Examination of the end item.- The end item shall be examined in accordance with the defects set forth in the applicable paragraphs at the inspection levels and acceptable quality levels (AQLs) in 4.3.1.5. Random samples shall be drawn from each lot of the end item for examination of visual dimensional, count and preparation for delivery defects. The lot size for the purpose of determining the sample size, in accordance with MIL-STD-105, shall be expressed in units of intermediate package for examinations in 4.3.1.1, 4.3.1.2 and 4.3.1.3 and in units of shipping containers or palletized unit loads for examination under 4.3.1.4.

4.3.1.1 Examination for visual defects.- The sample unit for this examination shall be one sheet. Both sides of the sheet shall be examined.

Examine	Defects
Appearance	Color and texture not uniform, not as specified. Surface not smooth. Not clean, any discoloration or mark affecting appearance.
Construction and workmanship	Any hole, tear, cut, crease, wrinkle or fold. Edges ragged, smashed, uneven, not square cut.
Grid lines	Not clear and distinct, not straight. Not color ink specified, any smearing or feathering. Printed on both sides of sheet, or lines missing. Vertical and horizontal lines do not form squares. Vertical and horizontal lines not respectively parallel. Intersections not clear and sharp. Grid rectangle not parallel to, and not centered on base sheet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

Examine	Defects
Marking	Omitted, incorrect, incomplete or illegible. Any portion inside grid rectangle or on grid line. Not printed near bottom of sheet equidistant from ends.

* 4.3.1.2 Examination for defects in dimensions.- The sample unit for this examination shall be one planetable sheet.

Examine	Defects
Sheet length and width	Varies from specified dimension by more than ± 1/16 inch.
Number of grid lines vertical and horizontal	Not as specified for applicable size (see table I).
Distance of markings from bottom of sheet	
1,000 yard grid	
Size A	Less than 0.1 inch from bottom.
Size B	Less than 0.063 inch from bottom.
1,000 meter grid, size B	Less than 0.1 inch.
Height of letter in marking	
Sizes A and B (1,000 yard grid and size B, 1,000 meter grid)	Less than 0.10 inch. More than 0.20 inch.
Size B, 1,000 yard grid	Less than 0.047 inch. More than 0.079 inch.

4.3.1.3 Examination of the end item for count.- The sample unit for this examination shall be one package of planetable sheets. The average count per package shall be not less than the specified or indicated quantity.

* 4.3.1.4 Examination of preparation for delivery requirements.-

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:05Z
Check the source to verify that this is the current version before use.

4.3.1.4.1 Examination for packaging, packing and marking.- An examination shall be made to determine that packaging, packing and marking requirements of Section 5 of this specification are complied with. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery except that it shall not be palletized and need not be sealed. Shipping containers fully prepared for delivery that have not been palletized shall be examined for defects of closure. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be S-2 and the AQL shall be 2.5 defects per hundred units.

Examine	Defects
Markings (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Any component missing. Any component damaged.
Workmanship	Inadequate application of components, such as incomplete closure of container flaps, improper taping, loose strapping, inadequate stapling. Bulged or distorted container.
Content	(To reflect Section 5 requirements.)

4.3.1.4.2 Examination for palletization.- An examination shall be made to determine that the palletization requirements of Section 5 of this specification are complied with. Defects shall be scored in accordance with the list below. The sample unit shall be one palletized unit load fully prepared for delivery. The lot size shall be the number of palletized unit loads in the end item inspection lot. The inspection level shall be S-1 and the AQL shall be 6.5 defects per hundred units.

Examine	Defects
Finished dimension	Length, width or height exceeds specified maximum requirement.
Palletization	Not as specified. Container pattern not as specified. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits.
Marking	Omitted; incorrect; illegible; of improper size, location, sequence or method of application.

Source: https://assist.dla.mil -- Downloaded: 20260-17T15:05Z
Check the source to verify that this is the current version before use.

* 4.3.1.5 Inspection levels and acceptable quality levels (AQL's)for examination.- The inspection levels, for determining the sample size, and acceptable quality levels (AQL's) expressed in defects per 100 units shall be as follows:

Examination paragraph	Inspection levels	AQL
4.3.1.1	I	2.5
4.3.1.2	S-2	4.0
4.3.1.3	S-2	---
4.3.1.4.1	S-2	2.5
4.3.1.4.2	S-1	6.5

4.3.2 Testing of the end item.- The end item shall be tested for the characteristics in table II for each lot of material. The sample unit shall be one sheet. The lot size shall be expressed in units of individual packages; no more than one sample unit shall be drawn from any one package. The inspection level, for the purpose of determining the sample size in accordance with MIL-STD-105, shall be S-1 and the acceptable quality level (AQL), shall be 2.5 expressed as defects per one hundred sample units.

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:05Z
Check the source to verify that this is the currentversion before use.

INSTRUCTIONS FOR TESTING OF THE END ITEM

TABLE II

CHARACTERISTIC	Specification Reference		Requirements Applicable To		Number Determinations	Results Reported As		Inspect Level	AQL
	Requirement	Test Method	Individ Unit	Lot Aver	Per sample unit	Pass or Fail	Numerically to Nearest 1/		
Grid									
1,000-yard grid	3.4 and Table I	4.4.2.2	X		Average of 5		0.01 in.		
Scale 1/25,000									
Diagonals each direction	3.4 and Table I	4.4.2.2	X		Average of 5 in each direction		0.01 in.		
1,000-meter grid	3.4 and Table I	4.4.2.2	X		Average of 5		0.1 mm		
Scale 1/25,000									
Diagonals each direction	3.4 and Table I	4.4.2.2	X		Average of 5 in each direction		0.1 mm		
Thickness of and distance between grid lines	3.4	4.4.2.2	X		5 2/		0.001 in.		

1/ Test results shall include all values on which tests are based.

2/ No individual measurement shall exceed the maximum or minimum requirement.

AMXRE Form 598
8 February 1965

Source: https://assist.dla.mil -- Downloaded: 2026-01-17T15:05Z
Check the source to verify that this is the current version before use.

4.4 Tests.-

* 4.4.1 Certification.- Unless otherwise specified a certificate of compliance is required and will be acceptable for the requirement in 3.5 that the ink be waterproof.

4.4.2 Measurements.-

4.4.2.1 Conditioning.- All measurements in the testing of the end item shall be made under uniform atmospheric conditions at a temperature of 73° ± 3.5°F. and a relative humidity of 50 ± 2 percent. Paper shall be conditioned at least 12 hours before it is tested.

4.4.2.2 Grid lines.- The measurements for the thickness and distance between grid lines shall be made with a pocket comparator or other instrument suitable to the purpose.

5. PREPARATION FOR DELIVERY

5.1 Packaging.- Packaging shall be level A or C as specified (see 6.2).

5.1.1 Level A.- One hundred plotting sheets of one size only shall be evenly stacked and completely wrapped with waterproofed barrier material conforming to C-1 of PPP-B-1055. A minimum 1-inch overlap shall be provided at all overlapping edges. The wrap shall be securely sealed at all seams, joints and closures with 2-inch minimum width pressure-sensitive tape conforming to PPP-T-60 or PPP-T-76. Alternatively, the stacked sheets shall be completely wrapped with 30-pound minimum basis weight kraft paper conforming to grade B of UU-P-268. The paper wrap shall be secured with 2-inch minimum width gummed paper tape conforming to type III, grade B of PPP-T-45. The paper wrapped package shall then be placed in a close-fitting 0.0015-inch minimum thickness polyethylene bag conforming to type I or II, grade A, style 1 of PPP-B-26. The polyethylene bag may also be closed by double-folding he plastic material at the mouth and taping it to the bag body with the specified PPP-T-60 or PPP-T-76 tape. Prior to or during the final closure operation excess air within the polyethylene bag shall be expelled.

5.1.2 Level C.- Plotting sheets shall be packaged to afford adequate protection against physical damage during shipment from the supply source to the first receiving activity. The supplier may use his standard practice when it meets this requirement.

5.2 Packing.- Packing shall be level A, B or C as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

5.2.1 Level A.- Plotting sheets of one size only, packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style FTC, grade V2s of PPP-B-636; overseas type, style A or J, type 2 load of PPP-B-601; or class 2, style 2 or 4, type 2 load of PPP-B-621, as specified (see 6.2). Each PPP-B-621 container shall be lined with a full height liner and top and bottom pads fabricated from class weather-resistant fiberboard material conforming to PPP-F-320. The top and bottom pads shall have dimensions equal to 1/8-inch less than the length and width inside dimensions of the liner fitted within the container. Each shipping container shall be closed and reinforced in accordance with the appendix of the applicable container specification. The weight of the contents of each fiberboard container shall not exceed 65-pounds and for each wood container shall not exceed 150-pounds.

5.2.2 Level B.- Plotting sheets of one size only, packaged as specified in 5.1, shall be packed in a snug-fitting shipping container conforming to style FTC, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636; domestic type, style A or J, type 2 load of PPP-B-601; or class 1, style 2 or 4, type 2 load of PPP-B-621, as specified (see 6.2). Each PPP-B-621 container shall be lined with a full height liner and top and bottom pads fabricated from class domestic fiberboard material conforming to PPP-F-320. The top and bottom pads, shall have dimensions equal to 1/8-inch less than the length and width inside dimensions of the liner fitted within the container. Each shipping container shall be closed in accordance with the appendix of the applicable container specification. The weight of the contents of each fiberboard container shall not exceed 65-pounds and for each wood container shall not exceed 150-pounds.

5.2.2.1 When specified (see 6.2), the fiberboard shipping container specified in 5.2.2, shall be a grade V3c or V3s fiberboard box fabricated in accordance with PPP-B-636 and closed in accordance with the appendix of the container specification. The shipping container material may also be grade V4s of PPP-F-320.

5.2.3 Level C.- Plotting sheets, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery to destination at the lowest transportation rate for such supplies. Containers shall be in accordance with Uniform Freight Classification Rules or National Motor Freight Rules, as applicable.

5.3 Palletization.- Unless otherwise specified (see 6.2), plotting sheets of one size only, packed as specified in 5.2, shall be palletized in accordance with Load Type I of MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with the appendix of MIL-STD-147. Interlocking of loads shall be effected by reversing

Source: https://assist.dla.mil -- Downloaded: 202610-17T15:05Z
Check the source to verify that this is the current version before use.

the pattern of each course. If the container is of a size which does not conform to any of the container patterns specified in MIL-STD-147, the container pattern used shall be approved by the contracting officer.

5.4 Marking.- In addition to any special marking required by the contract or order, interior packages, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use.- The gridded planetable plotting paper is intended for use in plotting planetable surveys and related operations.

6.2 Ordering data.- Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Size of base sheet required (see 1.2).
c. Grid and scale required (see 3.4).
d. Number of sheets per package (see 5.1.1).
e. Selection of the applicable levels of packaging and packing (see 5.1 and 5.2).
f. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
g. Type of shipping container desired for level A or B packing (see 5.2.1 and 5.2.2).
h. When palletization is not required (see 5.3).

* 6.3 The margins of this specification were marked with an asterisk to indicate where changes (additions, corrections, modifications, deletions) from the prior issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and suppliers are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:

Army - GL
Air Force - 84

Review activities:

Army - ME
Air Force - 84,85

User activity:

Navy - MC

Preparing activity:

Army - GL

Project No. 7530-0148

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY
U. S. Army Natick Laboratories
Natick, Massachusetts 01760

POSTAGE AND FEES PAID
DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

Commanding General
U. S. Army Natick Laboratories
ATTN: AMXRES-EQS
Natick, Massachusetts 01760

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T15:05Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION MIL-P-11082C
Plotting Sheet, Planetable (Unmounted, White, Smooth Surface, Heavy, Gridded)

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026l0-17T15:05Z
Check the source to verify that this is the currentversion before use.