INCH-POUND

A-A-55001/5C
21 April 2017
SUPERSEDING
A-A-55001/5B
May 23, 1996

COMMERCIAL ITEM DESCRIPTION

DISK DRIVE UNIT, SEVEN DRIVE, SMALL COMPUTER SYSTEM INTERFACE (SCSI), HALF HEIGHT, EXTERNAL, CD-ROM, AND OTHER ACCESSORIES

The General Services Administration has authorized the use of this commercial item description (CID) for all federal agencies.

1. SCOPE. This CID covers the general requirements for a seven-drive, multimedia, half height, CD-ROM, disk drive unit with one controller card, cabinet, interface cables, seven cartridges, software programs and other accessories as specified. CD-ROM disk drive units covered by this CID are intended for commercial/industrial applications.

2. CLASSIFICATION. This CID uses a classification system which is included in the Part or Identification Number (PIN). The PIN shall be AA55001/05- (plus a dash number from table I). Complete PIN example: AA55001/05-02 (see 6.1).

3. SALIENT CHARACTERISTICS

3.1 Design and construction. CD-ROM disk drive units supplied to this CID shall be as specified herein.

3.2 Weight. The weight of this CD-ROM disk drive unit shall not exceed 21 kilograms (46 pounds) as a complete unit.

3.3 CD-ROM disk drives.

3.3.1 Memory storage capacity. The memory storage capacity of this CD-ROM disk drive unit shall be a minimum of 4.2 gigabytes (GB).

3.3.2 Form factor. The external form factor of each CD-ROM disk drive shall be 130 millimeters (mm) (5.25 inches) half height.

Comments, suggestions, or questions on this document should be addressed to DLA Troop Support - Industrial Hardware Division (ATTN: Code FHTE), 700 Robbins Avenue, Philadelphia, PA 19111-5096 or email trpsptspecspa@dla.mil. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

TABLE I.
Characteristics.

AA55001/05-	Characteristics	CD-audio	Transfer rate	Access time	Interface	Bus architecture supported
01	CD-ROM Multimedia PC Marketing Council (MPC) level II compliant (double-speed) disk drive	Yes	300 kilobytes (kb) per second minimum	Less than or equal to 325 milliseconds (ms)	SCSI-2	Industry Standard Architecture (ISA) 16-bit
02	CD-ROM MPC level II compliant (double-speed) disk drive	Yes	300 kb per second minimum	Less than or equal to 325 ms	SCSI-2	Extended Industry Standard Architecture (EISA) 32-bit
03	CD-ROM MPC level II compliant (double-speed) disk drive	Yes	300 kb per second minimum	Less than or equal to 325 ms	SCSI-2	Micro Channel Architecture for IBM (MCA) 16-bit
04	CD-ROM MPC level II compliant (quad-speed) disk drive	Yes	600 kb per second minimum	Less than or equal to 250 ms	SCSI-2	Industry Standard Architecture (ISA) 16-bit
05	CD-ROM MPC level II compliant (quad-speed) disk drive	Yes	600 kb per second minimum	Less than or equal to 250 ms	SCSI-2	Extended Industry Standard Architecture (EISA) 32-bit
06	CD-ROM MPC level II compliant (quad-speed) disk drive	Yes	600 kb per second minimum	Less than or equal to 250 ms	SCSI-2	Micro Channel Architecture for IBM (MCA) 16-bit

3.3.4 Front loadable. This CD-ROM disk drive unit contains seven CD-ROM disk drives and shall be front loadable with seven cartridges (i.e., caddies). A cartridge is not required if the unit has a loading tray that does not require a cartridge.

3.3.5 Multiple sectors. Each CD-ROM disk drive shall be able to read multiple sectors.

3.3.6 File structure compatibility. Each CD-ROM disk drive shall be ISO 9660 compatible.

3.3.7 Buffer memory capacity. The buffer memory capacity shall be a minimum of 64 kb.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

3.3.8 Mean time between failures (MTBF). The MTBF shall be 50,000 hours minimum.

3.3.9 Operation temperature. The operation temperature shall be +5 C to +40 C (±2 C).

3.3.10 Seek error. The seek error shall be $10x10^{-6}$ or less.

3.3.11 Relative humidity (Rh). The Rh operating range shall be 30 percent to 70 percent Rh (±2 percent).

3.3.12 Operation vibration. This CD-ROM disk drive unit shall be able to withstand 0.1 G_{o-p} at 7 hertz (Hz) to 300 Hz in x, y, and z directions without the loss of data transmission.

3.3.13 Nonoperating vibration. The nonoperating vibration shall be 1.0 G_{o-p} at 7 Hz to 300 Hz.

3.3.14 Operational shock. This CD-ROM disk drive unit shall be able to withstand 0.4 G_{o-p} at 11 ms half-sine wave without the loss of data transmission.

3.3.15 Nonoperating shock. The nonoperating shock shall be 20 G_{o-p} at 11 ms half-sine wave.

3.3.16 CD-audio compatibility. This CD-ROM disk drive unit shall be capable of reproducing CD audio. A volume control and headphone stereo mini-jack for each CD-ROM disk drive shall be located in the front of the unit.

3.3.17 SCSI addressing. SCSI addressing shall be external and user selectable.

3.3.18 Self-cleaning mechanism. Each CD-ROM disk drive shall have a self-cleaning optical pickup mechanism unless the CD-ROM disk drives are completely sealed to prevent dust intrusion.

3.3.19 Busy/in-use indicator light. This CD-ROM disk drive unit shall be supplied with at least one busy/in- use indicator light for each CD-ROM disk drive.

3.3.20 Photo CD compatible. These CD-ROM multimedia disk drive units shall be multi-session photo CD compatible.

3.3.21 Federal Communications Commission (FCC) approval. This CD-ROM disk drive unit shall be certified to FCC class B computing devices pursuant to subpart J of part 15 of FCC rules. A CD-ROM disk drive unit consists of a number of connected CD-ROM disk drives within a single cabinet as a distinct fully integrated unit.

3.3.22 UL approval. The complete CD-ROM disk drive unit shall be certified to comply with UL 60950-1 for electronic data processing (EDP) equipment. Certification shall be performed by UL or another nationally recognized testing laboratory licensed by the United States Government to certify electrical products for compliance to UL standards.

3.4 Cabinet.

3.4.1 Cabinet dimensions. The cabinet dimensions shall be 66 cm (26 inches) in height maximum, 30.5 cm (12 inches) in width maximum, and 50.75 cm (20 inches) in length maximum and functionally able to accommodate seven CD-ROM disk drives.

3.4.2 Power supply. A power supply shall be enclosed which will support auto sensing or manual switching for 110 volts (V) AC nominal and 220 VAC nominal.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

3.4.3 Operating frequency. The operating frequency shall be 50/60 Hz.

3.4.4 Power dissipation. The power dissipation shall be no more that 85 watts.

3.4.5 Power switch. This CD-ROM disk drive unit shall be supplied with an external ON/OFF power switch.

3.4.6 Temperature maintaining cooling fan. This CD-ROM disk drive unit shall be supplied with a cooling fan that maintains the operational temperature range of the CD-ROM disk drives.

3.4.7 Input/output (I/O) port. This CD-ROM disk drive unit shall be supplied with at least one built-in I/O port. If more than one I/O port is built in, an external terminator plug must be supplied with each CD-ROM disk drive unit.

3.4.8 Cabinet material. The cabinet shall be constructed of a metal or a combination of metal and plastic materials.

3.5 SCSI controller card.

3.5.1 SCSI controller card characteristics. The controller card shall be 16-bit or 32-bit as specified in table I and shall be MS DOS compatible with IBM PC-XT, IBM PC-AT, 386sx, 386, 486sx, 486, or any 100 percent IBM compatible computer.

3.6 Cables.

3.6.1 Cables. This CD-ROM disk drive unit shall include the necessary cabling and power cords intelligence to run selected operations on IBM PC-XT, IBM PC-AT, 386sx, 386, 486sx, 486, or any 100 percent IBM compatible computer as specified as follows.

3.6.2 Interface cable. A compatible host to CD-ROM disk drive unit SCSI interface cable shall be provided.

3.6.3 Interface cable length. The interface cables length shall be 0.6 meter (2 feet) minimum.

3.6.4 Power cable. The power cable shall be a UL rated three prong power cable 1.5 meters (5 feet) in length.

3.7 Technical documentation. CD-ROM disk drive units shall be provided with technical documentation including owner's manual, and related information on operation and use.

3.8 Software. CD-ROM disk drive units shall be supplied with a copy of Microsoft Extension (MSCDEX) CD-ROM operating program and installation instructions on a 90 mm (3.50 inches) floppy disk.

3.9 Operating system software supported. This CD-ROM disk drive unit shall support Novell NetWare version 3.11 or higher, MS-DOS and PC-DOS version 3.30 or higher operating system software.

3.10 Software driver interface. This CD-ROM disk drive unit shall be compatible with Advanced SCSI Programming interface (ASPI); Novell NetWare driver with version 4.0 Media Manager interface.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

3.11 Accessory kit. Each CD-ROM disk drive unit shall be provided with the following accessories.

a. SCSI controller card.

b. SCSI terminator (plug or switchable).

c. Cable (host to CD-ROM disk drive unit).

d. Instruction manual(s).

e. Software.

4. QUALITY ASSURANCE PROVISIONS. Quality assurance provisions shall be as specified in A-A-55001.

5. PACKAGING. Packaging shall be as specified in A-A-55001.

6. NOTES

6.1 PIN. The PIN should be used for Government purposes to buy products to this CID. See section 2 for PIN format example.

6.2 CD-ROM disk drive unit. A CD-ROM disk drive unit consists of a number of connected CD-ROM disk drives within a single cabinet as a distinct fully integrated unit.

6.2.1 CD-ROM disk drive. A CD-ROM disk drive is a computer peripheral that plays CD-ROM disks.

6.3 Multimedia PC Marketing Council (MPC) level II minimum requirements. The following requirements are minimum requirements which a CD-ROM disk drive must meet to be compliant to MPC level II.

a. Double speed with CD-DA outputs (capable of sustained 300 kilobytes/second transfer rate).

b. No more than 40 percent of the CPU bandwidth may be consumed when maintaining a sustained transfer rate of 150 kilobytes/second.

c. Average seek time of 400 ms or less.

d. 10,000 hours MTBF.

e. CD-ROM XA ready (mode 1 capable, mode 2 form 1 capable, mode 2 form 2 capable).

f. Multisession capable.

g. MSCDEX 2.2 driver or equivalent that implements extended audio APIs.

h. Subchannel Q support (P, R-W optional).

6.4 CAGE code. For ordering purposes, inventory control, and submission of these CD-ROM disk drive units to DESC under the Military Parts Control Advisory Group (MPCAG) evaluation program, CAGE code 58536 should be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

6.5 Source of documents.

Commercial Item Description

A-A-55001 - Disk Drive Unit, Half Height, CD-ROM, Small Computer System Interface (SCSI), and Other Accessories, General Requirements for.

(Copies of this CID are available online at: ASSIST Online (https://assist.dla.mil) or ASSIST Quick Search (http://quicksearch.dla.mil).)

Other Publications

INTERNATIONAL STANDARDS OFFICE (ISO)

ISO 9660 - Information Processing - Volume and File Structure of CD ROM for Information Interchange.

(Applications for copies should be addressed to the International Standards Organization, 3 Rue De Varembe' Geneve, Switzerland.)

UNDERWRITERS LABORATORIES, INCORPORATED (UL)

UL 60950-1 - Safety of Information Technology Equipment – Safety – Part 1: General Requirements.

(Applications for copies should be addressed to the Underwriters Laboratories, Incorporated, 333 Pfingsten Road, Northbrook, IL 60062-2096.)

6.6 Ordering data. Ordering data shall be as specified in A-A-55001.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

6.7 Commercial products. As part of the research effort, this CID was coordinated with the following manufacturers of commercial products. At the time of CID preparation and coordination, these manufacturers were known to have commercial products that would meet the requirements of this CID. (NOTE: This information should not be considered as a list of approved manufacturers or be used to restrict procurement to only the manufacturers shown.)

MFGR's CAGE	MFGR's name and address
0YKR0	Future Echo 9559 Irondale Avenue Chatsworth, CA 91311-5007 (818) 709-2091
8Y261	Government Technology Services, Incorporated 4100 Lafayette Center Drive Chantilly, VA 22021-1200 (703) 502-2564
2S373	SMS Data Products Group, Incorporated 1501 Farm Credit Drive McLean, VA 22102-5004 (703) 883-4399
0ZAW7	TAC Systems, Incorporated 1031 Putman Drive Huntsville, AL 35816-2271 (205) 721-1976
0BU86	Todd Enterprises, Incorporated 31 Water Mill Lane Great Neck, NY 11021-4234 (718) 343-1040

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

6.8 Government users. To acquire information on obtaining these CD-ROM disk drive units from the Government inventory system, contact Defense Electronics Supply Center, ATTN: DESC-EOC, 1507 Wilmington Pike, Dayton, OH 45444-5270, or telephone (513) 296-5307.

6.8.1 NSNs. The following is a list of NSNs assigned which correspond to this CID. The list is for information only and may not be indicative of all possible NSNs associated with the CID. For up to date information on assigned NSNs, please contact the Defense Electronics Supply Center, ATTN: DESC-EOC, 1507 Wilmington Pike, Dayton, OH 45444-5270, or telephone (513) 296-5307.

Dash number (see table I) AA55001/05-	NSN
01	7025-01-379-4415
02	7025-01-379-4431
03	7025-01-397-5575
04	7025-01-413-5857
05	7025-01-413-5862
06	7025-01-413-5867

6.9 Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Preparing Activity:

DLA-IS

Project 7025-2017-005

NOTE: The activities listed above were interested in this document as of the date of document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.