A-A-55006
24 September 1991

COMMERCIAL ITEM DESCRIPTION

"V" BLOCKS, SOLID BODY, WITHOUT CLAMP

The General Services Administration has authorized the use of this commercial item description in preference to the Type I, Style F of A-A-51150.

Abstract. This description covers "V" blocks of the solid body type without a clamping device which is used for inspection of parts and other tool room operations. The "V" blocks shall be similar to that shown in figure 1.




FIGURE 1. "V" Block solid body.

Classification. The "V" blocks shall be furnished in the following grades. The grade to be furnished shall be as specified (see ordering data).

Grade A - Alloy steel
Grade B - Mild steel
Grade C - Cast iron

Salient characteristics.

1. Design. The "V" blocks shall be provided with a 90 degree "V" groove, 45 degrees from center cut and extending the entire length of the "V" block. At the apex of the groove, a slot shall extend the length of the block providing for chip relief. Unless otherwise specified (see ordering data), the "V" blocks shall be furnished in sets with V's matched. The blocks shall be plainly marked to identify them as a matched set.

Beneficial comments recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSG, 2163 Airways Blvd., Memphis TN 38114-5213.

AMSC N/A FSC 3460

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

2. Dimensions. The "V" block furnished shall be 3-3/4 inches long by 1-1/4 inches wide by 1-3/8 inches high. The diametrical capacity shall be not less than 1 inch. All dimensions shall be +0.03 inch, -0.00 inch.

3. Hardness. The grade A (alloy steel) "V" block shall be furnished with a hardness of not less than 60 and not more than 65 on the Rockwell "C" scale. Grade B (mild steel) shall have a hardness of not less than 40 and not more than 45 on the Rockwell "C" scale. Grade C (cast iron) shall have a hardness of not less than 150 and not more than 180 Brinell. All tests shall be in accordance with ASTM E 18.

4. Tolerance. The "V" groove shall be central with the sides and square and parallel with all surfaces within 0.0003 inch. All surfaces shall be square with other within 0.002 inch.

5. Surface finish. The surface finish of the "V" block shall have a roughness average (RA) of not greater than 32 microinches when measured in accordance with ASME B46.1. Edges of all exterior surfaces shall be free of sharp edges, fins and burrs.

Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this commercial item description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this commercial item description are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request shall be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Environmental protection. During the manufacture of the V" block, materials hazardous to the ecological system as prohibited by the Federal, state, or local statutes in effect on the date of the contract shall not be used or emitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

Preservation, packaging, packing, labeling, and marking. Preservation, packaging, packing, labeling, and marking shall be as specified in the contract order.

NOTES

Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

a. Title, number, and date of this commercial item description.

b. Quantity required.

c. Grade required (see Para. 3).

d. If other than matched pairs (see Para 1).

CID based part identification number. The following part identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor.

AXXXXX X

----- Grade

---------- CID number

Federal Standard FED-STD-376 is available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19120-5099.

ASTM E 18 is available from American Society for Testing and Materials, 1916 Race street, Philadelphia, PA 19103-1187.

ASME B46.1 is available from The American National Standards Institute, 1430 Broadway, New York, NY 10018-3363.

MILITARY INTEREST:

Custodians

Army - AL
Navy - SH
Air Force 99

Review Activities

Army - AR
Air Force - 84
DLA - GS

CIVIL AGENCY COORDINATION ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

DLA - IP

Project 3460-0163

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.