COMMERCIAL ITEM DESCRIPTION

"V" BLOCK, RIBBED BODY, WITHOUT CLAMP

The General Services Administration has authorized the use of this commercial item description in preference to the Type I, Style E of A-A-51150.

Abstract. This description covers a "V" block of the ribbed body type without a clamping device which is used for inspection of parts and other tool room operations. The "V" block shall be similar to that shown in figure 1.




FIGURE 1. "V" Block ribbed body.

Size. The size to be furnished shall be selected from table I.

TABLE 1. Sizes and capacity.

Size	Length (in.)	Width (in.)	Height (in.)	Diametrical capacity (in.)
1	2-1/4	4	4	3
2	3-1/2	4	4	4
3	5	6	6	5-1/2
4	8	8	8	7

Beneficial comments recommendations, additions, deletions, clarifications, etc., and any data which may improve this document should be sent to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSG, 2163 Airways Blvd., Memphis TN 38114-5213.

AMSC N/A FSC 3460

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

Salient characteristics.

1. Design. The "V" block shall be provided with a 90 degree "V" groove, 45 degrees from center cut and extending the entire length of the "V" block. At the apex of the groove a slot shall extend the length of the block providing for chip relief. The "V" block shall be of the ribbed design to provide strength with light weight. When specified (see ordering data), the "V" block shall be furnished in pairs with "V" matched. The "V" blocks shall be plainly marked to identify them as matched pairs.

2. Materials. The block shall be manufactured of cast iron.

3. Hardness. The hardness for the "V" block shall be not less than 150 and not more than 180 Brinell when tested in accordance with ASTM E 18.

4. Tolerance. The "V" groove shall be central with the sides and square and parallel with all surfaces within 0.0003 inches. All surfaces shall be square with each other within 0.0002 inches. The tolerance of the length, width, and height shall be +.03, -00. The diametrical capacity shall be not less than stated in table I.

5. Surface finish. The surface finish of the "V" block shall have a roughness average (RA) of not greater than 32 microinches when measured in accordance with ASME B46.1. Edges of all exterior surfaces shall be free from sharp edges, fins and burrs.

Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this commercial item description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this commercial item description are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request shall be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

Environmental protection. During the manufacture of the "V" block, materials hazardous to the ecological system as prohibited by the Federal, state, or local statutes in effect on the date of the contract shall not be used or emitted.

Preservation, packaging, packing, labeling, and marking. Preservation, packaging, packing, labeling, and marking shall be as specified in the contract order.

NOTES


Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

a. Title, number, and date of this commercial item description.

b. Size, and quantity required.

c. If matched pairs are required, (see Para 1).

CID based part identification number. The following part identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor.



Federal Standard FED-STD-376 is available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19120-5099.

ASTM E 18 is available from American Society for Testing and Materials, 1916 Race street, Philadelphia, PA 19103-1187.

ASME B46.1 is available from The American National Standards Institute, 1430 Broadway, New York, NY 10018-3363.

MILITARY INTEREST:

Custodians

Army - AL
Navy - SH
Air Force 99

Review Activities

Army - AR
Air Force - 84
DLA - GS

CIVIL AGENCY COORDINATION ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

DLA - IP

Project 3460-0166

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.