COMMERCIAL ITEM DESCRIPTION

WHEEL, POLISHING, CANVAS

The General Services Administration has authorized the use of this commercial item description in preference to GGG-W-301B, type IV, class 1.

Abstract. This description covers polishing wheels manufactured from sections of woven canvas. The wheels are normally used for initial finishing operations on rough surfaces of cast iron, steel, or brass.

Salient characteristics.

1. Design. The polishing wheels shall be of the full disc type (see notes). Several layers of canvas discs shall be sewed together to form a section and then a sufficient number of sewn sections shall be glued together to form the required face width.

2. Material. The polishing wheel shall be manufactured from cotton canvas. The material shall be free from imperfections and contamination that may affect appearance or serviceability.

3. Sewing. The polishing wheels shall be spirally sewn.

4. Hardness. The hardness of the wheel is determined by the spacing between the sewn rows. A medium wheel shall have rows which are sewn 3/8 inch apart, a hard wheel shall have rows sewn 1/4 inch apart, and extra-hard wheel shall have rows sewn 1/8 inch apart. The hardness of the wheel identified as medium, hard, or extra-hard shall be as specified by the procuring activity (see ordering data).

Beneficial comments recommendations, additions, deletions, clarifications, ETC., and any data which may improve this document should be sent to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSG, 2163 Airways Blvd., Memphis TN 38114-5213.

AMSC N/A FSC 3460

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

5. Diameter. The diameter of the wheel to be furnished shall be as specified (see ordering data), and shall be selected from the following diameters.

6 inch, 8 inch, 10 inch
12 inch, 14 inch, 16 inch

6. Width. The face width of the wheels to be furnished shall be as specified (see ordering data), and shall be selected from the following widths.

0.500 inch, 0.625 inch,
0.750 inch, 0.875 inch,
1.000 inch, 1.250 inch

7. Arbor hole diameter. The arbor hole diameter for the wheel furnished shall be as specified (see ordering data), and shall be selected from the following diameters:

0.500 inch, 0.625 inch, 0.750 inch
0.875 inch, 1.000 inch, 1.250 inch

Contractor certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this commercial item description, and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, provided they fall within specified tolerances using conversion tables contained in the latest revision of FED-STD-376, and all other requirements of this commercial item description are met.

If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request shall be made to the contracting officer to determine if the product is acceptable.

The contracting officer has the option of accepting or rejecting the product.

Regulatory requirements. In accordance with section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Environmental protection. During the manufacture of the polishing wheels, materials hazardous to the ecological system as prohibited by the Federal, state, or local statutes in effect on the date of the contract shall not be used or emitted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

Preservation, packaging, packing, labeling, and marking. Preservation, packaging, packing, labeling, and marking shall be as specified in the contract order.

NOTES.

Ordering data. Purchasers should select the preferred options permitted herein, and include the following information in procurement documents:

a. Title, number, and date of this commercial item description.

b. Hardness of wheel.

c. Diameter of wheel.

d. Width of wheel.

e. Diameter of arbor hole.

CID based part identification number. The following part identification numbering procedure is for Government purposes and does not constitute a requirement for the contractor.

AXXXXX X X X X

- X: Arbor diameter: 1 - 0.500 inch, 2 - 0.625 inch, 3 - 0.750 inch, 4 - 0.875 inch, 5 - 1.000 inch, 6 - 1.250 inch
- X: Wheel width: 1 - 0.500 inch, 2 - 0.625 inch, 3 - 0.750 inch, 4 - 0.875 inch, 5 - 1.000 inch, 6 - 1.250 inch
- X: Wheel diameter: A - 6 inch, B - 8 inch, C - 10 inch, D - 12 inch, E - 14 inch, F - 16 inch
- X: Hardness: 1 - Medium, 2 - Hard, 3 - Extra-hard
- AXXXXX: CID number

Definition.

Full disc type. A full disc type polishing wheel is defined as a wheel which is made of individual layers of material which are the full diameter of the wheel.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.

Applicable document.

FED-STD-376 is available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19120-5099.

MILITARY INTEREST:

Custodians

Air Force - 99

Review Activities:

Air Force - 84
DLA - GS

CIVIL AGENCY COORDINATION ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:
DLA - IP

Project 3460-0160

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:41Z
Check the source to verify that this is the current version before use.