INCH-POUND

MIL-B-64043(AR)
AMENDMENT 4
17 September 1996
SUPERSEDING
AMENDMENT 3
6 July 1994

MILITARY SPECIFICATION

BODY, LOADED ASSEMBLY, GENERAL PURPOSE GRENADE: M73

This amendment forms a part of MIL-B-64043(AR), dated 22 August 1983 and is approved for use by the Armament Research, Development, and Engineering Center, U.S. Army, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Paragraph 2.1, SPECIFICATIONS, MILITARY, Add:

"MIL-A-12560 - Armor Plate, Steel, Wrought, Homogeneous (For Use in Combat-Vehicles and for Ammunition Testing)."

PAGE 5

Table I, Body, Loaded Assembly (Dwg. 9334105): Add the following line below Functional Test:

"Penetration test, 5(a), 3.6, 4.5.2.1"

Add Note (a) to NOTES block:

"(a) The five sample units shall be selected from the 229 sample units required for the function test."

PAGE 9

Paragraph 4.4.2.3: Add major defects 104 and 105 as follows:

"104. True position of waveshaper cavity .40% 3.2 Gage
105. True position of booster pellet cavity .40% 3.2 Gage"

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

Paragraph 4.4.2.3, minor defects 201 and 202:

Delete “of” and substitute “to bottom of”.

PAGE 10

Paragraph 4.4.2.4: Add major defect 102 as follows:

“102. Penetration test 5(a) 3.6 4.5.2.1”

Add Note (a) to NOTES block:

“(a) The five sample units shall be selected from the 125 sample units required for major defect 101 (Functional test)”.

PAGE 11

Add paragraph 4.5.2.1 as follows:

“4.5.2.1 Penetration test. Five grenades, from 4.5.2, shall be functioned with PA526 detonators on a single piece of rolled homogeneous armor (RHA) plate. The RHA plate shall conform to the requirements of MIL-A-12560, Class I, and shall be of such a thickness to contain the expected maximum penetration of the grenade. The depth of the penetration shall be measured without cutting the plate. The average of the five penetration readings shall meet the specified penetration depth in the classified annex to this specification. The classified annex may be obtained by requesting it from: Commander, U.S. Army Armament Research, Development, and Engineering Center, Attn: AMSTA-AR-QAC-S, Picatinny Arsenal, NJ 07806-5000.”

The margins of this amendment are marked with vertical lines to indicate where changes to the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1330-0399)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.