MILITARY SPECIFICATION

CAP, NOSE
FOR
ROCKET, HE, 66mm, ANTI-TANK, M72
ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-C-60006A(MU), dated 20 May 1966.

Page 1

Specification title: Delete "M72" and substitute "M72A2".

1.1, line 6: Delete "M72" and substitute "M72A2".

Page 3

3.5 add new paragraph in sequence as follows:

"3.5 Nose cap assembly. The electrical resistance between the ground terminal pin and the nose cap shall not exceed ten ohms."

Page 9

4.3.2.7, delete Minor defect #201 in its entirety.

Add new Minor defect #205 as follows:

"205. Extended length to terminals from open nose cap end ---------- Gage 07013"

Page 10

4.3.3.5, add new paragraph in sequence as follows:

"4.3.3.5 Electrical resistance (see dwg. 10048528) - Major defect - Code No. 07012. This test shall be performed 100 percent. Any nose cap assemblies which are classed defective shall be removed from the lot. This test shall be performed as specified in 4.4.3 using test equipment specified in 4.3.4."

FSC 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:03Z
Check the source to verify that this is the current version before use.

4.4.3 add new paragraph in sequence as follows:

"4.4.3 Electrical resistance. The resistance of the nose cap assembly shall be measured between the ground terminal pin and the nose cap. The assembly shall be classed defective if the resistance exceeds the specified requirement."

Custodian:
Army - MI

Review Activity:
Army - PA

Preparing Activity:
Army - MI

Project No. 1340-A495

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:03Z
Check the source to verify that this is the current version before use.