MILITARY SPECIFICATION

FIRING DEVICE, MULTI-PURPOSE, M142
PARTS, ASSEMBLY, AND PACKING

This amendment forms a part of Military Specification MIL-F-63090A(AR), dated 21 April 1981, and is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1: Drawings - Under list of drawings, add the following:

"9349653 - Test Cap, Blasting, Non-Electric, for M142 Firing Device.

PAGE 37

4.5.1.1: Delete second sentence, "Screw . . . switch." and substitute a new sentence to read:

"Screw coupling base with attached M7 Non-Electric Blasting cap or alternative test cap (Dwg. 9349653) into the switch."

4.5.1.2: (See change to 4.5.1.1).

4.5.1.3: (See change to 4.5.1.1).

4.5.1.4: (See change to 4.5.1.1).

4.5.2: (See change to 4.5.1.1).

PAGE 38

4.5.3: Delete the first sentence, "Condition . . . hours." and substitute a new sentence to read:

"Condition firing devices, with coupling base with attached M7 Non-Electric Blasting cap or alternative test cap (Dwg. 9349653) screwed in, at minus 50° for not less than sixteen (16) hours."

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:10Z
Check the source to verify that this is the current version before use.

5.4 After "Unitization" add "(Palletization)."

5.4.1: Delete "19-48-4116/8S-20PA1002" and substitute "19-48-4116-20PA1002 Appendix 128F."

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1375-A240)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:10Z
Check the source to verify that this is the current version before use.