INCH-POUND

MIL-C-64037 (AR)
AMENDMENT 5
16 January 2001
SUPERSEDING
AMENDMENT 4
19 September 1997

MILITARY SPECIFICATION

CARTRIDGE, HE 60MM, M888 W/FUZE M935
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of MIL-C-64037 (AR), dated 28 February 1983, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

TITLE: Delete prefix "X" from "XM888" and "XM935" in title and all places within this entire specification.

* 2.1.1, Under “MILITARY STANDARDS”, Delete “MIL-STD-105 – Sampling Procedures and Tables for Inspection by Attributes”.

PAGE 4

3.7.6, Line 2: Delete "11 meters" and substitute "15 meters".

PAGE 7

* 4.4.2, Delete first sentence in its entirely and substitute:

"Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major defects shall be in accordance with MIL-STD-1916, Verification Level IV (VL IV), and minor defects shall be in accordance with Verification Level III (VL III).”

AMSC N/A FSC 1310
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

PAGE 8

* 4.4.2.1, Delete "AQL or 100% and substitute "CONFORMANCE CRITERIA".

For each Major defect listed: delete, "0.40%" and substitute "VL IV".

For each Minor defect listed: delete, "0.65%" and substitute "VL III".

PAGE 9

***** 4.4.2.2, Delete "AQL or 100%" and substitute "CONFORMANCE CRITERIA".

For each Major defect listed: delete, "0.40%" and substitute "VL IV".

For each Minor defect listed: delete, "0.65%" and substitute "VL III".

***** 4.4.2.2, Delete Minor 202 in its entirety.

***** 4.4.2.2, Add Under “Critical” as follows: “2 High explosives on threads … 100% … 3.5 … Visual”

PAGE 10

***** 4.4.2.3, Delete "AQL or 100%" and substitute "CONFORMANCE CRITERIA".

For each Major defect listed: delete, "0.40%" and substitute "VL IV".

For each Minor defect listed: delete, "0.65%" and substitute "VL III".

PAGE 11

***** 4.4.2.4, Delete "AQL or 100%" and substitute "CONFORMANCE CRITERIA".

For each Major defect listed: delete, "0.40%" and substitute "VL IV".

For each Minor defect listed: delete, "0.65%" and substitute "VL III".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

4.4.2.4, Special A: Change "label" to "notice(s)".

Major 102: Delete in its entirety.

Critical 1: Delete in its entirety and substitute:

"Major 111 Minimum distance from top of ignition cartridge assembly to edge of fin, incorrect."

Page 12

* 4.4.2.4, Delete "AQL or 100%" and substitute "CONFORMANCE CRITERIA".

For each Major defect listed: delete, "0.40%" and substitute "VL IV".

For each Minor defect listed: delete, "0.65%" and substitute "VL III".

PAGE 13

* 4.4.2.5, Delete "AQL or 100%" and substitute "CONFORMANCE CRITERIA".

For each Major defect listed: delete, "0.40%" and substitute "VL IV".

For each Minor defect listed: delete, "0.65%" and substitute "VL III".

PAGE 14

* 4.4.2.6, Delete "AQL or 100%" and substitute "CONFORMANCE CRITERIA".

For each Major defect listed: delete, "0.40%" and substitute "VL IV".

For each Minor defect listed: delete, "0.65%" and substitute "VL III".

PAGE 15

* 4.4.2.7, Delete "AQL or 100%" and substitute "CONFORMANCE CRITERIA".

For each Major defect listed: delete, "0.40%" and substitute "VL IV".

For each Minor defect listed: delete, "0.65%" and substitute "VL III".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

PAGE 16

4.4.2.8, Add new minor defect as follows:

"201 firing table/graphical firing scale missing ... 0.65% ... 5.1 ... Visual"

* 4.4.2.8, Delete "AQL or 100%" and substitute "CONFORMANCE CRITERIA".

For each Major defect listed: delete, "0.40%" and substitute "VL IV".

For each Minor defect listed: delete, "0.65%" and substitute "VL III".

PAGE 17

* 4.4.2.9, Delete "AQL or 100%" and substitute "CONFORMANCE CRITERIA".

For each Major defect listed: delete, "0.40%" and substitute "VL IV".

For each Minor defect listed: delete, "0.65%" and substitute "VL III".

PAGE 18

* 4.4.2.10, Delete "AQL or 100%" and substitute "CONFORMANCE CRITERIA".

For each Major defect listed: delete, "0.40%" and substitute "VL IV".

For each Minor defect listed: delete, "0.65%" and substitute "VL III".

PAGE 19

4.4.3.2, Line 7: Delete "e. Metal parts separation, critical defect (see 3.7.5)." and substitute "e. Metal parts separation, Special defect (see 3.7.5)".

PAGE 20

4.5.2, Sub-paragraph 5, line 5: Delete, "All fuzes shall be set for impact functioning" and substitute, "All fuzes shall be set to super quick (SQ)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.

4.5.3.1, Line 1: Delete "6 ¾ inches" and substitute "4 ¼ inches."

The margins of this amendment are marked with an asterisk, or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-0609)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:11Z
Check the source to verify that this is the current version before use.