MILITARY SPECIFICATION

TRUCK, FORKLIFT, ELECTRIC, FRONT/SIDE LOADING

6000/6000 POUND CAPACITY

TYPE E

COMMERCIAL

This amendment forms a part of Military Specification MIL-T-53019(ME), dated 4 January 1983, and is approved for use by the USA Belvoir Research and Development Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 4

3.4.1, line 3, delete "110" and substitute "120".

PAGE 15

4.4.12, line 14, delete "110" and substitute "120".

PAGE 16

After 4.4.17, add the following new paragraph:

"4.4.18 Cold weather operation. When a cold weather kit is specified (see 6.2), operation of the forklift shall be demonstrated as follows:

a. Install the kit on the forklift.
b. Service the forklift with applicable lubricants.
c. Place the forklift, with a 6000 pound load on the forks, in a temperature controlled chamber.
d. Cold-soak the forklift for no less than 12 hours at a temperature of -50° F.
e. Energize the forklift and operate the steering, lift, tilt, pivot and sideshift for 10 minutes.
f. Drive the forklift forward and backward within the confines of the chamber continuously for 20 minutes.

Nonconformance to 3.4 shall be cause for rejection."

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 3930-A558

FSC 3930

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:50Z
Check the source to verify that this is the current version before use.