INCH-POUND

MIL-T-60697A
21 September 1992
SUPERSEDING
MIL-T-60697
6 November 1968

MILITARY SPECIFICATION

THRUSTER, CARTRIDGE ACTUATED, M3A3 REMANUFACTURED METAL PARTS ASSEMBLY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for the M3A3 Cartridge Actuated Thruster Remanufactured Metal Parts Assembly (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplements thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-A-2550	Ammunition, General Specification For

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures And Tables For Inspection By Attributes
MIL-STD-109	Quality Assurance Terms And Definitions
MIL-STD-413	Visual Inspection Guide for Elastomeric O-rings

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Standardization Branch (Code 8420), 101 Strauss Avenue, Indian Head, MD 20640-5000, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by sending a letter.

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.
(Unless otherwise indicated, copies of federal and military specifications and standards are available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following Government drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation (see 6.2).

DRAWINGS

Naval Surface Warfare Center, Indian Head (CAGE Codes 19200 and 19203)

10522631	Thruster, Cartridge Actuated, M3A3, Metal Parts Assembly
8796719	Box, Fiberboard (Inner), Packing, Ammunition, For Thruster, Cartridge Actuated, M3A3
8797270	Box, Packing, Ammunition, For Thruster, Cartridge Actuated, M3A3
9217573	Box, Fiberboard (Outer), Alternative, Packing Ammunition, for Thruster, Cartridge Actuated, M3A3

U.S. Air Force

TPO 00-953-5567	Thruster, Cartridge Actuated, M3A3

(Application for copies should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Attn: Data Control Branch (Code 8410), Indian Head, MD 20640-5035.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. All materials used in the manufacture of the thrusters shall conform to the specifications referred to on the respective drawings unless specific approval in writing covering a departure therefrom has been obtained from the cognizant Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal. The remanufactured thruster metal parts assembly shall contain a new shear pin, new O-rings, and a new piston locking spring.

3.2 Hydrostatic pressure. The body and end cap shall withstand a hydrostatic pressure of 8,000 pounds per square inch (psi) for 15 seconds, minimum, without leaking, deformation, or mechanical failure (see 6.3.1).

3.3 Structural strength. The assembled thruster shall withstand a static tensile force of 800 pounds, minimum, for 15 seconds, minimum, between mounting points without unlocking and without mechanical failure (see 6.3.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

3.4 Protective finish. Protective finish shall be in accordance with the applicable specifications and drawings and shall apply to all surfaces of the component regardless of configuration. Remanufactured exterior components (see 6.3.2) shall have the existing protective finish stripped and the specified protective finish reapplied. When there are only small surface areas of exposed base metal on the aluminum exterior components (body assembly and end cap) it may be permissible to treat the surfaces with chemical film Class 1A as specified in MIL-C-5541.

3.5 Residual magnetism. The metal parts assembly shall not deflect the indicator of the compass more than five degrees in either direction using the procedures of 4.5.4.

3.6 Shear pin strength. The shear pin, after application of protective finish, shall shear when a load of 41 ± 5 pounds is applied at the steady rate of 0.125 inch per minute.

3.7 Metal parts assembly. Parts shall be combined to produce an assembly which conforms to the requirements of the metal parts assembly drawing. All threaded joints shall be assembled with sufficient torque to bottom components.

3.7.1 Integrated plant products. When remanufacturing and loading of the assembly is performed in an integrated plant, the metal parts assembly requirement may be waived and the residual magnetism requirement performed on the loaded assembly only.

3.7.2 Threaded component parts. Class 2A or 2B thread gage shall be used on remanufactured component parts inspection versus class 3A or 3B thread gage required on new hardware for thrusters.

3.8 Workmanship. Thrusters shall be free of cracks, splits, or other defects which might prevent proper mating with connecting parts or proper functioning of the device.

3.8.1 Metal defects. All components shall be free from cracks, splits, cold shuts, inclusions, porosity, or any similar defect.

3.8.2 Burr. No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.8.3 Foreign matter. No part or assembly shall contain chips, dirt, grease, rust, corrosion, or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements; however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Quality assurance terms and definitions. Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

4.1.3 Inspections. Inspections shall be in accordance with MIL-A-2550.

4.2 Inspection conditions. Unless otherwise specified (see 6.2), all inspections shall be performed under the following conditions:

a. Temperature: room ambient (68 to 77•F)
b. Altitude: sea level
c. Humidity: 50 percent relative, maximum
d. Atmospheric pressure: 14.7 psi

4.3 Quality conformance inspection.

4.3.1 Lot.

4.3.1.1 Submission of product. Unless otherwise specified by the contracting activity, formation and identification of lots shall be in accordance with MIL-STD-105.

4.3.1.2 Size of lot. For the purpose of identification and shipment, the shipping lots of metal parts assemblies shall consist of 1200 assemblies, maximum, provided the homogeneity requirements of inspection lots have been retained.

4.3.2 Examination. On reprocessed parts, one hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects. Four power (4x) magnification may be used in performing visual examination for such defects as burr and foreign matter. Inspection for rubber O-rings shall be in accordance with MIL-STD-413. When compliance with the applicable requirement is in doubt as a result of visual examination, the characteristic shall be measured or gaged to determine acceptability. All nonconforming material shall be rejected.

4.3.2.1 Examination of reclaimed parts. Examination of reusable parts, which require no reprocessing, shall be limited to inspection of defects that require visual type inspection. One hundred percent examination shall be performed for all such defects. All nonconforming parts shall be reprocessed or rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

4.3.2.2 Rod, Piston, Drawing 8594494, covering a detail of Drawing 10522631.

Characteristics	Defect	Method of Inspection
Critical		
None defined		
Major		
101	Metal defective	Visual
102	Protective finish inadequate or defective	Visual
103	Burr or sharp corner	Visual
104	Foreign matter	Visual
Minor		
None defined		

4.3.2.3 Breech, Assembly, Drawing 8594496, covering a detail of Drawing 10522631.

Critical		
1	Surface finish of cavity improper	Gage
Major		
101	Thread damaged or not full	Visual
102	Metal defective	Visual
103	Protective finish inadequate or defective	Visual
104	Pellet missing, loose, or improperly inserted	Manual/Visual
105	Surface finish of internal thread and mouth chamfer improper	Visual
106	Burr or sharp corner	Visual
107	Foreign matter	Visual
108	Pitch diameter of large external thread, min	Gage
109	Pitch diameter of small internal thread, min	Gage
110	Pitch diameter of inlet port, max	Gage
Minor		
None defined		

4.3.2.4 Sleeve, End, Drawing 8594497, covering a detail of Drawing 10522631.

Critical		
None defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

Major

101	Threads damaged or not full	Visual
102	Metal defective	Visual
103	Protective finish inadequate or defective	Visual
104	Burr or sharp corner	Visual
105	Foreign matter	Visual
106	Pitch diameter of thread, min	Gage

Minor
None defined

4.3.2.5 Key, Drawing 8594498, covering a detail of Drawing 10522631.

Critical
None defined

Major

101	Metal defective	Visual
102	Protective finish inadequate or defective	Visual
103	Burr or sharp corner	Visual
104	Foreign matter	Visual

Minor
None defined

4.3.2.6 Body, Assembly, Drawing 10522633, covering a detail of Drawing 10522631.

Critical
None defined

Major

101	Thickness of wall at internal thread undercut, min	Gage
102	Pellets missing, loose, or improperly inserted	Manual/Visual
103	Thread damaged or not full	Visual
104	Metal defective	Visual
105	Protective finish inadequate or defective	Visual
106	Burr or sharp corner	Visual
107	Foreign matter	Visual
108	Pitch diameter of external thread, min	Gage
109	Pitch diameter of internal thread, max	Gage

Minor
None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

4.3.2.7 Trunnion, Drawing 8594501, covering a detail of Drawing 10522631.

Critical
None defined

Major

101	Diameter of lugs	Gage
102	Metal defective	Visual
103	Protective finish inadequate or defective	Visual
104	Burr or sharp corner	Visual
105	Foreign matter	Visual

Minor
None defined

4.3.2.8 Cap, End, Drawing 10522634, covering a detail of Drawing 10522631.

Critical
None defined

Major

101	Threads damaged or not full	Visual
102	Metal defective	Visual
103	Protective finish inadequate or defective	Visual
104	Burr or sharp corner	Visual
105	Foreign matter	Visual
106	Pitch diameter of large internal thread, max	Gage
107	Pitch diameter of outlet port thread, max	Gage

Minor
None defined

4.3.2.9 Retainer, Cartridge, Drawing 8594503, covering a detail of Drawing 10522631.

Critical
None defined

Major

101	Thread damaged or not full	Visual
102	Metal defective	Visual
103	Protective finish inadequate or defective	Visual
104	Burr or sharp corner	Visual
105	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

Minor
None defined

4.3.2.10 Pin, Firing, Drawing 8594744, covering a detail of Drawing 10522631.

Critical
None defined

Major

101	Metal defective	Visual
102	Protective finish inadequate or defective	Visual
103	Burr or sharp corner	Visual
104	Foreign matter	Visual

Minor
None defined

4.3.2.11 Assembly (Breech), Drawing 10522631, less all components, except Drawings 8594496, 8594744 and MS28775-009.

Critical

1	Firing pin protrusion	Gage

Major

101	Any part missing	Visual
102	Thread damaged or not full	Visual
103	Metal defective	Visual
104	Protective finish inadequate or defective	Visual
105	Foreign matter	Visual

Minor
None defined

4.3.2.12 Assembly, Drawing 10522631.

Critical
None defined

Major

101	Trunnion not free to rotate 360 degrees	Manual
102	End sleeve not free to rotate 360 degrees clockwise	Manual
103	Any part missing, except as otherwise classified	Visual
104	Improper assembly	Visual
105	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

Minor		
201	Protective cap or plug missing	Visual
202	Protective finish inadequate or defective	Visual

4.3.2.13 Spring, Piston Locking, Drawing 8594504, covering a detail of Drawing 10522631.

Critical
None defined

Major		
101	Load at specified heights, incorrect	Gage
102	Solid length, max	Gage
103	Ends incorrect	Visual
104	Protective finish inadequate or defective	Visual
105	Burr or sharp edges	Visual
106	Foreign matter	Visual
Minor		
201	Outside diameter	Gage

4.3.2.14 Pin, Shear, Drawing 8594506, covering a detail of Drawing 10522631.

Critical
None defined

Major		
101	Diameter, max	Gage
102	Total length, min	Gage
103	Metal defective	Visual
104	Protective finish inadequate or defective	Visual
105	Surface finish improper	Visual
106	Burr	Visual
107	Foreign matter	Visual
Minor		
201	Total length, max	Gage
202	Profile of end	Gage

4.3.2.15 Box, Fiberboard (Inner), Packing, Ammunition, Drawing 8796719.

Critical
None defined

Major
None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

Minor		
201	Contents loose	Manual
202	Box damaged	Visual
203	Marking missing, incorrect, or illegible	Visual
204	Cut, damaged, or improperly sealed bag	Visual

4.3.2.16 Box, Packing, Ammunition, Drawing 8797270.

Critical
None defined

Major
None defined

Minor		
201	Contents loose	Visual/Manual
202	Strapping missing, loose, broken, or improperly assembled	Visual/Manual
203	Contents of box exposed	Visual
204	Box damaged	Visual
205	Marking missing, incorrect, or illegible	Visual
206	Number of units incorrect	Visual

4.3.2.17 Box, Fiberboard (Outer), Alternative, Packing, Ammunition, Drawing 9217573.

Critical
None defined

Major
None defined

Minor		
201	Contents loose	Manual/Visual
202	Hardware missing, loose, broken, or improperly engaged	Visual
203	Strapping missing, loosed, broken, or improperly engaged	Visual
204	Contents of box exposed	Visual
205	Box damaged	Visual
206	Marking missing, incorrect, or illegible	Visual

4.4 Inspection testing. The following tests shall be performed in accordance with 4.5.

4.4.1 Hydrostatic pressure. Each body and end cap shall be subjected to the hydrostatic pressure test. Failure of any unit to comply with 3.2 shall be cause for rejection of the unit.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

4.4.2 Structural strength. Each thruster shall be subjected to the structural strength test. Failure of any thruster to comply with the requirements of 3.3 shall be cause for rejection of the thruster.

4.4.3 Protective finish. The number of units for protective finish tests shall be in accordance with the applicable specification. Failure of any unit in the inspection sample to comply with the requirements of the applicable specification shall be cause for rejection of the lot.

4.4.4 Residual magnetism. Each assembly shall be subjected to the test for excessive residual magnetism as specified in 4.5.4. Failure of any unit in the inspection sample to comply with 3.5 shall be cause for rejection of the assembly.

4.4.5 Shear pin strength. Fifty pins from each lot of shear pins shall be tested for shear strength. Failure of any shear pin to comply with 3.6 shall be cause for rejection of the lot.

4.5 Test methods and procedures.

4.5.1 Hydrostatic pressure. Prior to application of protective finish the body and end shall be mounted in the device, using a fixture for properly sealing all openings, and subjected to the internal hydrostatic pressure to determine compliance with 3.2.

4.5.2 Structural strength. The thruster shall be subjected to the structural strength test in accordance with the requirements of 3.3. The test shall be performed in a fixture in conjunction with a tensile testing machine or other device.

4.5.3 Protective finish. Test procedures for protective finish shall be in accordance with the applicable specification referenced on the applicable drawing.

4.5.4 Residual magnetism. The assembly shall be tested for excessive residual magnetism using an approved compass in an area free of local magnetic effects by placing the assembly 5 inches from the end and at the same height as the compass, in a north-south horizontal position (head end at south) with the compass set in an east-west heading. The assembly shall be moved at a speed no greater than 10 feet per minute past the compass for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the assembly for four full passes.

4.5.5 Shear pin strength. After application of protective finish, the pin shall be subjected to the shear pin strength test to determine compliance with 3.6. The test shall be performed in a fixture in conjunction with a tensile testing machine.

4.6 Inspection of packaging. The sampling and inspection of the packaging, packing, and container marking shall be in accordance with the requirements of section 5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packing and marking. Packing and marking shall be Level A or B, as specified by the contracting activity (see 6.2). Level A shall be in accordance with Drawings 8796719 and 8797270. Level B shall be in accordance with Drawings 8796719 and 9217573.

5.2 Air Force packaging. Air Force packaging shall be in accordance with TPO 00-953-5567.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The thruster assembly is used in conjunction with other propellant actuated devices in Aircrew Emergency Escape Systems.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification

b. Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2.1.1 and 2.1.2)

c. The responsible inspection activity (see 4.1)

d. Any special instruction requirements (see 4.2)

e. Level of packing and marking (see 5.1)

6.3 Definitions.

6.3.1 Mechanical failure. Mechanical failure is any deformation or breakage of a part, the occurrence of which is other than a design function.

6.3.2 Exterior components. Remanufactured exterior components are: breech assembly, trunnion, end sleeve, body assembly, and end cap.

6.4 Old engraved or stamped lot and serial numbers. Old serial numbers and lot numbers engraved or stamped on metal parts shall be over-stamped by x's to obliterate those markings before applications of final protective finish.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

6.5 Subject term (keyword) listing.

Ejection systems, aircrew
Emergency escape systems, aircrew
Escape systems, aircrew
Life-saving systems, aircrew

6.6 Changes from previous issue. Marginal notations are not used to identify changes with respect to the previous issue because of the extensiveness of the changes.

Custodian:

Preparing activity
Navy - OS

Navy - OS

Air Force - 99

(Project 1377-0E04)

Review activity:
Air Force - 70

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.