MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (ALUMINUM OXIDE) (POLARIZED), (STACKED FOIL), NON-ESTABLISHED RELIABILITY, AND ESTABLISHED RELIABILITY STYLES CU81 (INSULATED) AND CUR81 (INSULATED)

This amendment forms a part of Military Specification Sheet MIL-C-39018/5A, dated 23 March 1978, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

FIGURE 1: Delete "POSITIVE TERMINAL IDENTIFIED BY MOLDED PLUS (+) SIGN ON COVER AND POSITIVE INSERT DYED RED" and substitute "POSITIVE TERMINAL IDENTIFIED BY MOLDED PLUS (+) SIGN ON COVER".

Custodians:
Army - ER
Navy - EC
Air Force - 11

Review activities:
Army - ER, AV
Navy - SH
Air Force - 17, 85, 99
DLA - ES

User activities:
Navy - CG, MC, AS, OS
Air Force - 19

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5910-1453)

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:04Z
Check the source to verify that this is the current version before use.