INCH-POUND
MIL-PRF-39018C
SUPPLEMENT 1B
14 February 2001

PERFORMANCE SPECIFICATION

CAPACITORS, FIXED, ELECTROLYTIC (ALUMINUM OXIDE), ESTABLISHED RELIABILITY, AND NONESTABLISHED RELIABILITY GENERAL SPECIFICATION FOR

This supplement forms a part of MIL-PRF-39018C, dated 7 January 1991

MIL-PRF-39018/1E	Capacitors, Fixed, Electrolytic (Aluminum Oxide), (Polarized), Non-Established Reliability and Established Reliability, Styles CU12 (Uninsulated), CU13 (Insulated), and CUR13 (Insulated).
MIL-PRF-39018/2C	Capacitors, Fixed, Electrolytic (Aluminum Oxide), (Nonpolarized), Styles CU14 (Uninsulated) and CU15 (Insulated).
MIL-PRF-39018/3D	Capacitors, Fixed, Electrolytic (Aluminum Oxide), (Polarized), Non-Established Reliability and Established Reliability Styles CU16 (Uninsulated) CU17 (Insulated) and CUR17 (Insulated).
MIL-PRF-39018/4B	Capacitors, Fixed, Electrolytic (Aluminum Oxide), (Polarized), Non-Established Reliability and Established Reliability Styles CU71 (Insulated) and CUR71 (Insulated).
MIL-PRF-39018/6A	Capacitors, Fixed, Electrolytic (Aluminum Oxide), (Polarized), Established Reliability Style CUR91 (Insulated).
MIL-PRF-39018/7	Capacitors, Fixed, Electrolytic (Aluminum Oxide), (Polarized), (Four-Terminal), Established Reliability Style CUR19 (Insulated).

Preparing activity:
DLA - CC

(Project 5910-2123)

AMSC N/A FSC 5910
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:01Z
Check the source to verify that this is the current version before use.