MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (ALUMINUM OXIDE) (POLARIZED), NON-ESTABLISHED RELIABILITY AND ESTABLISHED RELIABILITY, STYLES CU16 (UNINSULATED), CU17 (INSULATED), AND CUR17 (INSULATED)

This amendment forms a part of Military Specification Sheet MIL-C-39018/3D, dated 23 March 1978, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Stability at reduced and high temperatures REQUIREMENT, Step 2: Delete "50 to 350 Vdc inclusive: ±20 percent" and substitute:

"50 to 100 Vdc inclusive: ±20 percent.
150 to 350 Vdc inclusive: ±30 percent."

Custodians:
Army - ER
Navy - EC
Air Force - 11

Review activities:
Army -
Navy - SH
Air Force - 17, 99, 85
DLA - ES

User activities:
Navy - CG, MC, AS, OS
Air Force - 19

Preparing activity:
Navy - EC

Agent:
DLA - ES

(Project 5910-1363)

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:03Z
Check the source to verify that this is the current version before use.