MILITARY SPECIFICATION SHEET

CAPACITORS, FIXED, ELECTROLYTIC (ALUMINUM OXIDE)
(POLARIZED), NON-ESTABLISHED RELIABILITY AND ESTABLISHED RELIABILITY,
STYLES CU71 (INSULATED) and CUR71 (INSULATED)

This amendment forms a part of Military Specification Sheet MIL-C-39018/4B, dated 23 March 1978, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 7

*Table I, line 4, under dash number column, delete "1301" and substitute "1304".

Page 8

Stability at reduced and high temperatures REQUIREMENT, Step 2: Delete "30 to 350Vdc inclusive: ±20 percent" and substitute:

"30 to 100Vdc inclusive: ±20 percent.
150 to 350Vdc inclusive: ±30 percent."

Page 9

*After Part Number, add the following:

"APPLICATION NOTE:

Torque. The minimum and maximum torque applied to the steel screw/aluminum insert shall be as follows:

	Min	Max
With a minimum of 3 engaged threads --	12 inch/lbs	18 inch/lbs
With a minimum of 6 engaged threads --	20 inch/lbs	25 inch/lbs"

The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 11

Review activities:
Army - AV
Navy - SH
Air Force - 17, 85, 99
DLA - ES

User activities:
Navy - CG, MC, AS, OS
Air Force - 19

Agent:
DLA-ES

Preparing activity:
Navy - EC

(Project 5910-1392)

☆ U.S. GOVERNMENT PRINTING OFFICE: 1982--505-022/1732 2-1

FSC 5910

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T18:03Z
Check the source to verify that this is the current version before use.