FED. SUP CLASS
5935




NOTES:

1. DIMENSIONS IN INCHES. DIMENSIONING IN ACCORDANCE WITH ANSI Y14.5-1966.
2. DIMENSIONS LOCATING CONTACTS AND INSERTS ARE TRUE POSITION. FOLLOWING TOLERANCES APPLY TO INSERT INSTALLED IN SHELL.
   (A) FOR CRIMP CONTACT CONNECTORS, CENTER OF EACH HOLE IN INSERT SHALL BE LOCATED AT TRUE POSITION WITHIN .014 DIA. ⊕ .014 DIA.
   (B) CENTER OF ENGAGING END OF EACH CONTACT SHALL BE LOCATED AT TRUE POSITION WITHIN .024 DIA. ⊕ .024 DIA.
3. DIMENSIONS AND MARKINGS SHOWN ARE FOR ENGAGING FACE OF PIN INSERT (SOCKET INSERT OPPOSITE).
4. UNLESS OTHERWISE INDICATED, DIMENSIONS ARE SYNMETRICAL ABOUT CENTERLINES.
5. EACH INSERT ARRANGEMENT IS SHOWN IN ITS NORMAL POSITION IN THE SHELL.
6. IN NORMAL POSITION THE INDEXING RADIUS COINCIDES WITH ℄ OF THE MASTER KEY OR KEYWAY OF SHELL.
7. IN ALTERNATE POSITIONS THE PIN INSERT IS ROTATED CLOCKWISE SO THAT ANGLE "A" BETWEEN THE INDEXING RADIUS AND THE ℄ OF THE MASTER KEY OR KEYWAY OF SHELL IS AS REQUIRED.
8. IN ALTERNATE POSITIONS THE SOCKET INSERT IS ROTATED COUNTER-CLOCKWISE SO THAT ANGLE "A" BETWEEN THE INDEXING RADIUS AND THE ℄ OF THE MASTER KEY OR KEYWAY OF SHELL IS AS REQUIRED.

CANCELED AFTER 20 February 78

USE MIL-STD-1669 (B)

(B) Denotes Changes

THIS IS A DESIGN STANDARD. NOT TO BE USED AS A PART NUMBER.

APPROVED 26 MARCH 1969 REVISED (A) 6 AUG 1971 (B) 20 Feb 78

(B) Reviewers : AF 99

Approved by the AFLC /LOIE for use by this activity. All other military activities are required to employ this standard when suitable.

| P.A. AIR FORCE 85 (B) Other Cust | TITLE INSERT ARRANGEMENTS MIL-C-83723 ELECTRIC CONNECTOR SIZE 18 | MILITARY STANDARD MS27730 (USAF) |
|---|---|---|
| PROCUREMENT SPECIFICATION NONE | SUPERSEDES: | SHEET 1 OF 1 |

DD FORM 672-1 (Limited coordination)

5935-F089-4

☆ U.S. GOVERNMENT PRINTING OFFICE: 1978 703-427/153

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:49Z.
Check the source to verify that this is the current version before use.