FED. SUP CLASS
4730



MS PART NO.	TUBE O.D.	A DIA ±.003	B DIA ±.003	C DIA +.000 -.010	D DIA +.002 -.000	E DIA +.002 -.007	F ±.005	G	H ±.015	J DIA +.005 -.000	APPROX WEIGHT LBS/EA
MS27858-04	1/4	.252	.204	.282	.470	.625	.248	1.125	.450	.275	
MS27858-06	3/8	.377	.317	.420	.608	.740	.251	1.187	.490	.405	
MS27858-08	1/2	.502	.428	.536	.724	.865	.255	1.250	.520	.535	
MS27858-12	3/4	.752	.678	.808	.986	1.110	.303	1.375	.630	.787	
MS27858-16	1	1.002	.900	1.090	1.282	1.420	.312	1.500	.640	1.050	.028

1. ALL DIAMETERS SHALL BE CONCENTRIC WITHIN .005 FIR.
2. MATERIAL: ALUMINUM ALLOY, AMS 4117.
3. CLEANING: FINISHED PARTS SHALL BE CLEANED PER MIL-F-27417.
4. SURFACE TEXTURE, IN ACCORDANCE WITH USAS B46.1, UNLESS OTHERWISE SPECIFIED ALL MACHINED SURFACES TO BE 63 MICROINCHES.
5. BREAK EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.
6. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: LINEAR DIMENSIONS, ±.010, ANGULAR DIMENSIONS ± 5°.
7. DO NOT USE UNASSIGNED PART NUMBERS.
8. REFER TO MS27856 FOR ASSEMBLY.
   FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.
   REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID.

CANCELLED AFTER 16 JULY 1980. NO SUPERSEDING STANDARD

APPROVED 14 JULY 1967 REVISED A 16 July 1980

Review activities: 11, 14, 19, 69, 85 & NAS

This standard has been approved by the Department of the AIR FORCE and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

P.A. USAF 12 Other Cust	TITLE FLANGE, PLAIN, ALUMINUM, FLUID CONNECTION FITTING, LOW PRESSURE	MILITARY STANDARD MS27858 (USAF)
PROCUREMENT SPECIFICATION MIL-F-27417	SUPERSEDES:	SHEET 1 OF 1

DD FORM 1 SEP 67 672-1 (Limited coordination) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T16:52Z
Check the source to verify that this is the current version before use.