MILITARY SPECIFICATION

AMPLIFIERS, VARIABLE GAIN

This specification has been approved by the Bureau of Naval Weapons, Department of the Navy.

1. SCOPE

1.1 Scope.- This specification describes the requirements for the procurement of two types of Variable Gain Amplifiers, BUORD LD-L99688 and BUORD LD-5179A7. The Variable Gain Amplifiers BUORD LD-499688 and BUORD LD-517947 are identical except for sealing compound and are designed to accept 400-cycle input signals and to amplify them prior to insertion into a servo amplifier. The amplifier consists of two independent, three-stage transistorized channels. The gain is variable with the amount of feedback determined by an external resistor network. The amplifier is designed so that the gain varies to maintain the output within certain limits.

1.2 Classification.- The amplifiers shall be of the following types:

Type 1	BUORD LD-499688	Variable Gain Amplifier Assy
Type 11	BUORD LD-517947,	Variable Gain Amplifier Assembly (Sealed)

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, drawings, and publications, or such portion thereof as may be designated herein, of the issue in effect on the date of invitation for bids, form a part of this specification.

SPECIFICATIONS

FEDERAL

PPP-B-601 Boxes, Wood, Cleated-Plywood

FSC 1290

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:55Z
Check the source to verify that this is the current version before use.

PPP-B-621	Boxes, Wood, Nailed and Lock Corner
PPP-B-636	Boxes, Fiberboard

MILITARY

MIL-P-116	Preservation, Methods of
MIL-S-901	Shockproof Equipment Class HI (High Impact) Shipboard Application, Tests for
MIL-E-5272	Environmental. Testing, Aeronautical and Associated Equipment, General Specification for
MIL-E-17555	Electronic and Electrical Equipment and Associated Repair Parts, Preparation for Delivery of
MIL-F-18870	Fire Control, optical and Associated Equipment Intended for Shipboard Use, the General Specification for Design and Procurement of

STANDARDS

MILITARY

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-167	Mechanical Vibrations of Shipboard Equipment

DRAWINGS

NAVY DEPARTMENT

BUORD LD-499688	Variable Gain Amplifier Assy
BUORD LD-517947	Variable Gain Amplifier Assembly (Sealed)
BUORD SA-2530405	Amplifier Test Fixture

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:55Z
Check the source to verify that this is the current version before use.

PUBLICATIONS

BUREAU OF NAVAL WEAPONS

WR-11	Design and Test of Packaging, Packing Shipping and Handling Equipment for Weapon System Components
NAVORD OS 6341	**Miscellaneous General Ordnance Design Requirements**
NAVORD OD 12352	Description and Operating Instructions for Amplifier Test Fixture Shop Accessory SA 2530405

(Copies of specifications, standards, drawings, **and publications requested by the contractors in connection with specific procurement functions should be Obtained from the procuring actitity or as directed by the contracting officer.)**

2.2 Other publications. - The following documents form a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

NATIONAL BUREAU OF STANDARDS PUBLICATIONS

Handbook H28	Screw-thread Standards for Federal **Services**

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D. C.)

CONSOLIDATED CLASSIFICATON COMMITTEE PUBLICATION

Consolidated Freight Classification Rules

(Application for copies should be addressed to the Consolidated Classification Committee, 202 Chicago Union Station, Chicago **6, Ill.)**

AMERICAN TRUCKING ASSOCIATION, INC. PUBLICATION

Motor Freight Classification Rules

(Application for copies should be addressed to the Issuing Officer American Trucking Association, Inc., 1424 **16th** Street, N.W., Washington 6, D. c.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:55Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General requirements.

3.1.1 Pre-production samples .- Unless otherwise specified in the contract or order, pre-production samples of the Variable Gain Amplifier shall be manufactured by the methods and procedures proposed for the production lot. These samples shall be tested as specified in section 4 herein and are for the purpose of determining that the production item meets the requirements of this specification, and the designs See 4.1.2.

3.1.2 Materials.- Unless otherwise specified in the contract, requisition, or order, all materials and purchased parts entering into the final assembly of the Variable Gain Amplifier shall conform to the detailed requirements given on the drawings and specifications listed in BUORD LD-499688 or BUORD LD-517947 as applicable, and in Specification MIL-F-18870.

3.1.3 Finishes, coatings, construction,and dimensions.- Finishes, coatings, construction,and.dimensions for the Variable Gain Amplifier shall be in accordance with the applicable drawings, specifications, and publications listed in BUORD LD-4996880r BUORD LD-517947.

3.1.4 Moistures fungus, and corrosion.- The Variable Gain Amplifier shall be rendered moisture, fungus, and corrosion resistant in accordance with detail requirements specified on drawings and specifications in BUORD LD -99688 or BUORD LD-517947.

3.1.5 Marking.- Marking of assemblies, sub-assemblies, and parts shall be in accordance with the applicable drawings listed in BUORD LD-499688 or BUORD LD -517947.

3.1.6 Interchangeability.- Component parts of the assembled units (unless otherwise specified on the applicable drawings) fabricated in accordance with their applicable drawings shall be interchangeable and shall assemble with mating components of the units without selection or fitting. If, during assembly of the fabricated parts of a unit, selection or fitting Is required, then changes in dimension are necessary, and revision and correction of the applicable drawings is required. See 3.1.10.

3.1.7 Gages.- The contractor shall provide himself with whatever gages are necessary and adequate to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings. If so stipulated in the contract, order, or requisition, the Government will furnish drawings of pertinent Navy

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:55Z
Check the source to verify that this is the current version before use.

Final Inspection Gages for guidance in the design of the contractor's inspection gages. However, such procedure shall not relieve the contractor of his responsibility In the design and manufacture of such gages as may be required for the satisfactory fulfillment of the contract requirements, but is intended to facilitate acceptance of all components and assemblies by Navy Final Inspection Gages.

3.1.8 Threads. - Unless otherwise specified, all. threads shall be in accordance with the National Bureau of Standards Handbook H28. The class or fit for threads shall be as specified on the applicable drawings, and the NOT-GO gaging practice shall be as set forth in the aforementioned Handbook H28.

3.1.9 Requests for deviation. - Each request that a deviation be authorized shall have been submitted to the procuring activity, and the deviation shall have been authorized by the Bureau Of Naval Weapons or by a Naval activity delegated such authority, prior to the production of the affected item, or prior to the performance of a particular operation on the item. The deviation shall apply only to this specific item or operation. The request shall define the suggested deviation in sufficient detail to permit the procuring activity to evaluate its effect on performance and reliability and the reasons for the suggested deviation shall be stated. Each request that a deviation be authorized, and the authorization, shall state specifically the extent of the departure, the identifying number of the item, the contractor (or bidder) and the contract number. A deviation is essentially temporary in character, and usually represents a departure limited to a specific period, to a specific number of items, or to the contract to which it applies. It may require an equitable reduction in contract price if a decrease in the cost of performance results therefrom.

3.1.10 Conflicting requirements. - Conflicting requirements arising between this specification or any specification, publication, or drawing listed herein shall be referred in writing to the procuring agency or appointed agent for interpretation, clarification, and resolution (or correction).

3.2 Definitions. - Definitions applicable to the environmental requirements of this specification are as follows:

3.2.1 Tropical envionment. - Tropical environment is defined as conditions of high humidity, high temperature, and spore exposure, which present an opportunity for fungi growth.

3.3 performance requirements and product characteristics. - The Variable Gain Amplifier shall meet the following performance requirements and product characters tics:

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:55Z
Check the source to verify that this is the current version before use.

3.3.1 Gain, low, channel 1. - When tested with the test equipment specified in 4.3, the low gain characteristic of-channel 1 of the amplifier shall be such that the vacuum tube voltmeter reading is between 0.35 and 0.45 volt for an input Signal of 0.1000 PlUS or minus 0.0025 volt.

3.3.2 Gain, high, channel 1. - When tested with the test equipment specified in 4.3, the high gain characteristic of channel 1 of the amplifier shall. be such that the vacuum tube voltmeter reading is between 4.0and8.0 volts for an input signal of o.1ooo plus or minus 0 .0025 volt.

3.3.3 Gain,low, channel 2. - When tested with the test equipment specified in 4.3, the low gain characteristic of channel 2 of the amplifier shall be such that the vacuum tube voltmeter reading is between 0.35 and 0.45 volt for an input signal of 0.1000 plus or minus 0.0025 volt.

3.3.4 Gain, high, channel 2. -When tested with the test equipment specified in 4.3, the high gain characteristic of channel 2 of the amplifier shall be such that the vacuum tube voltmeter reading is between 4.0 and 8.0 volts for an input signal of 0.1000 plUS or minus 0.0025 volt.

3.3.5 Phase, Shift, *channel* 1, low gain.- When tested with the test equipment specified in 4.3, the phase shift characteristic of channel 1, low gain, shall be such that the vacuum tube voltmeter reading is less than 140 millivolts for an input signal of 140 plus or minus 1 millivolt. (The conversion factor for millivolts per degree is 10 millivolts equal 1 degree.)

3.3.6 Phase shift, channel 1, high gain. -When tested with the test equipment specified in 4.3, the phase shift characteristic of channel 1, high gain, shall be such that the vacuum tube voltmeter reading is less than 140 millivolts for an input signal of 140plus or minus 1 millivolt. (The conversion factor for millivolts per degree is 10 millivolts equal 1 degree.)

3.3.7 Phase shift, Channel 2, low gains - When tested with the test equipment specified in 4.3, the phase shift characteristic of channel 2, low gain, shall be such that the vacuum tube voltmeter reading is less than 140 millivolts for an input signal. of 140 plus or minus 1 millivolt. (The conversion factor for millivolts per degree is 10 millivolts equal 1 degree.)

3.3.8 *Phase* shift, channel 2, high gain. - When tested with the test equipment specified in 4.3, the phase shift characteristic of channel 2, high gain, shall be such that the vacuum tube voltmeter reading is less than 140 millivolts for an input signal of 140 plus or minus 1 millivolt. (The conversion factor for millivolts per degree is 10millivolts equal 1 degree.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:55Z
Check the source to verify that this is the current version before use.

3.3.9 **Noise,** channel 1. -When tested with the test equipment specified in **4.3, the noise characteristic of channel 1 shall be such that the vacuum tube voltmeter reading is less than 0.050 volt when the input signal is shorted.**

3.3.10 Noise, **channel 2. - When** tested with the test equipment specified in **4.3, "the noise characteristic of' channel 2 shall be such that the vacuum tube voltmeter reading is less than 0.05 volt when the input signal is shorted.**

3.4 Envionmental requirements. - The Variable Gain Amplifier shall meet the other applicable requirements of this specification during or after tests defined or specified in 4.5.

3.4.1 Vibration, operating condition. - The Variable Gain Amplifier shall withstand the Type I vibration requirements specified in Standard **MIL-STD-167, shall function during and after vibration tests, and thereafter shall show no damage and shall meet all the performance requirements and product characteristics of this specification.**

3.4.2 Vibration-transportation. - The Variable Gain Amplifier subjected to the tests specified in 4.5.2 shall show no damage and shall meet all the requirements of section **3.**

3.4.3 Shock, non-operating condition. - The Variable Gain Amplifier shall withstand the Type **A** shock requirements specified in Specification **MIL-S-901, and thereafter shall show no damage and shall meet all the performance requirements and product characteristics of this specification.**

3.4.4 Shock transportation, storage and handling. - The Variable Gain Amplifier after being subjected to the tests specified in 4.5.4 shall show no damage and shall meet all the requirements of section **3.**

3.4.5 **Temperature, operating condition. - The variable Gain Amplifier shall withstand operational ambient temperature of between zero degrees Fahrenheit (minus 18 degrees centigrade) and 185 degrees** Fahrenheit **(85 degrees centigrade) in accordance with Specification MIL-F-18870, shall function during and after temperature tests, and thereafter shall show no damage or corrosion and shall meet all the performance requirements and product characteristics of this specification.**

3.4.6 Temperature, non-operating condition. - The Variable Gain Amplifier shall withstand storage temperatures of between minus 40 degrees Fahrenheit (minus 40 degrees centigrade) and 160 degrees Fahrenheit 71 degrees centigrade) in accordance with Condition II of OS 6341, and thereafter shall show no corrosion or damage and shall meet all the performance requirements and product characteristics of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:55Z
Check the source to verify that this is the current version before use.

3.4.7 Humidity. - The Variable Gain Amplifier shall withstand operational ambient humidities in accordance with Specification MIL-F-18870, and thereafter shall show no corrosion or damage and shall meet all the performance requirements and product characteristics of this specification.

3.4.8 Tropical envionment. - The Variable Gain Amplifier shall withstand the tropical environmental conditions specified in Specification MIL-E-5272 under "Fungus Resistance Tests", and thereafter shall show no fungus growth, corrosion or other damage, and shall meet all the performance requirements and product characteristics of this specification.

3.5 Clean-up. - Prior to and after final assembly, all parts, components and the assembly shall be thoroughly cleaned of loose, spattered, or excess solder, metal chips, and other foreign matter. Burrs and sharp edges, as well as rosin flash, shall be removed.

3.6 Workmanship. - The equipment, including all parts and accessories, shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention shall be paid to neatness and thoroughness of soldering, marking of parts and assemblies, riveting, machine screw assemblage, and freedom of parts from burrs and sharp edges.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. - Unless otherwise **specified in** the contract or purchase order, the" supplier is responsible **for the performance** of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 sampling. - Unless otherwise specified by the contract or purchase order, and when applicable, the sampling plans and procedures used by the Government inspector in the determination of the acceptability of products submitted by a supplier for Government inspection shall be in accordance with 4.1.2 and 4.1.3.

4.1.2 Pre-production sample. - Unless otherwise specified in the contract or order (see 6.2), three **Variable Gain Amplifiers manufactured in accordance with 3.1.1 shall be furnished to the activity designated by the procuring agency(see 6.2) for testing in accordance with 4.5. Further production of the item, prior to completion of the tests and approval of the sample by the procuring agency, shall be at the contractors risk.**

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:55Z
Check the source to verify that this is the current version before use.

4.1.3 Periodic production sample. - Periodic production samples shall be randomly selected as follows from production units which have satisfactorily passed the tests of 4.4, and subjected to the tests of 4.6 by the activity designated in the contract or order (see 6.2):

Step 1. Upon initiation of production select one (1) unit from each **group of ten (10) units for submission to an activity designated by the procuring agency.**

Step 2. Upon satisfactory compliance of each unit from three (3) **consecutive** groups, select one (1) unit from each group of twenty-five (25) units.

Step 3. Upon satisfactory compliance of each unit from three (3) consecutive groups, select one (1) unit from each group of fifty (50) units. Continue this procedure until a defective unit is found.

Step 4. When a defective unit is found in any group, the group represented by the sample shall be rejected. Shift to Step 1 and proceed as indicated.

4.2 Clssification of tests. - The inspection and testing of the Variable Gain Amplifier shall be classified as follows:

4.2.1 Acceptance tests. - These tests shall be accomplished on each Variable Gain Amplifier submitted for acceptance under contract. Acceptance tests shall be either performed by the manufacturer and witnessed by the Government inspector, or they may be conducted by the Government inspector. These tests are detailed in 4.4.

4.2.2 Pre-production and periodic production tests. - Pre-production and periodic production tests shall be accomplished on samples selected as specified in 4.1.2 and 4.1.3 which are representative of the production of the Variable Gain Amplifier after the award of the contract, to determine that the production meets the requirements of this specification. These tests are detailed in 4.5. Acceptance shall be based on no **defects in the sample. Failure of the sample to comply with these requirements will result in the rejection of the lot or the cessation of production, as determined by the procuring activity.**

4.2.3 Tests after delivery. - Unless otherwise specified in the contract, the Government reserves the right to conduct any or all the tests specified herein, as deemed necessary, after installation of the Variable Gain Amplifier. Any defects discovered during or after these tests due to the contractor's failure to comply with drawings or specifications for this equipment shall be correctedby the contractor at no expense to **the Government,** provided the contractor is notified of such defects within the guarantee period of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:55Z
Check the source to verify that this is the current version before use.

4.3 Test equipment. - The following item of test equipment is required to perform the acceptance tests set forth in this specification.

4.3.1 Shop accessory SA-2530405. Amplifier Test Fixture.

4.4 Acceptance tests.

4.4.1 The contractor shall conduct acceptance tests as specified in 4.3.1 to assure that the Variable Gain Amplifier is in compliance with the requirements of 3.1, 3.3, 3.5, and 3.6. Manufacturer's certification may be used in lieu of material tests, provided that such certificates contain actual test results or other verifiable inspection data.

4.4.2 Test conditions. - Unless otherwise specified, the Variable Gain Amplifier shall be subjected to acceptance tests under the following conditions:

4.4.2.1 Temperature: Room ambient 65 to 95 degrees Fahrenheit (18 to 35 degrees centigrade).

4.4.2.2 Altitude: Normal ground atmospheric pressure.

4.4.2.3 Vibration: None.

4.4.2.4 Humidity: Room ambient to 95 percent relative maximum.

4.4.3 Test and inspection equipment and facilities. - The manufacturer shall furnish and maintain all necessary test equipment, facilities, and personnel for performing all acceptance tests. The test equipment shall be adequate in quantity and, unless definite requirements are specified, shall be of sufficient accuracy and quality to assure the adequacy and accuracy of test results relative to required tests.

4.4.4 Test procedure. - The Variable Gain Amplifier shall be tested in accordance with the detailed test procedure given in OD 12352 to determine compliance with the requirements of 3.1, 3.3, 3.5, and 3.6.

4.4.4.1 Preparation for shipment. - The preservation, packaging, and packing of the units shall be examined to determine compliance with the requirements of section 5.

4.5 Pre-production and periodic production sample tests. - Variable Gain Amplifiers subjected to these tests shall be considered not suitable for service use, and shall not be issued to the fleet, nor used in equipment to be issued to the fleet.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:55Z
Check the source to verify that this is the current version before use.

4.5.1 Vibration, operating condition. - The Variable Gain Amplifier, rigidly mounted in a suitable vibration fixture, shall be subjected to vibration tests so as to meet the requirements specified in 3.4.1, and shall meet all the performance requirements and product characteristics of this specification during and after the vibration tests.

4.5.2 Vibration-transportation. - The Variable Gain Amplifier packaged and packed as specified in section 5, shall be vibration tested as specified in Weapons Requirement WR-11.

4.5.3 Shock, non-operating condition. - The Variable Gain Amplifier, rigidly mounted in a suitable shock fixture, shall be subjected to shock tests so as to meet the requirements specified in 3.4.3, and thereafter shall meet all the performance requirements and product characteristics of this specification.

4.5.4 Shock-transportation, storage and handling. - The Variable Gain Amplifier packaged and packed as specified in section 5, shall be subjected to the appropriate shock isolation tests specified in Weapons Requirement WR-11.

4.5.5 Temperature, operating condition. - The Vaiable Gain Amplifier shall be subjected to temperature tests so as to meet the requirements specified in 3.4.5, and thereafter shall meet all the performance requirements and product characteristics of this specification.

4.5.6 Temperature, non-operating condition. - The Variable Gain Amplifier shall be subjected to temperature tests so as to meet the requirements specified in 3.4.6, and thereafter shall meet all the performance requirements specified in 3.4.6, and thereafter shall meet all the performance requirements and product characterstics of this specification.

4.5.7 Humidity. - The Variable Gain Amplifier shall be subjected to humidity tests so as to meet the requirements specified in 3.4.7, and thereafter shall meet all the performance requirements and product characteristics of this specification.

4.5.8 Tropical environment. - The Variable Gain Amplifier shall be exposed to fungus tests so as to meet the requirements specified in 3.4.8, and thereafter shall meet all the performance requirements and product characteristics of this specification.

4.6 Failure of the Variable Gain Amplifier to meet any **of the requirements and tests of this specification shall be considered cause for** rejection

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:55Z
Check the source to verify that this is the current version before use.

4.7 Functional tests. - At the conclusion of the tests specified in 4.5.2 and 4.5.4 above, functional and other tests, as applicable, shall be conducted on the Variable Gain Amplifier to determine freedom from operational malfunction and compliance with all requirements of section 3.

4.8 Waiver of tests. - Tests specified in 4.5.2 and 4.5.4 above maybe waived by the procuring agency for level C packs only, provided the contractor guarantees safe delivery to the using activity.

5. PREPARATION For DELIVERY

5.1 Preservation and packaging.

5.1.1 Level A. - ln addition to the following Level A packaging shall be in accordance with specification MIL-E-17555.

5.1.1.1 Cleaning, drying and preservative application. - Not applicable.

5.1.1.2 Unit packaging. - Unit packaging of the Variable **Gain Amplifier shall be in accordance with Method IIe of Specification MIL-P-116. The unit package shall contain one Variable Gain Amplifier.**

5.1.1.3 Intermediate package. - Not applicable.

5.1.1.4 Cushioning. - The unit package, and pack, shall incorporate sufficient cushioning material, bracing, or other adequate shock absorbing devices to ensure that the Variable Gain Amplifier will meet all the requirements of section 3 after being tested in accordance with 4.5.2 and 4.5.4.

At the time of packaging or packing, the moisture content of the cushioning material. shall be no more than 5 percent.

5.1.2 Level B. - Not applicable.

501.3 Level C.

5.1.3.1 Cleaning, drying and preservative application. - Not applicable.

5.1.3.2 **Unit packaging. - Unit packaging of the Variable Gain Amplifier shall be in accordance with Method III of Specification MIL-P-116. The unit package shall contain one Variable Gain Amplifier.**

5.1.3.3 Intermediate package. - Not applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:55Z
Check the source to verify that this is the current version before use.

5.2 Packing.

5.2.1 Level A. - In addition to the following Level A packing shall be in accordance with Specifications MIL-E-17555.

5.2.1.1 Exterior containers. - Variable Gain Amplifier packaged as described in 5.1.1.2 shall be packed in a wood box *in* accordance with Specification PPP-B-601, overseas type, or PPP-B-621, class 2 (weight not to exceed 150 lbs) or in a fiberboard box in accordance with Specification PPP-B-636, class 2 (weight not to exceed 70 lbs).

5.2.2 Level B. - Not applicable.

5.2.3 Level C. - The Variable Gain Amplifier packaged in accordance with 5.1.3.2 shall be packed to afford protection against damage during shipment from the supply to the first receiving activity for immediate use. Containers shall comply with Consolidated Freight Classification Rules or other common carrier regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 special **markings.** - None, unless otherwise specified.

5.3.2 Normal markings **.** - in addition to the markings required by contract or order, unit packages, and shipping containers shall be marked in accordance with the requirements of MIL-STD-129, including serial numhers.

6. NOTES

6.1 Intended *use.* - The Variable Gain Amplifier is intended for use in the Angle Solvers Mark 18 Mod 2 and Mod 3, the Fire Control System Mark 112 Mod 1, the Sonar Receiving Sets AN/BQG-l, -2, -3, -4, or other suitable application.

6.2 Ordering data. - Procurement documents should specify the following:

a. Title, number and date of this specification.
b. Quantity required including samples required for pre-production and periodic tests (see 4.5).
c. sampling if different from 4.1.1.
. If pre-production or periodic samples are not required **(see 3.l.1.**
e. Activity to conduct pre-production and periodic tests (see 4.1.2 and 4.1.3).

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T11:55Z
Check the source to verify that this is the current version before use.

f. Materials, if different from 3.1.2.
g. Level of "Preparation for delivery" (see section 5).
h. Additional marking if required (see 5.3.1).

6.2.1 *The* attention of the contracting officer is invited to the Quality Assurance Provisions and options in Specification MIL-P-116 and to para 4.8 of this specification.

6.3 Criteria for use of proper level of preservation, packaging, and packing shall be as follows:

For Level A. - This level shall be used for those items which are to be shipped to indeterminate destinations or stored under indeterminate conditions for redistribution anywhere.

For Level B. - This level shall be used only when it is definitely known that the item will be held in covered storage in overseas locations for 6 **months or less or in domestic locations for an indefinite period.**

For Level C. - This level shall be used only when it is definitely known that the packaged item is to be shipped to domestic installations for immediate use at the first receiving activity.

6.4 Guarantee. - The contract or order shall include a requirement for a guarantee stating that any Variable Gain Amplifier which fails to meet the requirements of this specification within one year after delivery because of a defect in material or workmanship or because of the vendor's failure to comply with the requirements of the applicable drawings and specifications shall be replaced by the vendor at no cost to the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T11:55Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID

U.S.MAIL

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Commander
Naval Sea Systems Command
Engineering Support Division
ATTN: SEA 605
Department of the Navy
Washington, DC 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-19T11:55Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

MIL-A-22335(Wep) AMPLIFIERS, VARIABLE GAIN

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

Source: https://assist.dla.mil -- Downloaded: 202610-19T11:55Z
Check the source to verify that this is the current version before use.