MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

DRIVER, LAMP/RELAY, DIGITAL, KEY CODE ABF

This amendment forms a part of Military Specification MIL-M-28787/152A(EC), dated 15 June 1982, and is approved for use by the Naval Electronic Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

4.4.2, delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through N shall be performed in any order with the following exceptions. Test conditions A, B, and C are stress tests and will be performed only at 25°C ±5°C. If test conditions A, B, or C are part of a sequence of tests, the order of testing shall be as follows: A, B, C where applicable, followed by the remaining tests in the sequence."

PAGE 4

TABLE I, Test conditions A1-A8, Parameter column: Delete "static output current (50 V)" and substitute "Static input current (50 V)".

TABLE I, Test conditions B1-B4, Parameter column: Delete "Collector to emitter current (50 V)" and substitute "Collector to emitter leakage current (50 V)".

PAGE 26

TABLE VIII: Delete and substitute new table VIII as printed on page 2 of this amendment.

FSC 5963
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:18Z
Check the source to verify that this is the current version before use.

TABLE VIII. Input threshold voltages (low-level and high-level) test.

Test condition	ABF input	Logic level	V_{CC} voltage (±1%) 1/	Acceptance requirements 25°C ±5°C ambient temperature 1/		0°C to 60°C 1/ Operating temperature	
				Initial	End-of-life	Initial	End-of-life
F1-F12	A and B	Low	4.5 V	0.8	1.1	1.0	1.3
F13-F16	E	Low	4.5 V	1.5	1.7	1.6	1.9
F17-F24	A and B	Low	22.5 V	12.0	13.3	13.3	14.5
F25-F28	E	Low	22.5 V	12.5	13.8	13.8	15.0
G1-G4	ALL	High	5.5 V	3.5	3.7	3.9	4.0
G5-G8	ALL	High	27.5 V	25.5	25.7	25.9	26.0
		High	V_{CC}	V_{CC} -2.0 V	V_{CC} -1.8 V	V_{CC} -1.6V	V_{CC} -1.5 V

1/ When performing tables VI, VII, and figures 9 and 10 tests, adjust item PO1-1 voltage (V_{CC}) as specified in the V_{CC} column and adjust item PO1-2 voltage (V_{IN}) as specified in this table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:18Z
Check the source to verify that this is the current version before use.

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5963-N669)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:18Z
Check the source to verify that this is the current version before use.