INCH-POUND

MIL-M-28787/166B(SH)
AMENDMENT 2
24 August 1990
SUPERSEDING
AMENDMENT 1
24 September 1985

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

COUNTER, UP/DOWN, BINARY, DIGITAL, KEY CODE BBJ

This amendment forms a part of Military Specification MIL-M-28787/166B (SH), dated 6 December 1982, and is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

* 4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through FF shall be performed in any order with the following exceptions. Test conditions A, B, C, D, and G are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, D, or G are part of a sequence of tests, the order of testing shall be as follows: C, A, B, D, and G where applicable, followed by the remaining tests in the sequence."

* 4.5.1: Delete and substitute the following:

"4.5.1 Operating temperature tests. The operating temperature tests shall be conducted in accordance with MIL-M-28787. Before starting these tests, test conditions A through FF in table I shall be performed in the order specified in 4.4.2 using the initial limits at 25°C ambient. When electrical testing is called for at the end of each temperature stabilization period, test conditions E, F, H through N6, P1-P6, Q1-Q12, R1-R12, S1-S12, T1-T12, U1-U18, V1-V18, W1-W12, X1-X12, Y1-Y12, and Z through BB shall be performed in the order specified in 4.4.2 using the initial limits for the applicable operating temperature. At all other times during the operating temperature tests, the module shall be operated in the test circuit shown on figure 2."

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:23Z
Check the source to verify that this is the current version before use.

* 4.5.3: Delete and substitute the following:

"4.5.3 Life test. The life test shall be conducted in accordance with MIL-M-28787. The module shall be operated as shown on figure 2. Following the life test and while still at the maximum class temperature, electrical tests E, F, H through N6, P1-P6, Q1-Q12, R1-R12, S1-S12, T1-T12, U1-U18, V1-V8, W1-W12, X1-X12, Y1-Y12, and Z through BB shall be performed in the order specified in 4.4.2 using the operating temperature end-of-life requirements in table I. Following the return of the module to 25 ± 5°C, electrical tests E, F, H through N6, P1-P6, Q1-Q12, R1-R12, S1-S12, T1-T12, U1-U18, V1-V18, W1-W12, X1-X12, Y1-Y12, and Z through BB shall be performed in the order specified in 4.4.2 using the 25 ± 5°C ambient end-of-life requirements in table I."

PAGE 5

* TABLE I, Test conditions G1-G18, Test type column: Delete "X" and substitute "S".

PAGE 7

* TABLE I, Test conditions U1-U18, Max column: Delete "60" (four places) and substitute "80" (four places).

TABLE I, Test conditions U19-U36, Max columns: Delete "80" (four places) and substitute "95" (four places).

TABLE I, Test conditions V1-V18, Max columns: Delete "25" (four places) and substitute "35" (four places).

TABLE I, Test conditions V19-V36, Max columns: Delete "35" (four places) and substitute "65" (four places).

PAGE 8

TABLE I, Test conditions FF1-FF18, Max columns: Delete "12" (four places) and substitute "15" (four places).

PAGE 60

* TABLE XIII, Test conditions U1-U12, Max column: Delete "60" and substitute "80".

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:23Z
Check the source to verify that this is the current version before use.

PAGE 61

* TABLE XIII, Test conditions U13–U18, Max column: Delete "60" and substitute "80".

TABLE XIII, Test conditions U19–U23, Max column: Delete "80" and substitute "95".

PAGE 62

TABLE XIII, Test conditions U24–U34, Max column: Delete "80" and substitute "95".

PAGE 63

TABLE XIII, Test conditions U35 and U36, Max column: Delete "80" (two places) and substitute "95" (two places).

TABLE XIII, Test conditions V1–V10, Max column: Delete "25" and substitute "35".

PAGE 64

TABLE XIII, Test conditions V11–V18, Max column: Delete "25" and substitute "35".

TABLE XIII, Test conditions V19 and V20, Max column. Delete "35" (two places) and substitute "65" (two places).

PAGE 65

TABLE XIII, Test conditions V21–V32, Max column: Delete "35" and substitute "65".

PAGE 66

TABLE XIII, Test conditions V33–V36, Max column: Delete "35" and substitute "65".

PAGE 99

TABLE XX, Test conditions FF1–FF18, Max column: Delete "12" and substitute "15".

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:23Z
Check the source to verify that this is the current version before use.

MIL-M-28787/166B(SH)
AMENDMENT 2

NOTE: The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment

Preparing activity:
Navy – SH

(Project 5963–N755)

Agent: NW

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T16:23Z
Check the source to verify that this is the current version before use.