INCH-POUND

MIL-M-28787/170A
AMENDMENT 1
31 December 1992

MILITARY SPECIFICATION

MODULES, STANDARD ELECTRONIC

GATE, AND-OR-INVERT, DIGITAL, KEY CODE EBA

This amendment forms a part of Military Specification MIL-M-28787/170A(EC), dated 1 June 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 4

TABLE I, Test conditions H1-H12, Test type column: Delete "X" and substitute "S"

PAGE 6

4.4.2: Delete and substitute the following:

"4.4.2 Order of testing. Test conditions A through W shall be performed in any order with the following exceptions. Test conditions A, B, C, and H are stress tests and shall be performed only at 25 ± 5°C. If test conditions A, B, C, or H are part of a sequence of tests, the order of testing shall be as follows: C, A, B, and H where applicable, followed by the remaining tests in the sequence."

4.5.1, line 5: Delete "D through R" and substitute "D through G, J through R".

4.5.2, line 4: Insert "and test condition V" following "in the test type column".

4.5.3, line 3: Delete "D through W" and substitute "D through G and J through W".

4.5.3, line 6: Delete "D through W" and substitute "D through G and J through W"

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-20T16:25Z
Check the source to verify that this is the current version before use.

PAGE 45

FIGURE 18, NOTE 3, first line: Delete "(C01)" and substitute "(C06)".

FIGURE 18, NOTE 3, second line: Delete "Frequency = 120 Hz." and substitute "Frequency = 1 KHz."

Custodians:
Army - ER
Navy - SH
Air Force - 85

Preparing activity:
Navy - NW

(Project 5963-0157)

Review activities:
Army - AT
Navy - AS, MC
Air Force - 13, 19
DLA - ES

Source: https://assist.dla.mil -- Downloaded: 20260-20T16:25Z
Check the source to verify that this is the current version before use.