MIL-C-0010244H(AR)
16 May 1978
USED IN LIEU OF
MIL-C-10244G
21 December 1970

MILITARY SPECIFICATION

CRYPTOGRAPHIC EQUIPMENT DESTROYER
INCENDIARY, TH4, M2A1

This limited coordination military specification has been prepared by the U.S. Army Armament Research and Development Command based upon currently available technical information, but it has not been approved for promulgation as a coordinated revision of MIL-C-10244G. It is subject to modification. However, pending its promulgation as a coordinated military specification, it may be used in procurement.

1. SCOPE

1.1 This specification covers one type of equipment destroyer.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of initiation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-T-60 - Tape, Pressure-Sensitive Adhesive, Waterproof, for packaging.
PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (container grade) and Cut Shapes.
TT-W-572 - Wood Preservative, Water Repellant
PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Box, Fiberboard

FSC: 1375

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116 - Preservation, Methods of
MIL-B-117 - Bags, Sleeves and Tubing, Interior Packaging.
MIL-B-2427- Boxes, Ammunition Packing, Wood, Nailed.
MIL-B-46506-Box, Ammunition Packing, Wood, Wirebound.
MIL-A-48078-Ammunition, Standard Quality Assurance Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

D4-4-27 - Cryptographic Equipment Destroyer, Incendiary, TH4, M2A1 Assembly.
IDL4-4-27- Cryptographic Equipment Destroyer, Incendiary, TH4, M2A1 - Inspection Data List
C4-4-36 - Card, Instruction
D4-4-57 - Palletization
D4-4-58 - Marking Drawing

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. - The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM B-117 - Standard Method of Salt Spray (Fog) Testing.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

CODE OF FEDERAL REGULATIONS

Title 49 - Transportation, Parts 0-190

(The Code of Federal Regulations is available from the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402. Orders should specify, "49 CFR 0-190 (latest revision)").

3. REQUIREMENTS

3.1 Materials. - Materials shall be in accordance with applicable drawings and specifications.

3.2 Components and assemblies. - The components and assemblies shall comply with all requirements specified on Dwg. DL4-4-27, all associated drawings, and with all requirements specified in applicable specifications and standards. The cryptographic equipment destroyer shall be loaded and assembled as specified on Dwg. D4-4-27. The fuzes shall not be assembled with the equipment destroyer until after leakage test. Insulated electric wire shall not be exposed to acid fumes at any time.

3.3 Main incendiary charge. - The main incendiary charge shall conform to Dwg. B143-13-6 and shall be loaded to a minimum weight of 8.5 pounds. Test as specified in 4.5.3. (See Note 6.4)

3.4 First fire mixture

3.4.1 Loading and weight. - The igniter charge assembly (Dwg. B4-4-28) shall be loaded with first fire mixture conforming to Dwg. B143-9-4. The weight of the mixture shall be no less than 27 grams when tested as specified in 4.5.2.1.

3.4.2 Moisture content. - Moisture content of first fire mixture (Dwg. B143-9-4) shall not exceed 0.10% when tested as specified in 4.5.2.2.

3.5 Leakage

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

3.5.1 Body. - The body assembly (Dwg. D4-4-34A) shall not leak when subjected to an air pressure of 5 ± 0.5 PSIG for a minimum period of 15 seconds and tested as specified in 4.5.4a.

3.5.2 Cover and adapter. - The cover (Dwg. D4-4-34B) and the adapter (Dwg. B4-4-14) assembled as shown on Dwg. D4-4-27 shall not leak when subjected to an air pressure of 5.0 ± 0.5 PSIG for a minimum period of 15 seconds and tested as specified in 4.5.4b.

3.5.3 Destroyer. - The destroyer (Dwg. D4-4-27) shall not leak when subjected to a pressure differential of 14±2 inches of water maintained in a bottle for a minimum of 15 seconds as specified in 4.5.4c.

3.6 Functioning. - Burning of the incendiary filling shall be initiated by either type fuze and shall continue until the destroyer is completely consumed when tested as specified in 4.5.5. The term "completely consumed" means that there shall be no unburned incendiary filling in the ash after burning ceases and at least 50% of the body and cover shall be consumed or burned.

3.7 First article inspection. - This specification contains technical provisions for first article inspection. Requirements for submission of first article samples shall be specified in the contract.

3.8 Workmanship. - All parts and assemblies shall be fabricated, loaded and assembled in a thorough, workmanlike manner. They shall be free from burrs, chips, sharp edges, cracks, surface defects, dirt, grease, rust, corrosion products and other foreign matter. The cleaning method and cleaning agent shall not be injurious to any part. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. - The following types of inspection shall be conducted on this item:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawing	Quantity
Body	D4-4-34A	15
Cover	D4-4-34B	15
Adapter	B4-4-14	15
Cover & Adapter, Assy	D4-4-27 Sect. A-A	15
Support assembly	D4-4-34C	15
Container, Igniter, Chg.	B4-4-30	15
Charge, Igniter Assembly	B4-4-28	15
First fire mixture V (FF-30)	B-143-9-4	5 grams
Destroyer, M2A1	D4-4-27	26

4.3.2 Inspections to be performed. - See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

TABLE I-FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-C-0010244H(AR)

PARAGRAPH	TITLE	SHEET 1 OF 2		DRAWING NUMBER
	Cryptographic Equipment Destroyer, Incendiary, TH4, M2A1			See below
				NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body (Dwg. D4-4-34A) Examination of defects	15		3.2	4.4.2.1
	Cover (Dwg. D4-4-34B) Examination of defects	15		3.2	4.4.2.2
	Support Assembly (Dwg. D4-4-34C) Examination of defects	15		3.2	4.4.2.3
	Salt Spray	5(a)		3.2	4.5.6
	Adapter (Dwg. B4-4-14) Examination of defects	15		3.2	4.4.2.4
	Cover & Adapter Assembly (Dwg D4-4-27 Section A-A) Examination of defects	15		3.2	4.4.2.5
	Container, Igniter Charge (Dwg. B4-4-30) Examination of defects	15		3.2	4.4.2.6

NOTES: (a) Samples taken from the 15.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS MIL-C-0010244H(AR)

PARAGRAPH	TITLE CONTINUATION Cryptographic Equipment Destroyer, Incendiary, TH4, M2A1		SHEET 2 OF 2		DRAWING NUMBER See below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Charge, Igniter, Assembly (Dwg. B4-4-28) Examination of defects	15		3.2	4.4.2.7
	First Fire Mixture V, (FF-30) (Dwg. B143-9-4) Examination of defects	5gr.		3.4.2	4.4.2.8
	Destroyer, M2A1 (Dwg. D4-4-27) Examination of defects	26		3.2	4.4.2.9
	Functioning	8		3.6	4.5.5

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of destroyers shall contain:

a. Parts bearing the same lot interfix number from one manufacturer.
b. Fuzes from not more than one lot interfix number from one manufacturer.
c. First fire mixture from not more than one lot interfix number from one manufacturer.
d. Incendiary mixture from not more than one lot interfix number from one manufacturer.

4.4.2 Examination. - See MIL-A-48078.

a. Sampling plans. - Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-0010244H(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Body				D4-4-34A
					NEXT HIGHER ASSEMBLY
					D4-4-27
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Width		0.40%	3.2	Gage
103	Height		0.40%	3.2	Gage
104	Soldering unsatisfactory		0.40%	3.2	Visual
105	Leakage	(a)	1.5%	3.5.1	4.5.4a.
Minor					
201	Zinc coating improper or missing		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:
(a) Table I, Level S-4 of MIL-STD-105

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-0010244H(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Cover				D 4-4-34B
					NEXT HIGHER ASSEMBLY D 4-4-27
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside length		0.40%	3.2	Gage
102	Inside width		0.40%	3.2	Gage
103	Height		0.40%	3.2	Gage
104	Diameter of fuze holes (2 places)		0.40%	3.2	Gage
105	Location of fuze holes (2 places)		0.40%	3.2	Gage
106	Welding unsatisfactory		0.40%	3.2	Visual
107	Soldering unsatisfactory		0.40%	3.2	Visual
Minor					
201	Diameter of vent holes (2 places)		0.65%	3.2	Gage
202	Location of vent holes (2 places)		0.65%	3.2	Gage
203	Zinc coating improper or missing		0.65%	3.2	Visual
204	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-0010244H(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Support Assembly		D 4-4-34C
			NEXT HIGHER ASSEMBLY D 4-4-27

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Outside width		0.40%	3.2	Gage
103	Height		0.40%	3.2	Gage
104	Location of holes for bushing (2 places)		0.40%	3.2	Gage
105	Diameter of holes for bushing (2 places)		0.40%	3.2	Gage
106	Bushing outer diameter		0.40%	3.2	Gage
107	Bushing length		0.40%	3.2	Gage
108	Brazing unsatisfactory		0.40%	3.2	Visual
Minor					
201	Protective finish inadequate (base metal exposed)		0.65%	3.2	Visual
202	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Adapter				B 4-4-14
					NEXT HIGHER ASSEMBLY D 4-4-27
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Small outer diameter		0.65%	3.2	Gage
202	Flange length		0.65%	3.2	Gage
203	Pitch diameter of thread		0.65%	3.2	Gage
204	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-0010244H(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Cover and Adapter				D 4-4-27 (Section A-A)
					NEXT HIGHER ASSEMBLY D 4-4-27
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Crimping of adapter to cover (2 places)		0.40%	3.2	Visual
102	Soldering unsatisfactory (2 places)		0.40%	3.2	Visual
103	Leakage	(a)	1.5%	3.5.2	4.5.4b
Minor					
201	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

(a) Table I, Level S-4 of MIL-STD-105

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Container, Igniter Charge				B 4-4-30
					NEXT HIGHER ASSEMBLY
					B 4-4-28
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inner diameter		0.40%	3.2	Gage
102	Outer diameter		0.40%	3.2	Gage
103	Length		0.40%	3.2	Gage
104	Bond unsatisfactory		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-0010244H(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Charge, Igniter, Assembly				B 4-4-28
					NEXT HIGHER ASSEMBLY
					D 4-4-27
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Igniter charge weight		0.40%	3.4.1	4.5.2.1
102	Igniter charge loose, cracked, or improperly consolidated		0.40%	3.2	Visual/x-ray
Minor					
201	Igniter charge cavity depth		0.65%	3.2	Gage
202	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER B143-9-4
4.4.2.8	First Fire Mixture V, (FF-30)				NEXT HIGHER ASSEMBLY B4-4-28
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Moisture content	(a)	0.40%	3.4.2	4.5.2.2
Minor	None defined				

NOTES: (a)Sample shall be taken at each shift at time of loading

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.9	Cryptographic Equipment Destroyer, Incendiary, TH4, M2A1		D 4-4-27
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Lead wire not shunted and soldered (Dwg. 36-7-25)		100%	3.2	Visual
Major					
101	Taping of bushing to igniter charge container loose or not adhering (2 places)		0.40%	3.2	Visual
102	Incendiary mixture weight		0.40%	3.3	4.5.3
103	Length, cavity for igniter charge container (2 places)		0.40%	3.2	Gage
104	Diameter, cavity for igniter charge container (2 places)		0.40%	3.2	Gage
105	Minimum Torque, Smoke pot fuze electric		0.40%	3.2	Gage
106	Minimum Torque, Incendiary fuze, M210		0.40%	3.2	Gage
107	Tape on side seam loose or not adhering		0.40%	3.2	Visual
108	Tape on cover loose or not adhering		0.40%	3.2	Visual
109	Tape on pull ring loose or not adhering		0.40%	3.2	Visual
110	Component missing or incorrectly assembled		0.40%	3.2	Visual
111	Marking incorrect,missing, or illegible		0.40%	3.2	Visual
112	Leakage	(a)	1.5%	3.5.3	4.5.4c
113	Functioning	(a)	1.5%	3.6	4.5.5

NOTES:

(a) Table I, Level S-4 of MIL-STD-105

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.9	CONTINUATION Cryptographic Equipment Destroyer, Incendiary, TH4, M2A1				D 4-4-27
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Tape on vent hole loose or not adhering (2 places)		0.65%	3.2	Visual
202	Protective finish inadequate (base metal exposed)		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Packaging (Prior to closing fiber board box), Cryptographic Equipment Destroyer, Incendiary, TH4, M2A1				--- NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Wooden block improperly placed or missing		0.40%	3.2	Visual
102	Water-vapor proof barrier bag unsealed or torn		0.40%	3.2	Visual
103	Instruction card incorrect or missing		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.0%	3.3	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Packaging, Cryptographic Equipment Destroyer, Incendiary, TH4, M2A1				--- NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box punctured, cut or torn		0.40%	3.2	Visual
102	Tape strip incomplete or badly wrinkled		0.40%	3.2	Visual
Minor					
201	Contents move when shaken		0.65%	3.2	Manual
202	Marking incorrect or incomplete		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.00%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-00102441(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.12	Packing- (Prior to closing shipping container) Cryptographic Equipment Destroyer, Incendiary, TH4, M2A1		--- NEXT HIGHER ASSEMBLY ---

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Shipping container improperly treated and dried		0.40%	3.2	Visual
102	Less than 2 destroyers packed in shipping container		0.40%	3.2	Visual
103	Filler pads loose or missing		0.40%	3.2	Visual
Minor					
201	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-0010244H(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER ----
4.4.2.13	Packing-Cryptographic Equipment Destroyer, Incendiary, TH4, M2A1				NEXT HIGHER ASSEMBLY ----
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box, broken or split		0.40%	3.2	Visual
102	Strapping missing or loose		0.40%	3.2	Visual
Minor					
201	Contents move when shaken		0.65%	3.2	Manual
202	Marking incorrect or incomplete		0.65%	3.2	Visual
203	Evidence of poor workmanship		1.0%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. - Testing is described in the Qirst Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. - The inspection equipment required to perform the examinations is identified, either directly or by reference, in the "Paragraph Reference/Inspection Method" column of the First Article or Quality Conformance Inspection Tables herein. The contractor shall submit inspection equipment designs to the Government for approval in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures

4.5.1 Materials, components and processes. - Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed.

4.5.2 First fire mixture

4.5.2.1 Weight. - Weigh the igniter charge container before and after loading to calculate the net weight of the first fire mixture.

4.5.2.2 Moisture content. - Place 5 grams of the material to be tested into a tared weighing dish. Place in an oven maintained at 100°C for 3 hours. Cool in a desicator and weigh. Calculate the loss in weight of contents as the percent moisture.

4.5.3 Main incendiary charge. - The destroyer body shall be weighed prior to and after loading in order to determine weight of main incendiary charge.

4.5.4 Leakage

(a) Body. - Mount the body assembly in a suitable fixture in which a positive pressure can be maintained inside the body. Subject the body to the specified air pressure for the required period of time. Coat the seams with a soap solution. Bubbles shall indicate leakage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

(b) Cover. - Mount the cover assembly in a suitable fixture in which a positive pressure can be maintained inside the cover. Subject the cover to the specified air pressure for the required period of time. Coat the seams and the adapter's soldered joints with a soap solution. Bubbles shall indicate leakage.

(c) Destroyer. - The assembled destroyer shall have plugs in place of fuzes. Place 1 inch of water in a bottle and close with a two hole stopper. Insert a glass tube through one of the holes until the tube dips about 1/2 inch below the surface of the water. Connect the other end of the tube to a suitable trap, then through a flexible hose to a suitable adapter screwed into the fuze adapter hole in the cover. Connect the second hole in the stopper to a source of vacuum so that a pressure differential of 14 $\pm$ 2 inches of water is maintained in the bottle. A continuous stream of bubbles will be emitted from the tube and below the surface of the water until equal pressures exist between the bottle and the destroyer, at which time a definite break in bubbling continuity should occur. Continuous bubbling, evidenced by absence of the break in bubbling continuity, indicates a leak in the destroyer. If bubbles do not appear for a minimum period of 15 seconds subsequent to this definite break in bubbling continuity, the destroyer shall be considered intact. Intermittent bubbling subsequent to the 15 seconds break shall not be cause for rejection. All taped areas including the immediately adjacent metal surfaces shall be given at least one additional coat of paint on each test unit following any leakage testing.

4.5.5 Functioning. - Sample destroyers will be functioned by alternate use of the mechanical and electrical fuzes (i.e., function one destroyer with mechanical fuze and next destroyer with electric fuze). All destroyers shall be functioned in accordance with the instruction card, Dwg. C4-4-36. The destroyer shall be functioned while resting on the ground on its broadside and the electric circuit shall be capable of furnishing 1 amp maximum at 1.5 volts maximum (a standard 1.5 volt battery may be used).

4.5.6 Salt spray. - The support assembly shall be subjected to the salt spray test in accordance with ASTM B-117.

5. PREPARATION FOR DELIVERY

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

5.1 Packaging

5.1.1 Level A. - One cryptographic equipment destroyer and one instruction card, conforming to Drawing C4-4-36 shall be packaged in a fiberboard box conforming to grade W5c, style FOL of PPP-B-636. Inside dimensions shall be approximately 8-3/4 inches by 2 inches by 17-3/4 inches (length, width and depth respectively). A block of wood measuring approximately 4-1/4 inches by 3/4 inch by 1-3/8 inches shall be placed in the box between the mechanical and electrical fuzes. The block of wood shall be positioned so as to extend beyond the top protrusions of each fuze. Closure of the top box shall be in accordance with the appendix to PPP-B-636 using PPP-T-60 tape. The closed and taped box shall then be placed in a water-vapor proof barrier bag conforming to type II, class E, style 1 of MIL-B-117. The bag shall be heat sealed as specified in MIL-P-116. The inside dimensions of the bag shall be approximately 23 inches long by 11-3/4 inches wide.

5.2 Preservation and packing

5.2.1 Preservation. - The shipping container and all wood parts thereof, shall be fully immersed for a minimum of three minutes in a water-repellent wood preservative conforming to composition A of TT-W-572. Prior to packing the cryptographic equipment destroyers in the treated shipping containers, the preservative shall be dry as evidenced by the dryness test specified in MIL-B-2427.

5.2.2 Level A. - Two cryptographic equipment destroyers packaged as specified in 5.1.1 shall be packed together in a wooden shipping container conforming to either overseas type, style J of PPP-B-601; class 2, style 4, type 1 of PP-B-621; or type I, class B, grade A of MIL-B-46506. Inside dimensions of the box shall be approximately 18-7/8 inches by 10-1/4 inches by 5-1/4 inches (length, width and depth respectively). Filler pads fabricated from material conforming to grade W5c of PPP-F-320 shall separate the contents from the top, ends, sides and bottom of the shipping container. Additional filler pads shall be used as necessary to insure a tight pack. The box shall be closed and strapped in accordance with the appendix of the applicable box specification using galvanized strapping.

5.3 Marking. - In addition to any special marking required by the contract of order, the unit packages shall be marked in accordance with MIL-STD-129. Shipping containers

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

shall be marked in accordance with Drawing D4-4-58. Sufficient drying time shall be allowed after application of the wood preservative to insure that all marking shall be clear, legible and permanent.

5.4 Palletization. - When specified in the contract or order, shipping containers shall be palletized and marked in accordance with Drawing D4-4-57.

6. NOTES

6.1 Intended use. - This item is intended to destroy cryptographic equipment during emergencies.

6.2 Ordering data. - See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. - See MIL-A-48078. Submit equipment designs, as required, to Commander, USAARADCOM, ATTN: DRDAR-QAA-I, Dover, New Jersey 07801.

6.4 Loading. - A satisfactory loading procedure has been experienced by loading in four approximately equal increments individually tamped and pressed into the assembly.

6.5 Advisory note - sealing procedure. - Prior to placing the cover (D4-4-34B) onto the body (D4-4-34A), perform the following operations:

a. Clean the inside of the cover and the mating surface of the body thoroughly, then wipe with acetone.

b. Apply Dow Corning 1203 primer (red) to the cleaned surfaces and allow to dry for two hours at room temperature.

c. Apply Dow Corning 3145 RTV adhesive/sealant as a 3/16 uniform bead around the inside top of cover. Also, apply a 3/16 continuous uniform bead along outside of the body approximately 1" from the top.

d. Assemble the cover to the body and allow the unit to stand undisturbed at room temperature for 24 hours.

e. Next proceed to tape, paint, add the fuzes and complete assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

The above procedure has been found to produce a satisfactory seal in laboratory tests on a limited quantity of six items. This advisory note is furnished for informational purposes and this particular procedure is not a requirement of the contract. The contractor is required to meet the contractual requirements of the contract regardless of whether or not the contractor uses the note. The Government makes no warranty or representations that the use of the note will result in items conforming to contractual requirements.

6.6 Drawings. - Drawings listed in Section 2 of this specification under the heading "U.S. Army Armament Research and Development Command" (ARRADCOM) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARRADCOM.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number 1375-A-216

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.