MIL-C-10244G
21 December 1970
SUPERSEDING
MIL-C-0010244F(MU)
26 August 1969
MIL-C-10244E
12 January 1965

MILITARY SPECIFICATION

CRYPTOGRAPHIC EQUIPMENT DESTROYER,

INCENDIARY, TH4, M2A1

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of equipment destroyer.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

TT-W-572	-	Wood Preservative, Water Repellant.
PPP-B-601	-	Boxes, Wood, Cleated-Plywood.
PPP-B-621	-	Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636	-	Box, Fiberboard.
PPP-F-320	-	Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade) and Cut Shapes.
PPP-T-60	-	Tape, Pressure-Sensitive Adhesive, Waterproof, for Packaging.

MILITARY

MIL-P-116	-	Preservation, Methods of.
MIL-B-117	-	Bags, Sleeves and Tubing, Interior Packaging.
MIL-B-2427	-	Boxes, Ammunition Packing, Wood, Nailed.
MIL-B-46506	-	Box, Ammunition Packing, Wood, Wirebound.

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1168 - Lot Numbering of Ammunition.

DRAWINGS

US ARMY MUNITIONS COMMAND

EDGEWOOD ARSENAL

DL4-4-27 - Cryptographic Equipment Destroyer, Incendiary, TH4, M2A1.
IDL4-4-27 - Cryptographic Equipment Destroyer, Incendiary, TH4, M2A1 - Inspection Data List.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL4-4-27 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the cryptographic equipment destroyer shall conform to the specifications and drawings listed on Drawing DL4-4-27 and subsidiary drawings.

3.2 Assembly. The cryptographic equipment destroyer shall be loaded and assembled in accordance with Drawing D4-4-27. The fuzes shall not be assembled with the destroyer until after the leakage test. Insulated electric wire shall not be exposed to acid fumes at any time (see 6.3).

3.3 Main incendiary charge. The assembled destroyer shall be loaded with a main charge mixture conforming to Drawing B143-13-6 in four approximately equal increments individually tamped and pressed into the assembly (see 6.3). The weight of the charge shall be no less than 8.5 pounds.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

3.4 Igniter charger container. The igniter charger assembly, Drawing B4-4-28, shall be loaded with first fire mixture conforming to Drawing B143-9-4. The weight of the mixture shall be no less than 27 grams when tested as specified in 4.4.4.1 (see 6.3).

3.5 Leakage.

3.5.1 Body. The body assembly, Drawing D4-4-34 shall not leak when subjected to an air pressure of 5 ± 0.5 pound per square inch gage (psig) for a minimum period of 15 seconds and tested as specified in 4.4.4.2(a).

3.5.2 Cover. The cover assembly less fuzes, Drawing D4-4-34 shall not leak when subjected to an air pressure of 5 ± 0.5 psig for a minimum period of 15 seconds and tested as specified in 4.4.4.2(b).

3.5.3 Destroyer. The destroyer shall not leak when tested as specified in 4.4.4.2(c).

3.6 Functioning. Burning of the incendiary filling shall be initiated by either type fuze and shall continue until the destroyer is completely consumed when tested as specified in 4.4.4.3. The term "completely consumed" means that there shall be no unburned incendiary filling in the ash after burning ceases (see 6.3).

3.7 Preproduction. Prior to the start of regular production, a preproduction sample of destroyers shall be produced in accordance with this specification for examination and test (see 4.3).

3.8 Workmanship. The destroyer shall be free from contamination (oil, grease or foreign matter) and damage such as dents, cracks or deformation which could affect its use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to specified requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

4.1.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections.

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection.

4.3.1 Lot. A preproduction lot of 26 destroyers shall be manufactured using the same methods, materials, equipment and processes as will be used during regular production.

4.3.2 Sampling.

4.3.2.1 For examination and nondestructive test. Sampling shall be conducted in accordance with MIL-STD-105.

4.3.2.2 For destructive test. Eight destroyers shall be taken at random from the preproduction lot.

4.3.3 Inspection procedure.

4.3.3.1 For examination and nondestructive test. The sample destroyers shall be examined and tested in accordance with the classification of defects. The AQL's do not apply.

4.3.3.2 For destructive test. The sample destroyers shall be tested in accordance with 4.4.4.3.

4.3.3.3 Critical characteristics. Each destroyer in the preproduction lot shall be inspected for the critical characteristics listed in the classification of defects.

4.3.4 Acceptance/rejection criteria. The preproduction lot shall comply with the examinations and tests specified in 4.3.3 to be acceptable. The acceptance number is zero. The supplier shall obtain written approval from the contracting officer prior to proceeding with regular production.

4.4 Quality conformance inspection.

Source: https://assist.dla.mil -- Downloaded: 20261O-17T13:42Z
Check the source to verify that this is the current version before use.

4.4.1 Lotting. Each lot shall be identified and controlled in accordance with MIL-STD-1168. Contained in anyone interfix number of destroyers, no more than one interfix number from one manufacturer of the following components is permitted.

a. Fuzes
b. Loaded main charge containers
c. Loaded igniter charge containers

4.4.2 Sampling.

4.4.2.1 For examination and nondestructive test. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.2.2 For destructive test. Samples shall be taken from each lot at random in accordance with table I.

Table I. Sampling

Testing	Sample size
Normal	12
Reduced	2

4.4.3 Inspection procedure.

4.4.3.1 For examination and nondestructive test. Sample cryptographic equipment destroyers and the level A preparation for delivery shall be examined and tested in accordance with the classification of defects and with MIL-STD-105.

4.4.3.2 For destructive test. The sample destroyers shall be tested in accordance with 4.4.4.3. When three consecutive lots have been accepted, reduced testing shall be used. If one destroyer fails the test, the lot shall be rejected, with subsequent testing under the normal plan until three consecutive lots have been accepted. The destroyer may be refuzed and functioned, if fuze fails to ignite.

4.4.3.3 Critical characteristic. Each destroyer in the lot shall be inspected for its critical characteristic listed in the classification of defects.

Source: https://assist.dla.mil -- Downloaded: 20261O-17T13:42Z
Check the source to verify that this is the currentversion before use.

4.4.3.4 Classification of defects.

(a) Cryptographic equipment destroyer, incendiary, TH4, M2A1 - assembly (Dwg D4-4-27).

Categories	Defects	Acceptance standards
Critical:		
1	Lead wire not shunted and soldered	
Major: AQL 1.0 percent defective		
101	Igniter charge container length incorrect	
102	Igniter charge radius incorrect	
103	Igniter charge depth to radius incorrect	
104	Igniter charge cavity depth incorrect	
105	Igniter charge cavity diameter incorrect	
106	Component missing or incorrectly assembled	
107	Marking incorrect	
108	Igniter charge outside diameter at bottom incorrect	
109	Igniter charge mixture loose, cracked or improperly consoldiated	
110	Length incorrect (D4-4-34)	
111	Width incorrect (D4-4-34)	
112	Height incorrect (D4-4-34)	
113	Minimum torque incorrect	
114	Workmanship (3.8)	
115	Igniter charge container weight incorrect	4.4.4.1
116	Leakage	4.4.4.2
Minor: AQL 2.5 percent defective		
201	Main charge weight incorrect	
202	Protective finish missing or incorrect	
203	Marking missing or illegible	

Source: https://assist.dla.mil -- Downloaded: 20261O-17T13:42Z
Check the source to verify that this is the current version before use.

4.4.3.4 Classification of defects (continued).

(b) Preparation for delivery.

Categories	Defects
Critical:	None defined
Major:	AQL 2.5 percent defective
101	Hardware missing
102	Closure of containers incorrect
103	Straps loose or missing
104	Marking incorrect or illegible
105	Improperly sealed barrier bags
Minor:	AQL 4.0 percent defective
201	Instruction card missing or coated incorrectly

4.4.4 Tests. Tests shall be conducted as follows: (See inspection data list IDL4-4-27 for inspection equipment required to perform the tests specified in this section).

4.4.4.1 Igniter charge container. Weigh the igniter charge container before and after loading to calculate the net weight of the first fire mixture.

4.4.4.2 Leakage.

(a) Body. Mount the body assembly in a suitable fixture in which a positive pressure can be maintained inside the body. Subject the body to the specified air pressure for the required period of time. Coat the seams with a soap solution. Bubbles shall indicate leakage.

(b) Cover. Mount the cover assembly in a suitable fixture in which a positive pressure can be maintained inside the cover. Subject the cover to the specified air pressure for the required period of time. Coat the seams and the adapters soldered joints with a soap solution. Bubbles shall indicate leakage.

(c) Destroyer. The assembled destroyer shall have plugs in place of fuzes. Place 1 inch of water in a bottle and close with a two-hole stopper. Insert a glass tube through one of the holes until the tube dips about 1/2 inch below the surface of the water. Connect the other end of the tube to a suitable trap, then through a flexible

Source: https://assist.dla.mil -- Downloaded: 20261O-17T13:42Z
Check the source to verify that this is the current version before use.

hose to a suitable adapter screwed into the fuze adapter hole in the cover. Connect the second hole in the stopper to a source of vacuum so that a pressure differential of 14 ± 2 inches of water is maintained in the bottle. A continuous stream of bubbles will be emitted from the tube end below the surface of the water until equal pressures exist between the bottle and the destroyer, at which time a definite break in bubbling continuity should occur. Continuous bubbling, evidenced by absence of the break in bubbling continuity, indicates a leak in the destroyer. If bubbles do not appear for a minimum period of 15 seconds subsequent to this definite break in bubbling continuity, the destroyer shall be considered intact. Intermittent bubbling subsequent to the 15 seconds break shall not be cause for rejection. All taped areas including the immediately adjacent metal surfaces shall be given at least one additional coat of paint on bubbling continuity, indicates a leak in the destroyer.

4.4.4.3 Functioning. One half of the sample destroyers shall be functioned by the mechanical fuze and the remaining half by the electric fuze. All destroyers shall be functioned while resting on their broadest flat side.

5. PREPARATION FOR DELIVERY

5.1 Packaging level A. One cryptographic equipment destroyer and one instruction card, conforming to Drawing C4-4-36 shall be packaged in a fiberboard box conforming to grade W5c, style FOL of PPP-B-636. Inside dimensions shall be approximately 8-3/4 inches by 2 inches by 17-3/4 inches (length, width and depth respectively). A block of wood measuring approximately 4-1/4 inches by 3/4 inch by 1-3/8 inches shall be placed in the box between the mechanical and electrical fuzes. The block of wood shall be positioned so as to extend beyond the top protrusions of each fuze. Closure of the top box shall be in accordance with the appendix to PPP-B-636 using PPP-T-60 tape. The closed and taped box shall then be placed in a water-vapor proof barrier bag conforming to type II, class E, style 1 of MIL-B-117. The bag shall be heat sealed as specified in MIL-P-116. The inside dimensions of the bag shall be approximately 23 inches long by 11-3/4 inches wide.

5.2 Packing, level A. Two cryptographic equipment destroyers, packaged as specified in 5.1 shall be packed together in a wooden shipping container conforming to either overseas type, style J of PPP-B-601; class 2, style 4, type 1 of PPP-B-621; or type I, class B, grade A of MIL-B-46506. Inside dimensions of the box shall be approximately 18-7/8 inches by 10-1/4 inches by 5-1/4 inches (length, width and depth respectively). Filler pads fabricated from material conforming to grade W5c of PPP-F-320 shall separate the contents from the top, ends, sides and bottom of the shipping container. Additional filler pads shall be used as necessary to insure a tight pack. The shipping container and all wood parts thereof, shall be fully immersed for a minimum of three minutes in a water-repellent wood preservative

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

conforming to composition A of TT-W-572. Prior to packing the cryptographic equipment destroyers in the treated shipping containers, the preservative shall be dry as evidenced by the dryness test specified in MIL-B-2427. The box shall be closed and strapped in accordance with the appendix of the applicable box specification using galvanized strapping.

5.3 Marking. In addition to any special marking required by the contract of order, the unit packages shall be marked in accordance with MIL-STD-129. Shipping containers shall be marked in accordance with Drawing D4-4-58. Sufficient drying time shall be allowed after application of the wood preservative to insure that all marking shall be clear, legible and permanent.

5.4 Palletization. When specified in the contract or order, shipping containers shall be palletized and marked in accordance with Drawing D4-4-57.

6. NOTES

6.1 Intended use. This item is intended for destruction of cryptographic equipment in an emergency.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Preproduction:

(1) Time allowed for supplier submission of sample for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the supplier whether or not to proceed with production.

6.3 Caution. Suppliers are hereby notified to take all necessary precaution to protect personnel while preparing incendiary mixtures, loading and testing destroyers.

6.4 Component specification. The following specifications reflect the components required for the manufacture of the cryptographic equipment destroyer:

MIL-F-10915 - Fuze, Hand Grenade, M201A1, M207A1 and M210.
MIL-F-11673 - Fuze, Smoke Pot, Floating, Electric, M209.

Source: https://assist.dla.mil -- Downloaded: 20260-17T13:42Z
Check the source to verify that this is the current version before use.

Custodians:

Army - MU
Navy - OS
Air Force - 70

Review activities:

Navy - OS
Air Force - 70

Preparing activity:

Army - MU(EA)

Project No. 1375-0147

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.

TO DETACH FORM - CUT ON THIS LINE

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE | CONTRACT NUMBER

MATERIAL PROCURED UNDER A
☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
   ☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)* | DATE

DD FORM 1 JAN 66 1426 REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T13:42Z
Check the source to verify that this is the current version before use.