A-A-1274A
May 26, 1987
SUPERSEDING
A-A-1274
November 1, 1979

COMMERCIAL ITEM DESCRIPTION

WRENCH, TORQUE, INDICATING, DEFLECTING BEAM

The General Services Administration has authorized the use of this commercial item description in preference to Type I, Class 1, Styles A, B, and C of Federal Specification GGG-W-686.

Salient characteristics:

Conform to ANSI B107.14M and as follows:

National Stock Number	Square Drive Size (inch)	Torque Capacity	Increment Graduations (Maximum)
		Type 1, Class A, Style 1	
5120-00-595-9070	1/4	0-16 inch-ounces	1 inch-ounce
5120-00-580-7397	1/4	0-32 inch-ounces	2 inch-ounces
5120-00-729-6427	1/4	0-80 inch-ounces	5 inch-ounces
5120-00-736-2483	1/4	0-5 inch-pounds	1/4 inch-pound
5120-00-618-4433	1/4	0-10 inch-pounds	1/2 inch-pound
5120-00-221-7971	1/4	0-25 inch-pounds	1 inch-pound
5120-00-529-2552	1/4	0-60 inch-pounds	2 inch-pounds
5120-00-900-1283	1/4	0-120 inch-pounds	5 inch-pounds
5120-00-177-7337	3/8	0-25 inch-pounds	1 inch-pound
5120-00-684-0404	3/8	0-50 inch-pounds	2 inch-pounds
5120-01-026-4052	3/8	0-100 inch-pounds	5 inch-pounds
5120-00-585-7706	3/8	0-120 inch-pounds	5 inch-pounds
5120-00-853-4538	3/8	0-200 inch-pounds	10 inch-pounds
5120-00-542-5681	3/8	0-600 inch-pounds	25 inch-pounds
5120-00-541-3001	3/8	0-50 foot-pounds	2-1/2 foot-pounds
5120-00-247-2536	1/2	0-300 inch-pounds	10 inch-pounds
5120-00-221-7947	1/2	0-600 inch-pounds	25 inch-pounds
5120-00-116-2829	1/2	0-1200 inch-pounds	50 inch-pounds
5120-00-910-3350	1/2	0-2400 inch-pounds	50 inch-pounds
5120-00-247-2540	1/2	0-150 foot-pounds	5 foot-pounds
5120-01-086-3072	3/4	0-3600 inch-pounds	100 inch-pounds
5120-00-900-1285	3/4	0-300 foot-pounds	10 foot-pounds
		Type 1, Class A, Style 2	
5120-00-993-1522	3/8	0-50 inch-pounds	2 inch-pounds
5120-00-720-1975	3/8	0-100 inch-pounds	5 inch-pounds
5120-00-011-5860	3/8	0-200 inch-pounds	10 inch-pounds
5120-00-958-6906	3/8	0-300 inch-pounds	10 inch-pounds
5120-00-720-0714	3/8	0-600 inch-pounds	25 inch-pounds
5120-01-046-1738	3/8	0-1200 inch-pounds	50 inch-pounds
5120-00-965-5937	1/2	0-1200 inch-pounds	50 inch-pounds
5120-00-240-5371	1/2	0-100 foot-pounds	5 foot-pounds
5120-01-072-9780	3/4	0-0.3 foot-pound	0.1 foot-pound
5120-00-113-8211	3/4	0-200 foot-pounds	5 foot-pounds
5120-00-720-0715	1	0-750 foot-pounds	25 foot-pounds
		Type 1, Class A, Style 3	
5120-00-819-1049	3/8	0-600 inch-pounds	25 inch-pounds
5120-00-993-1521	1/2	0-1200 inch-pounds	50 inch-pounds

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:12Z
Check the source to verify that this is the current version before use.

Drive tang shall not be made of powdered metal.
Wrenches of a capacity greater than that specified are not acceptable.
Instructions shall include procedures for maintenance and recalibration of the torque wrenches.

Marking. Each torque wrench shall be be marked in a plain and permanent manner with month and year of manufacture (e.g., 12/85 for December 1985), manufacturer's name or identifying symbol, part number, and country of origin.

Quality assurance provisions.

Inspection. Sampling for inspection shall be in accordance with MIL-STD-105, Sampling Procedures and Tables for Inspection by Attributes, except where otherwise specified. The lot size shall consist of all torque wrenches offered for acceptance at one time. The sample unit is one torque wrench.

Examination for visual and operating load requirements. Each torque wrench shall be examined for workmanship, marking and operating load requirements. The inspection level shall be Level II with an acceptable quality level (AQL) of 2.5 defects per hundred units.

Testing for conformance. Each torque wrench shall be tested for conformance in accordance with criteria set forth in applicable portions of paragraphs 4.1 through 4.16 of ANSI B107.14M with an inspection level of S-2 with an AQL of 2.5 defects per hundred units.

Regulatory requirements. In accordance with the section 23.403 of the Federal Acquisition Regulations, the Government's policy is to acquire items composed of the highest percentage of recovered materials practicable, consistent with maintaining a satisfactory level of competition without adversely affecting performance requirements or exposing suppliers' employees to undue hazards from the recovered materials.

Preservation, packaging, packing, labeling, and marking. The preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order. (For use by GSA; optional for other agencies.) DoD may use Commercial Packaging, Standard ASTM D3951.

NOTE:

The issue of the referenced documents in effect on the date of the solicitation shall be used to determine compliance with stated requirements.

Military Standards are available from Naval Publications and Forms Center, 5801 Tabor Avenue, Philadelphia, PA 19120.

ANSI Standards are available from American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.

ASTM Standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

MILITARY INTERESTS:

Custodian:

Army - GL

Review Activity:

Air Force - 99
Navy - YD

User:

Navy - OS

PREPARING ACTIVITY:

GSA/FSS

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:12Z
Check the source to verify that this is the current version before use.