A-A-1723
October 19, 1982

COMMERCIAL ITEM DESCRIPTION

CLEANING COMPOUND, PORCELAIN AND CERAMIC TILE (CREAM CLEANSER)

The General Services Administration has authorized the use of this commercial item description in preference to Federal Specification P-C-1891, Type II.

Salient characteristics:

The cream cleanser shall be class 1 - with chlorine bleach, or class 2 - regular, as specified in the contract.

The cream cleanser shall be an aqueous suspension of mild abrasive, detergents, builder, chlorine bleach (class 1 only) and other ingredients as needed. The cream cleanser shall rapidly remove stubborn scuffs, stains, grease, soap scum, dirt and grime on porcelain, tile and stainless steel. The class 1 cleanser shall be safe to use on aluminum and chrome as well as porcelain, tile and stainless steel.

Available chlorine, class 1. The class 1 cream cleanser shall have not less than 1.20 percent by weight available chlorine when tested as specified in ASTM A 2022 - Sampling and Chemical Analysis of Chlorine-Containing Bleaches.

Performance. When tested as follows, the cream cleanser shall remove all the test soil and not scratch the glass panel:

Ingredients	Percent by weight
Lanolin, anhydrous	38.0
Asphalt (conforming to ASTM A 312, type II)	12.0
Turpentine	20.0
Lubricating oil, automotive, 30W nondetergent	15.0
Lampblack (conforming to ASTM D 209)	15.0

The issues of the ASTM standards in effect on the date of the solicitation shall be used to determine compliance with these requirements.

Weigh 3.0 grams of the soiling mixture onto the surface of a clean, scratch-free, 4" x 4" square window glass pane. Using a dry cloth, such as cheese-cloth, spread the soil to thinly and evenly coat one side of the pane. Weigh out 3.0 grams of cream cleanser, spread on a wad of clean, dampened cloth of soft material like unsized cotton and apply to the soiled glass panel with a circular hand motion. Let it dry, forming a film. Wipe the dried film off the glass panel with a clean, dry cloth. The soiling mixture shall have been completely removed from the glass panel. There shall be no streaks or scratches on the glass. There shall be no fine abrasion of the glass surface which causes distortion or blurring of images seen through the glass panel.

Preservation, packaging, packing, and marking. Preservation, packaging, packing, and marking shall be as specified in the contract or order.

Note: The ASTM standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

PREPARING ACTIVITY:

GSA - OPP

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.