A-A-1740
December 31, 1981

COMMERCIAL ITEM DESCRIPTION

LAMP, PHOTO, PROJECTION

The General Services Administration has authorized the use of this commercial item description.

This description covers photo projection lamps with a MR-16 glass reflector.

Salient characteristics:

The lamp shall be tungsten-halogen lamp.
The lamp shall be mounted in a 2-inch diameter dichroic reflector.
The mounting distance shall be 6 inches for ELH and ENH, and 11-3/4 inches for ENX, and 6-1/2 inches for ELD/EJN.
The lamp shall burn base down to horizontal.
The lamps shall have the following characteristics in accordance with Table I.
The lamp should be protected from scratches and abrasions.
The lamp should not be used at over 110 percent of rated voltage.

TABLE I

ANSI Lamp type	Watts	Volts	Base	Filament	Average rated Life (hours)	Max. Overall Length (inch)	Approx. Color Temp °K	Use
ELH	300	120	Oval 2-pin	CC-8	35	1-3/4	3350	Slide
ENH	250	120	Oval 2-pin	CC-8	175	1-3/4	3250	Slide
ENX	360	82	Oval 2-pin	CC-8	75	1-3/4	3300	Overhead
ELD/EJN	150	21	2-pin	CC-6	40	1-3/4	3350	Microfilm

The issues of ANSI C78.370 and C78.1405 in effect on the date of the solicitation shall be used to determine compliance with these requirements and lamp designations.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. Packaging, packing, and marking shall be as specified to the contract or order.

ANSI Standards C78.370 and C78.1405 are available from American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.

MILITARY INTERESTS:

User Activity

Air Force - 99

CIVIL AGENCY COORDINATING ACTIVITY:

GSA-FSS

PREPARING ACTIVITY:

GSA-FSS

FSC 6240

GSA SC-01201846

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:16Z
Check the source to verify that this is the current version before use.