A-A-1744
November 24, 1981

COMMERCIAL ITEM DESCRIPTION

LAMP, PHOTO, PROJECTION, MOVIE

The General Services Administration has authorized the use of this commercial item description.

This description covers photo projection lamps with a MR-14 glass reflector.

Salient characteristics:

The lamp shall be tungsten-halogen lamp.
The lamp shall be mounted in a 1-3/4 inch diameter dichroic reflector.
The mounting distance shall be 3-7/32 inches for ELE/ELT and 2-19/32 inches for EMM/EKS.
The lamp shall burn as indicated in Table I.
The lamp shall be protected from scratches and abrasions.
The lamp shall not be used at over 110 percent of rated voltage.
The lamps shall have the following characteristics in accordance with Table I.

TABLE I

ANSI Lamp type	Watts	Volts	Base	Filament	Average Rated Life Hrs	Light Center Length Inches	Max. Overall Length Inches	Approx Color Temp. °K	Use
ELE/ELT*	80	30	2-pin vented	CC-6 or CC-8	20	5/8	1-45/64	3,450	8 MM
EMM/EKS**	250	24	2-pin vented	CC-6	50	5/8	1-45/64	3,450	16 MM

* Burn horizontal
** Burn base down to horizontal

The issue of ANSI C78.1412 in effect on the date of the solicitation shall be used to determine compliance with these requirements and lamp designations.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. Packaging, packing, and marking shall be as specified in the contract or order.

ANSI Standard C78.1412 is available from American National Standards Institute Inc., 1430 Broadway, New York, NY 10018.

MILITARY INTERESTS:

User Activities

Air Force - 99

CIVIL AGENCY COORDINATING ACTIVITY:

GSA FSS

PREPARING ACTIVITY:

GSA - FSS

FSC 6240

GSA FPS-0130184

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.