A-A-1759
December 31, 1981

COMMERCIAL ITEM DESCRIPTION

LAMPS, METAL HALIDE (400 WATTS)

The General Services Administration has authorized the use of this commercial item description.

This description covers metal halide lamps of 400 watts for general and street lighting.

Salient characteristics:

The lamp shall operate only on ANSI specified M59 metal halide ballasts.
Although the outer bulb is made of heat-resistant glass, external protection of the lamp is still required to eliminate the chance of bulb breakage due to direct contact with water during lamp operation.
The lamp shall be in accordance with ANSI C78.380, C78.387, and C78.1375.
The lamp shall have the characteristics specified in Table I.

TABLE I

Type	ANSI Code ****	Watts	Bulb	Base	Max. Overall Length (Inches)	Finish	Average Rated Life (hrs)	Approx. Lumens **Initial	Approx. Lumens Mean***
1	M59PJ-R400/VBU	400	BT-37/E-37	Mogul	11-1/2	Clear	15,000	34,000	25,600
2	M59PJ-R400/VBD	400	BT-37/E-37	Mogul	11-1/2	Clear	15,000	34,000	25,600
3	M59PJ-R400/U	400	BT-37/E-37	Mogul	11-1/2	Clear	15,000	(Vertical) 34,000	25,600
								(Horizontal) 37,000	23,600
4	M59PK-R400/VBU	400	BT-37/E-37	Mogul	11-1/2	Coated	15,000	34,000	25,600
5	M59PK-R400/VBD	400	BT-37/E-37	Mogul	11-1/2	Coated	15,000	34,000	25,600
6	M59PK-R400/U	400	BT-37/E-37	Mogul	11-1/2	Coated	15,000	(Vertical) 34,000	24,600
								(Horizontal) 32,000	22,600

* The average rated life is for 10 hours per start.
** Initial lumen ratings are based upon 100 hour photometry readings at rated lamp watts.
*** Values shown are based on operation under specified test conditions with 10 hours or more burning per start.
****VBU = Base up - Burn Vertical Base Up to ± 15° of vertical base up.
VBD = Base down - Burn Vertical Base Down to ± 15° of vertical base down.
U = Universal burning, any burning position.

The issues of ANSI C78.380, C78.387, and C78.1375 in effect on the date of the solicitation shall be used to determine compliance with these requirements.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. Packaging, packing, and marking shall be as specified in the contract or order.

ANSI C78.380, C78.387, and C78.1375 are available from American National Standards Institute, Inc., 1430 Broadway, New York, NY 10018.

MILITARY INTERESTS:

User Activity

Air Force - 99

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

GSA - FSS

FSC 6240

Source: https://assist.dla.mil -- Downloaded: 202610-26T08:16Z
Check the source to verify that this is the currentversion before use.