A-A-1760
December 31, 1981

COMMERCIAL ITEM DESCRIPTION

LAMPS, METAL HALIDE (1,000 WATTS)

The General Services Administration has authorized the use of this commercial item description.

This description covers metal halide lamps of 1,000 watts for general and street lighting.

Salient characteristics:

The lamp shall operate only on ANSI specified M47 metal halide ballasts.
Although the outer bulb shall be made of heat-resistant glass, external protection of the lamp is still required to eliminate the chance of bulb breakage due to direct contact with water during lamp operation.
The lamp shall be in accordance with ANSI C78.380 and C78.387.
The lamp shall have the characteristics specified in Table I.

TABLE I

Type	ANSI Code ****	Watts	Bulb	Base	Max. Overall Length (Inches)	Finish	Average* Rated Life (hrs)	Approx. Lumens **Initial Mean*** (Vertical Pos.)	
1	M47PA-R1000/VBU	1000	BT-56	Mogul	15-3/8	Clear	10,000	105,000	83,000
2	M47PA-R1000/VBD	1000	BT-56	Mogul	15-3/8	Clear	10,000	105,000	83,000
3	M47PA-R1000/U	1000	BT-56	Mogul	15-3/8	Clear	10,000	105,000	83,000
4	M47PB-R1000/VBU	1000	BT-56	Mogul	15-3/8	Coated	10,000	100,000	79,000
5	M47PB-R1000/VBD	1000	BT-56	Mogul	15-3/8	Coated	10,000	100,000	79,000
6	M47PB-R1000/U	1000	BT-56	Mogul	15-3/8	Coated	10,000	100,000	79,000

* The average rated life is for 10 hours per start.
** Initial Lumen ratings are based upon 100-hour photometry readings at rated lamp watts.
*** Values shown are based on peration under specified test conditions with 10 or more burning hours per start on typical ballasts in use currently.
**** VBU - Means burn vertical base up to $\pm 15^{\circ}$ of vertical base up.
VBD - Means burn vertical base down to $\pm 15^{\circ}$ of vertical base down.
U - Means Universal burning positions, burn in any position.

The issues of ANSI C78.380 and C78.387 in effect on the date of the solicitation shall be used to determine compliance with these requirements.

Regulatory requirements. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. Packaging, packing, and marking shall be as specified in the contract or order.

ANSI C78.380 and C78.387 are available from American National Standards Institute Inc., 1430 Broadway, New York, NY 10018.

MILITARY INTERESTS:

User Activities

Navy - YD
Air Force - 99

CIVIL AGENCY COORDINATING ACTIVITY:

GSA - FSS

PREPARING ACTIVITY:

GSA - FSS

FSC 6240

GSA DC-01201859

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.