A-A-267A
April 23, 1982
SUPERSEDING
A-A-267
January 9, 1980

COMMERCIAL ITEM DESCRIPTION

DEODORANT, GENERAL PURPOSE (AEROSOL AIR FRESHENER)

The General Services Administration has authorized the use of this commercial item description in lieu of Federal Specification P-D-200.

This description covers an aerosol air freshener which is intended for use in indoor occupied areas such as public buildings and aircraft to counteract malodors.

Salient characteristics.

When used as directed on the container, the product shall counteract the odors from stale cigarette and cigar smoke, urine and fecal matter, vomit, food spillage, garbage, cooked foods, perspiration, pets, hospitals and nursing homes.

The product shall not contain formaldehyde.

The product shall leave a mild and pleasant odor immediately after spraying.

The product shall be packaged in an aerosol dispenser. The dispenser shall produce a spray in the form of a fine mist when moderate finger pressure is applied on the actuator. The dispenser shall stop the release of the spray immediately upon release of the pressure on the actuator. The dispenser shall deliver at least 98 percent by weight of its contents.

Delivery rate. When tested as specified in ASTM D 3069 - Delivery Rate of Aerosol Products, the dispenser shall have a delivery rate not less than 0.3 grams per second and not greater than 2.0 grams per second.

Net weight. The net weight of the contents of the aerosol dispensers shall be 14 ounces avoirdupois.

Flammability. When tested as specified in ASTM D 3065 - Flammability of Aerosol Products, the product shall meet the following requirements:

Flame Projection - 1 inch, maximum
Tag O/C Flash Point - 116°F, minimum
Closed Drum Test - 45 seconds, minimum

Seepage. When tested as specified in ASTM D 3094 - Seepage Rate of Aerosol Products, the dispensers shall have a seepage rate no greater than 3.0 mil, using wide mouth eudiometer tubes similar to that in Figure 2 of ASTM D 3094.

Container stability. The filled containers shall not leak or be damaged by internal pressure when heated to 130°F.

The issues of the ASTM test methods in effect on the date of the solicitation shall be used to determine compliance with these requirements.

Preservation, packaging, packing, labeling, and marking. Preservation, packaging, packing, labeling, and marking shall be as specified in the contract or order.

ASTM standards are available from the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.

MILITARY INTEREST:

Review Activities

Air Force - 68
DLA - GS

PREPARING ACTIVITY

GSA-FSS

FSC 6840

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:06Z
Check the source to verify that this is the current version before use.