A-A-586
October 31, 1979

COMMERCIAL ITEM DESCRIPTION

BATTERY CHARGER MOBILE, HIGH RATE, FOR 6 AND 12 VOLT BATTERIES

The General Services Administration has authorized the use of this commercial item description

This commercial item description covers all-weather, mobile, battery chargers for garage, fleet and industrial applications.

Salient characteristics:

Designed for charging both maintenance free and conventional (including dry charge activation) batteries.
Multi-position top switch or self-adjusting charging system.
Scaled ammeter.
Automatic reset circuit breaker.
Two hour timer (minimum) with hold position for continuous charging.
Full wave rectification.
Triple insulated transformer.
Copper charging cables and short-proof charging clamps.
Power cord with 3 prong plug.
Thermal overheat protected.
On-off switch.
Reverse polarity protection.
Rubber tread wheels.
Chargers shipped ready for service.
Markings, including identifying, rating, amd cautionary, shall be in accordance with UL requirements.
UL listed (conform to UL Standard 1236): the issue of UL Standard in effect on the date of solicitation shall be used to determine compliance with stated requirements.

BATTERY CHARGER SPECIFICATIONS

Discharged Battery Rating, AMPS 6/12 Volts	UL Rating, AMPS 6/12 Volts	A.C. Input at 110-120 Volts 60 Hz	Polarity Protection	Boost (Cranking) Current
A 120/80	100/60	15 Amps	Postitive	300 Amps
B 120/80	100/80	15 Amps	Indicator	300 Amps
C 75/45	60/40	11 Amps	Positive	200 Amps
D 75/45	60/40	11 Amps	Indicator	200 Amps

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing and marking. The battery chargers shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling and storage. The shipping containers shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Marking shall be as specified in the contract or order.

UL Standard 1236, is available from Underwriters' Laboratories (UL), Inc., 1285 Walt Whitman Road, Melville, Long Island, NY 11746.

FSC 6130

GSA DC-01002434

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.

Control system