A-A-602
October 31, 1979

COMMERCIAL ITEM DESCRIPTION

BATTERY CHARGER, DUAL CIRCUIT, SLOW RATE, FOR SERIES CHARGING OF 72 OR 144 VOLTS OF BATTERIES

The General Services Administration has authorized the use of this commercial item description.

This commercial item description covers wall-mounted battery chargers for personnel carrier, golf cart, motorcycle, snowmobile, lawn and garden tractor batteries.

Salient characteristics:

Two independently controlled charging circuits with ammeters for the series charging of up to 72- or 144-volt batteries.
Two multiposition tap switch or self-adjusting charging systems.
Two scaled ammeters and current overload protected.
Full wave rectification and insulated transformer.
Power cord with three-prong plug, three insulated charging cables and insulated clamp handles and an on-off switch.
Charger shipped ready for service.
Markings, including identifying, rating, and cautionary, in accordance with UL requirements.
UL listed (conform to UL Standard 1236); the issue of UL standard in effect on the date of solicitation shall be used to determine compliance with stated requirements.

Battery charger specifications

Model	DC output		Nominal AC input	
	Volts	Amps	Volts	Cycles
A	144	6	120	50/60
B	72	12	240	50/60

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards, and quality assurance practices and is the same product offered for sale in the commercial marketplace. The Government reserves the right to require proof of such conformance prior to first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

Recovered materials. The manufacturer shall utilize recovered materials to the maximum extent practicable.

Packaging, packing, and marking. The battery chargers shall be packaged in accordance with normal commercial practice and packed to assure acceptance by common carrier and provide product protection against loss and damage during multiple shipments, handling, and storage. The shipping containers shall be in compliance with the National Motor Freight Classification and Uniform Freight Classification. Marking shall be as specified in the contract or order.

UL Standard 1236 is available from Underwriters' Laboratories (UL), Inc., 1285 Walt Whitman Road, Melville, Long Island, NY 11746.

FSC 6130

GSA DC-01002449

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:09Z
Check the source to verify that this is the current version before use.