FED-STD-H28/8B
10 June 1992
SUPERSEDING
FED-STD-H28/8A
29 December 1980

FEDERAL STANDARD

SCREW-THREAD STANDARDS FOR FEDERAL SERVICES

SECTION 8

DRYSEAL PIPE THREADS

This standard was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

AMSC N/A AREA THDS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:53Z
Check the source to verify that this is the current version before use.

INFORMATION SHEET ON FEDERAL STANDARDS

This Federal Standard is issued in loose-leaf form to permit the insertion or removal of new or revised pages and sections.

All users of Federal Standards should keep them up to date by inserting revised or new pages as issued and removing superseded and canceled pages.

New and revised pages will be issued under Change Notices which will be numbered consecutively and will bear the date of issuance. Change Notices should be retained and filed in front of the Standard until such time as they are superseded by a reissue of the entire Standard.

FOREWORD

This section was developed to provide Dryseal Pipe Thread Standards for the Federal Services. It was formerly known as "Dryseal American Standard Pipe Threads". FED-STD-H28/8A was a complete revision of FED-STD-H28/8 dated 31 August 1978.

FED-STD-H28/8A was prepared by the Defense Industrial Supply Center (DLA-IS) and incorporated American National Standards for Dryseal Pipe Threads and their gages in inch units, ANSI B1.20.3-1976 and ANSI B1.20.5-1978. Changes from the previous issue included the following:

(1) NPTF Dryseal Pipe Threads cover two thread classes, with Class 1 being the same as in the previous issue and Class 2 being the same as Class 1, except that root and crest truncation inspection is required for acceptance.

(2) Added 6-step gages for checking root and crest truncation.

(3) Standard NPTF Dryseal thread step gages were modified to provide four steps identifying ranges for basic, maximum and minimum positions. This facilitates correlation with the new 6-step gages. Step gages for Dryseal SAE Short Taper Threads, NPT-SAE SHORT, and Dryseal Straight Threads, NPSF and NPSI, were modified to add a step for basic position.

(4) Deleted the position method of gaging with basic-notch gages.

(5) Added gage inspection requirements and master gage standards.

(6) Word "DRYSEAL" is no longer used in the thread designation.

FED-STD-H28/8B incorporates the American National Standard for gaging for Dryseal Pipe Threads, ASME B1.20.5-1991 which superseded ANSI B1.20.5-1978. It updates FED-STD-H28/8A dated 29 December 1980 and includes the following significant changes:

(1) Turns of engagement has been withdrawn as a standard method of gaging.

(2) Maximum width of gage thread root relief changed from 0.005 inch to the maximum product thread root width.

(3) Total cumulative tolerances on Working Ring Gages were revised.

(4) Maximum possible standoffs between conforming working ring and plug gages were revised.

(5) Added tolerances for step lengths of 4-step gages.

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:53Z
Check the source to verify that this is the current version before use.

SECTION 8 - Dryseal Pipe Threads

1. Scope. This section provides the standards for Dryseal type pipe threads and their gages. These threads feature contact at the crest and root to assure metal-to-metal contact coincident with or prior to flank contact. Contact at the crest and root prevents spiral leakage which permits joint assembly without the use of a lubricant or sealer. If not functionally objectionable, lubricants may be used to minimize the possibility of galling in assembly.

2. Referenced documents.

2.1 Government publications. The issues of the following document in effect on the date of invitation for bids or request for proposal forms a part of this standard to the extent specified herein.

Federal standards.

FED-STD-H28/1 - Nomenclature, Definitions and Letter Symbols for Screw Threads

(Activities outside the Federal Government may obtain copies of Federal specifications, standards, and commercial item descriptions as outlined under General Information in the Index of Federal Specifications, Standards, and Commercial Item Descriptions. The Index, which includes cumulative bi-monthly supplements as issued, is for sale on a subscription basis by the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.

(Single copies of this standard and other Federal specifications, standards and commercial item descriptions required by activities outside the Federal Government for bidding purposes are available from the General Services Administration Specification Section, Room 6654, 7th and D Streets, S.W., Washington, DC 20407; telephone (202) 708-9205.

(Federal Government activities may obtain copies of Federal standardization documents, and the Index of Federal Specifications, Standards, and Commercial Item Descriptions from established distribution points in their agencies.)

2.2 Other publications. The following documents form a part of this standard to the extent specified herein. Unless a specific issue is identified, the issue in effect on date of invitation for bids or request for proposal shall apply.

American National Standards.

ANSI B1.20.3-1976 - Dryseal Pipe Threads (Inch)
ASME B1.20.5-1991 - Gaging for Dryseal Pipe Threads (Inch)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:53Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Society of Mechanical Engineers, United Engineering Center, 345 East 47th Street, New York, NY 10017 or the American National Standards Institute, 11 West 42nd Street, New York, NY 10036.)

3. Definitions. The terms applicable to this standard are defined in FED-STD-H28/1 and ANSI B1.20.3-1976 Appendix A.

4. General requirements.

4.1 Thread design. Dryseal pipe threads shall be in accordance with the requirements of ANSI B1.20.3-1976.

4.2 Thread gaging. Gages and gaging for Dryseal pipe threads shall be in accordance with the requirements of ASME B1.20.5-1991.

5. Detailed requirements. Not applicable.

MILITARY INTERESTS:

Custodians:
Army - AR
Navy - AS

Review Activities:
Army - AT, ME, MI
Navy - OS

CIVIL AGENCY COORDINATING ACTIVITIES:

DOT - ACO
GSA - 7FXE
NASA - JFK, LRC

PREPARING ACTIVITY:
DLA - IS

(DoD Project THDS-0086)

Source: https://assist.dla.mil -- Downloaded: 202610-26T12:53Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 Alexandria, VA

POSTAGE WILL BE PAID BY

Defense Industrial Supply Center
ATTN: DISC-EFB
700 Robbins Ave.
Philadelphia, PA 19111-5096

Source: https://assist.dla.mil -- Downloaded: 202640-26T12:53Z
Check the source to verify that this is the currenversion before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	FED-STD-H28/8B	92-06-10

3. DOCUMENT TITLE

DRYSEAL PIPE THREADS

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON
Defense Industrial Supply Center	215-697-2735	442-2735
c. ADDRESS (Include Zip Code) ATTN: DISC-EFB 700 Robbins Avenue Philadelphia, PA 19111-5096	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 *Previous editions are obsolete.* 198/290

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:53Z
Check the source to verify that this is the current version before use.