MILITARY SPECIFICATION
DESTRUCTORS, WARHEAD, SINGLE POINT, XM13, M13, AND M14 LESS M30A1 SAFING AND ARMING DEVICE

1. SCOPE

1.1 Scope. This specification covers requirements, quality assurance provisions and the preparation for delivery criteria for three types of destructors entitled Destructors, Warhead Single Point XM13, M13 and M14 Less M30A1 Safing and Arming Device which is used in the Nike Hercules warhead section.

1.2 Classification. This specification covers destructors of the following types:

Type I - Destructor, Warhead, Single Point XM13.
Type II - Destructor, Warhead, Single Point M13.
Type III - Destructor, Warhead, Single Point M14.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-810 - Environmental Test Methods.
MIL-STD-1168 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

DRAWINGS

ORDNANCE CORPS

8795881 - Pellet and Loads.
8795882 - Pellet and Loads.
8795889 - Destructor Loading Assembly.
8795898 - Destructor Loading Assembly.
8795899 - Detonating Load Assembly.
8795901 - Destructor, Warhead, Single Point XM13.
8795902 - Destructor, Warhead, Single Point M14.
8804082 - Container, Metal, Ammunition, for Lead Assembly and Mounting Assembly for Destructor, Single Point XM13.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

8804084 - Container, Metal, Ammunition, for Lead Assembly and Mounting Assembly for Destructor, Warhead, Single Point M14.
8806540 - Carton, Packing, Ammunition, for Destructor Mounting Assembly.
8806541 - Bag, Packing, Ammunition for Destructor Lead Assembly.
EL-8815643 - Equipment Lists.
8825223 - Detonating Fuze Assembly.
8826700 - Detonating Lead Assembly.
8830310 - Destructor, Warhead, Single Point M13.
8830811 - Destructor Load Assembly.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The destructors shall comply with all requirements specified on drawing (dwg) 8795901, 8795902 or 8830310, as applicable, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 First article testing. Requirements for the submission of first article samples by the contractor shall be as specified in the contract (see 4.2).

3.4 Serialization. A serial number shall be assigned to each destructor by the procurement agency. The serial numbers shall be in addition to the normal lot numbers, but in no event shall there be any possibility of duplication, nor any indication of order or size of production in either the lot designation, the serial number, or any other number.

3.5 Environmental testing. The destructor (XM13 only) shall comply with MIL-STD-810, visual inspection and failure criteria, section 3. The destructor (XM13 only) shall also comply with 3.5.1. Testing shall be as specified in 4.4.2.

3.5.1 Container vibration (applicable to XM13 only). The container assembly shall show no evidence of damage as indicated by crack, dent, or exposure of base material and after test the destructor mounting assembly and destructor lead assembly shall show no evidence of visual damage such as cracked or broken pellet, fractured leads, or broken or cracked metal parts, when tested as specified in 4.4.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

3.6 Workmanship.

3.6.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.6.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.6.3 Burrs. Parts shall be free from burrs.

3.6.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.6.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

3.6.6 Electrical. Cable assemblies and wires shall be dressed in such a manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from burrs, sharp edges, or points. All parts shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.2.1 Quantity to be submitted. When the contract requires first article inspection, the contractor shall submit 1 complete assembly of the applicable type (see dwg 8795901, 8795902 or 8830310) for first article testing to the testing facility designated in the inviration for bids or request for proposal.

4.2.2 Inspection and testing to be performed. The first article inspection sample shall be subjected to the inspections and tests specified in Table I. Tests shall be conducted in order specified in Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table I
First article inspection and tests

Inspection or Test	Dest	Non Dest
1. Classification of characteristics (see 4.3.2.1)		X
2. Density (see 4.3.3.1)		X
3. Container vibration (see 3.5.1)		X

4.2.3 Inspection equipment. The inspection and testing specified in 4.2.2 shall be accomplished by using the gages and test equipment specified in 4.3.4.1.

4.2.4 Rejection. If any item fails to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table II and Table III), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table II
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-72	all	140-141	124	256-259	177	541-549	230
73	72	142	125	260-262	178	550-559	231
74	73	143-144	126	263-265	179	560-569	232
75	74	145	127	266-268	180	570-579	233
76	75	146-147	128	269-271	181	580-590	234
77	76	148-149	129	272-275	182	591-601	235
78	77	150	130	276-278	183	602-613	236
79	78	151-152	131	279-282	184	614-625	237
80	79	153-154	132	283-285	185	626-637	238
81-82	80	155-156	133	286-289	186	638-649	239
83	81	157	134	290-293	187	650-662	240
84	82	158-159	135	294-296	188	663-676	241
85	83	160-161	136	297-300	189	677-690	242
86	84	162-163	137	301-304	190	691-704	243
87	85	164-165	138	305-308	191	705-719	244
88-89	86	166-167	139	309-312	192	720-735	245
90	87	168	140	313-316	193	736-751	246
91	88	169-170	141	317-320	194	752-768	247
92	89	171-172	142	321-324	195	769-785	248
93	90	173-174	143	325-329	196	786-804	249
94-95	91	175-176	144	330-333	197	805-823	250
96	92	177-178	145	334-338	198	824-842	251
97	93	179-180	146	339-342	199	843-863	252
98	94	181-182	147	343-347	200	864-884	253
99-100	95	183-184	148	348-352	201	885-907	254
101	96	185-187	149	353-356	202	908-930	255
102	97	188-189	150	357-361	203	931-955	256
103	98	190-191	151	362-366	204	956-981	257
104-105	99	192-193	152	367-372	205	982-1008	258
106	100	194-195	153	373-377	206	1009-1036	259
107	101	196-197	154	378-382	207	1037-1066	260
108-109	102	198-200	155	383-388	208	1067-1098	261
110	103	201-202	156	389-393	209	1099-1131	262
111	104	203-204	157	394-399	210	1132-1166	263
112-113	105	205-207	158	400-405	211	1167-1204	264
114	106	208-209	159	406-411	212	1205-1243	265
115	107	210-212	160	412-417	213	1244-1285	266
116-117	108	213-214	161	418-424	214	1286-1330	267
118	109	215-217	162	425-430	215	1331-1378	268
119	110	218-219	163	431-437	216	1379-1429	269
120-121	111	220-222	164	438-443	217	1430-1483	270
122	112	223-224	165	444-450	218	1484-1542	271
123-124	113	225-227	166	451-457	219	1543-1605	272
125	114	228-230	167	458-465	220	1606-1673	273
126-127	115	231-232	168	466-472	221	1674-1747	274
128	116	233-235	169	473-480	222	1748-1827	275
129-130	117	236-238	170	481-488	223	1828-1914	276
131	118	239-241	171	489-496	224	1915-2010	277
132-133	119	242-243	172	497-504	225	2011-2115	278
134	120	244-246	173	505-513	226	2116-2232	279
135-136	121	247-249	174	514-521	227	2233-2361	280
137	122	250-252	175	522-530	228	over 2361	298
138-139	123	253-255	176	531-540	229		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Table III
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Pellet and leads, prior to loading (see dwgs 8795881 and 8795882 covering a detail of dwgs 8795901, 8795902 and 8830310).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Length	Gage
	102. Diameter	Gage
	103. Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.2 Detonating lead assembly (see dwg 8795899 and 8826700 covering a detail of dwg 8795901, 8795902 and 8830310).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Total length,min	Gage
	102. Location of groove	Gage
	103. Diameter of sleeve groove,min	Gage
	104. Diameter of sleeve, max	Gage
	105. Length from sleeve to end of relay cup	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

106. Length from cup to sleeve flange.....Gage
107. Identification color missing or incorrect on relay cup end of detonating fuze.....Visual
108. Detonating cord damaged.....Visual
109. Tape missing or improperly positioned.....Visual
110. Marking misleading, missing or unidentifiable.....Visual
111. Connector or nut fails to rotate freely.....Manual
112. Crimp of either sleeve missing or inadequate.....Visual/Manual
113. Any operation, missing incomplete or incorrect.....Visual/Manual
114. Any component, missing, loose or damaged.....Visual/Manual.
115. Objective evidence relating to material missing or improper (see 3.1).....Visual
116. Serialization missing or improper (see 3.4).....Visual

Minor:
201. Evidence of poor workmanship (see 3.6).....Visual

4.3.2.1.3 Destructor lead assembly, prior to applying tape (see dwg 8795898 and 8830811 covering a detail of dwg 8795901, 8830310 and 8795902).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Length from end of nut to braid	Gage
102.	Length from braid to connector	Gage
103.	Length of braid	Gage
104.	Braid damaged	Visual
105.	Any component loose, damaged or missing	Visual/Manual
106.	Threads damaged	Visual/Gage
107.	Objective evidence relating to material missing or improper (see 3.1)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Minor:

201.	Evidence of poor workmanship (see 3.6)	Visual
202.	Marking misleading or unidentifiable	Visual

4.3.2.1.4 Destructor load assembly (see dwg 8795898 and 8830811 covering a detail of dwg 8795901, 8795902 and 8830310).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Threads damaged	Visual/Gage
102.	Lead damaged	Visual
103.	Any component missing, loose or damaged	Visual
104.	Tape missing or improperly positioned	Visual
105.	Marking misleading or unidentifiable	Viaual
106.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.5 Destructor loading assembly (see dwg 8795889 covering a detail of dwg 8795901, 8795902 and 8830310).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Diameter of retaining ring, min	Gage
102.	Cup protrusion over max	Gage
103.	Diameter of holder flange,min	Gage
104.	Assembly damaged	Visual
105.	Marking misleading or unidentifiable	Visual
106.	Adhesive missing from threads joining body and holder	Visual
107.	Any component damaged or missing	Visual
108.	Any component missing or loose	Visual/Manual
109.	Evidence of looseness between destructor holder (with finger pressure)	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

110. Explosive powder or other foreign matter in receptacles or joints.....Visual/Manual
111. Objective evidence relating to material missing or improper (see 3.1).....Visual

Minor:
201. Evidence or poor workmanship (see 3.6).....Visual
202. Serialization improper or missing (see 3.4).....Visual

4.3.2.1.6 Body, prior to assembling in holder (see dwg 8795889 covering a detail of dwg 8795901, 8795902 and 8830310).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Pad missing	Visual
102.	Lead cracked or broken	Visual
103.	Objective evidence relating to material missing or improper (see 3.1)	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.7 Detonating fuze assembly (see dwg 8825223 covering a detail of dwg 8830310).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Total length, min	Gage
102.	Outside diameter at front end, max	Gage
103.	Diameter of grooves,min	Gage
104.	Location of grooves	Gage
105.	Gap between relay charge and primer cord	Radiographic/Examination
106.	Gap between primer cord and relay cup over max	Radiographic/Examination
107.	Any operation loose, damaged or missing	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

108. Any component loose, damaged or missing.....Visual
109. PETN flush with cut ends after dip.....Visual
110. Objective evidence relating to material missing or improper (see 3.1).....Visual

Minor:
201. Evidence of poor workmanship (see 3.6).....Visual

4.3.2.1.8 Destructor assembly (see dwg 8830310).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Any component loose, missing or damaged.....	Visual/Manual
102.	Any component missing, incomplete or incorrect.....	Visual
103.	Objective evidence relating to material missing or improper (see 3.1).....	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6).....	Visual

4.3.2.1.9 Bag, sealed (see dwg 8806540).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Bag torn or perforated.....	Visual
102.	Bag insecurely sealed.....	Visual
103.	Seal mislocated.....	Visual
104.	Marking misleading or unidentifiable.....	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6).....	Visaul

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.2.1.10 Carton, prior to sealing (see dwg 8806540).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Bottom flaps not secure	Visual
	102. Wrapper missing or torn	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.11 Carton sealed (see dwg 8806540).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Carton insecurely sealed	Visual
	102. Label missing	Visual
	103. Corners not blunted	Visual
	104. Marking misleading or unidentifiable	Visual
	105. Contents loose	Manual
Minor:		
	201. Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.12 Bag, prior to sealing (see dwg 8806541).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
	101. Destructor leads improperly coiled	Visual
Minor:		
	201. Evidence of poor workmanship (see 3.6)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

4.3.2.1.13 Bag, sealed (see dwg 8806541).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Bag torn or perforated	Visual
102.	Bag incorrectly sealed	Visual
103.	Seal mislocated	Visual
104.	Marking misleading or unidentifiable	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.14 Container, prior to sealing (see dwg 8804084).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Destructor loading assembly missing or damaged	Visual
102.	Destructor lead assembly missing or damaged	Visual
103.	Any packing component missing	Visual
104.	Desiccant bags torn or insufficient	Visual
105.	Packing list missing or mutilated	Visual
Minor:		
201.	Evidence of poor workmanship (see 3.6)	Visual

4.3.2.1.15 Container, sealed (see dwg 8804082).

Categories	Characteristics	Method of Inspection
Critical:	None defined.	
Major:		
101.	Container damaged	Visual
102.	Marking misleading or unidentifiable	Visual
103.	Car seal missing or damaged	Visual
104.	Contents loose	Visual
105.	Cover loose or improperly assembled	Visual/Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

Minor:
201. Evidence of poor workmanship (see 3.6).....Visual

4.3.2.1.16 Preparation for delivery (M14 only see 5).

Categories	Characteristics	Method of Inspection

Critical: None defined.

Major:
101. Preservation, packing and packaging not in accordance with applicable contract.....Visual
102. Marking not in accordance with applicable drawing.....Visual

Minor:
201. Evidence of poor workmanship (see 3.6).....Visual

4.3.3 Testing. All tests shall be performed. Tests shall be performed in the order specified below:

Test	Test Classification
a. Container vibration	Major
b. Density	Major

None of these tests are considered destructive and samples so tested may be returned to the lot.

4.3.3.1 Container vibration. One out of every 50 consecutively produced container assemblies shall be tested in accordance with 4.4.2. If any item fails to comply with 3.5.1 the 50 container assemblies from which the sample was taken shall be rejected.

4.3.3.2 Density, (see dwg 8795881 and 8795882). Sample pellets and leads shall be selected at random from each lot in accordance with Table IV. The sample shall be tested in accordance with 4.4.1. If any item fails to comply with the drawing requirements, the lot shall be rejected.

Table IV
Sample size for non-destructive testing

Lot Size	Sample Size
2-8	1
9-15	2
16-25	3
26-40	5

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

41-65	8
66-110	13
111-180	22
181-300	36
300-and over	MIL-STD-105 (AQL 0.25 percent)

4.3.4 Acceptance inspection equipment.

4.3.4.1 Major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (see EL-8815643). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. The tolerances specified herein are absolute with no allowance for test equipment inaccuracy. The tolerances used by the manufacturer shall be equal to the absolute tolerances less the accuracy tolerances of the test equipment used.

4.4.1 Density. Density values of the explosive elements shall be determined by utilizing the Bask definition of density to determine compliance with the requirement specified on the applicable drawing. The volume shall be computed from average reading of diameter and height obtained from a representative number of measurements per individual pellet or lead. The weight shall be determined by use of a balance scale. Proper dimensional and weight conversion factors shall be used to obtain the specified units of density.

4.4.2 Container vibration. The packed container assembly shall be secured to a vibration table and vibrated for 15 minutes in each of three mutually perpendicular axes through a frequency range of 10 to 55 Hertz (Hz) at a double amplitude of 0.064 inch. The frequency shall be varied uniformly from 10 to 50 to 10 Hz, making approximately one cycle per minute. After test the container and contents shall be examined to determine compliance with the requirements. Test shall be performed behind a suitable barricade.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1 Destructor XM13 and M13.

5.1.1.1 Level A. The destructors shall be packaged in accordance with dwgs 8806540 and 8806541 using the specified moisture barrier.

5.1.1.2 Level C. The destructors shall be packaged in accordance with dwgs 8806540 and 8806541 except that the moisture barrier may be omitted.

5.1.2 Destructor M14. The destructor M14 shall be packaged in accordance with applicable contract.

5.2 Packing.

5.2.1 Destructor XM13 and M13.

5.2.1.1 Level A and C. The destructors shall be packed in accordance with dwg 8804082.

5.2.2 Destructor M14.

5.2.2.1 The M14 destructor shall be packed in accordance with the applicable contract.

5.3 Marking. Marking shall be in accordance with drawings.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Type required (see 1.2).
c. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on a numbered DD Form 1664 when specified on a DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commander, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SARPA-QA-T.

6.4 Supersession data. This specification supersedes the requirements of Purchase Description PA-PD-1424 Rev. 3 dated 12 October 1962.

Custodian:
Army - PA

Preparing activity:
Army - PA

Project No. 1190-A089

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
   A. GIVE PARAGRAPH NUMBER AND WORDING.

   B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

   ☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:41Z
Check the source to verify that this is the current version before use.