MIL-D-50868A (PA)
5 February 1974
SUPERSEDING
MIL-D-50868 (MU)
5 February 1971

MILITARY SPECIFICATION

DETONATOR, FLASH, M85
PARTS AND LOADING, ASSEMBLING AND PACKING

*This Specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the inspection of the parts and the loading, assembling and packing of one type of flash detonator designated as Detonator, Flash, M85.

*2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116	- Preservation, Methods of
MIL-A-2550	- Ammunition, General Specification for

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105)

FSC: 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

MIL-STD-109 - Quality Assurance Terms and Definitions

MIL-STD-650 - Explosives: Sampling, Inspection and Testing

MIL-STD-1168 - Lot Numbering of Ammunition

MIL-STD-1235 - Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

U.S. ARMY PICATINNY ARSENAL

PRODUCT AND PACKAGING DRAWINGS

9211395 - Detonator, Flash, M85, Assembly
9258182 - Box, Set up, Packing, Ammunition Inner for Small Explosive Components
9258183 - Box, Set up, Packing, Ammunition Outer for Small Explosive Components
9258184 - Box, Packing, Ammunition for Small Explosive Components

INSPECTION EQUIPMENT DRAWINGS

8816367 - Guide, Firing Pin
8827829 - Bushing
8827934 - Ball, Steel
8867811 - Holder, Primer
9200012 - Pin, Firing
9247106 - Sleeve, Centering, Aluminum

(Copies of specifications, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer).

3. REQUIREMENTS

3.1 Material.-Materials and parts shall be in accordance with applicable drawings and specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

3.2 Detonator assembly.-The detonator assembly shall comply with all requirements specified on Drawing (dwg.) 9211395 and with all requirements specified in applicable specifications.

*3.3 Moisture content

3.3.1 Lead azide.-At the time of loading, the moisture content of the lead azide used in loading the detonators shall not exceed 0.50 percent.

*3.4 Functioning.

3.4.1 Sensitivity.-The detonator shall function on the first attempt and shall cause perforation of a .1345 inch thick lead disc, to a diameter of not less than .210 inch.

3.4.2 Waterproofness.-The detonators shall be waterproof as evidenced by normal functioning, after being immersed in water maintained at 75 degrees Fahrenheit (F.) plus or minus 5 degrees F., at a depth of 2 inches minimum, for not less than 48 hours.

3.5 Workmanship.-All parts and assemblies shall be fabricated, loaded and assembled in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, grease, rust, and other foreign matter. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

3.6 First article inspection.-This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

*4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspection set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to MIL-STD-109 to define terms used herein. The provisions of MIL-A-2550 shall apply.

4.1.1 Submission of product.-At the time the completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all the quality assurance provisions specified in this specification.
b. Drawing and specification number and date, together with identification and date of changes thereto.
c. A statement that all material purchased by the contractor meets requirements when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.
d. Number of items in the lot.
e. Date submitted.

The certificates shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

*4.2 First article inspection.

4.2.1 Submission.-Prior to the start of regular production the contractor shall submit a first article sample (see 6.1c) to a Government approved facility as designated by the contracting officer for evaluation in accordance with the provisions of 4.2.2 and 4.2.3. The first article sample shall consist of 50 complete sets of parts and sub-assemblies (i.e. 50 each of every component and sub-assembly), which have been produced by the contractor or furnished by a supplier and which have been manufactured using

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and material including packaging and packing shall be obtained from the same source of supply as will be used in regular production. Prior to submission, the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample, including a certificate of conformance for materials. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer. A first article sample, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days or whenever a change occurs in manufacturing process, material used, drawing or specification such as to significantly affect product uniformity as determined by the Government.

4.2.2 Inspections to be performed.-Components will be subjected by the Government to any or all of the examinations and tests specified in this specification and any or all requirements of the applicable drawings.

4.2.3 Rejection.-If any component fails to comply with the applicable requirements, the first article sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an inert component or sub-assembly to comply with any of the stated requirements.

4.3 *Inspection provisions*.-

4.3.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance with applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process in accordance with the same drawing, same drawing revision, same specification and same specification revision, and complies with the provisions for submission of product as specified in MIL-STD-105. Change to process, specification, or drawing not affecting safety, performance, interchangeability, or storage, as determined by the

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot of loaded detonator assemblies shall contain:

a. Parts from one lot interfix number from one manufacturer.
b. RDX from not more than one lot.
c. Lead azide of the same type from not more than two lots produced by the same manufacturer in accordance with the same specification and same specification revision and which have subsequently been subjected to uniformly controlled drying operating conditions at the loading plant.

4.3.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.3.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plan for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed, the contractor may elect to apply an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable sub-paragraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Disc, detonator (see dwg. 9215433 covering a detail of dwg. 9211395).

Categories	Defects	Method of Inspection	Code No.
Critical: None defined			

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:41Z
Check the source to verify that this is the current version before use.

Major:	AQL 0.40 percent		
101.	Diameter	Gage	01001
102.	Thickness	Gage	01002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	01003

4.3.2.2 Disc, detonator closing (see dwg. 9215434 covering a detail of dwg. 9211395).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Diameter	Gage	02001
102.	Thickness	Gage	02002
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	02003

4.3.2.3 Cup, detonator (see dwg. 9215432 covering a detail of dwg. 9211395).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 1.00 percent		
101.	Diameter of hole, min.	Gage	03001
102.	Concentricity of flash hole with outside diameter	Gage	03002
103.	Thickness through bottom	Gage	03003
104.	Length	Gage	03004
105.	Outside diameter	Gage	03005
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	03006

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:41Z
Check the source to verify that this is the current version before use.

4.3.2.4 Assembly (see dwg. 9211395).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Cup cracked or split	Visual	04001
Major:	AQL 1.00 percent		
101.	Length	Gage	04002
102.	Diameter	Gage	04003
103.	Disc loose, punctured, torn or wrinkled to such a degree that the contents are exposed	Visual	04004
104.	Color or lacquer incorrect on either end	Visual	04005
105.	Cup damaged except as described in critical above	Visual	04006
106.	Crimp not full 360 degrees	Visual	04007
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	04008

*4.3.2.5 Box, set-up, inner, after loading and prior to closing slide cover (see dwg. 9258182).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Filler and cushion assembly missing	Visual	05001
2.	Filler and cushion assembly improperly assembled	Visual	05002
3.	Stiffener missing	Visual	05003
4.	Slide cover assembled reversed	Visual	05004
Major:	AQL 0.40 percent		
101.	Release paper missing	Visual	05005

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:41Z
Check the source to verify that this is the currentversion before use.

Minor:	AQL 1.00 percent		
201.	Marking missing, incomplete or illegible	Visual	05006
202.	Evidence of poor workmanship (see 3.5)	Visual	05007

*4.3.2.6 Box, set-up, outer with inner set-up boxes assembled and prior to assembling top and sealing strip (see dwg. 9258183).

Categories	Defects	Method of Inspection	Code No.
Critical:			
1.	Red surfaces on inner set-up boxes do not alternate on same side of outer set-up box	Visual	06001
2.	Stiffener not facing one direction	Visual	06002
Major:	None defined		
Minor:	AQL 1.00 percent		
201.	Marking missing, incomplete or illegible	Visual	06003
202.	Evidence of poor workmanship (see 3.5)	Visual	06004

*4.3.2.7 Box, packing, ammunition prior to assembling cover and strapping (see dwg. 9258184).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.40 percent		
101.	Bags containing set-up boxes damaged	Visual	07001
102.	Cushioning material incomplete or missing from around outer set-up boxes	Visual	07002

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No.
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	07003

*4.3.2.8 Box, packing, ammunition (see dwg. 9258184).

Categories	Defects	Method of Inspection	Code No.
Critical:	None defined		
Major:	AQL 0.65 percent		
101.	Strapping missing, broken, loose or improperly fastened	Visual/Manual	08001
102.	Box damaged	Visual	08002
103.	Marking missing, broken or illegible	Visual	08003
Minor:	AQL 0.65 percent		
201.	Evidence of poor workmanship (see 3.5)	Visual	08004

4.3.3 Testing

4.3.3.1 Moisture content (see 3.3).-Major defect - Code No. 04009.-The moisture content of the lead azide shall be determined for each lot at the time of loading. A sample in sufficient quantity to perform the test detailed in 4.4.2 shall be selected and tested as specified in 4.4.2. If the moisture content is in excess of the percentage specified and loading has not yet begun, the lot of lead azide shall be rejected. If loading has begun, action on the unloaded lead azide shall be as specified above and all detonators loaded with the questionable lead azide shall be rejected.

4.3.3.2 Binder-lubricant content of RDX (see dwg. 9211395).-Major defect - Code No. 09001.-The binder-lubricant content of the RDX shall be determined for each lot at the time of loading. A sample, in sufficient quantity to perform the test detailed in 4.4.1, shall be selected and tested as specified in 4.4.1. If the binder-lubricant content is in excess of the percentage specified

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:41Z
Check the source to verify that this is the current version before use.

and if loading has not yet begun, the lot of RDX shall be rejected. If loading has begun, action on the unloaded RDX shall be as specified above and all detonators loaded with questionable RDX shall be rejected.

4.3.3.3 Functioning.-

4.3.3.3.1 Functioning (see 3.4.1) - Major defect - Code No. 04010.-A sample of 315 detonators shall be selected at random from each lot. If 3 or more detonators fail to comply with the requirement specified the lot shall be rejected. If one or two defects are found, a second sample of 315 shall be selected at random and tested. If, in the combined first and second sample, a total of 4 or more defects are found, the lot shall be rejected. The test shall be performed as specified in 4.4.3, using test equipment in accordance with 4.3.4.

4.3.3.3.2 Waterproofness (see 3.4.2) - Major defect - Code No. 04011.-A sample of 25 detonators shall be selected at random from each lot. If one or more detonators fail to comply with the requirement specified the lot shall be rejected. The test shall be performed as specified in 4.4.3.2, using test equipment in accordance with 4.3.4.

4.3.3.4 Heat seal test of sealed bag (see dwg. 9258183) - Major defect - Code No. 07005.-Sampling, acceptance criteria, and test procedures for this test shall be as specified in MIL-P-116.

*4.3.4 Inspection equipment.-Inspection equipment required to perform the inspection prescribed in this specification is identified in the Examination (4.3.2) and Test Method (4.4) paragraphs herein. See 6.3 for details concerning responsibilities for inspection equipment design and approval.

4.4 Test methods and procedures

4.4.1 Determination of binder-lubricant content of RDX.- The calcium resinate, graphite and total binder-lubricant content of RDX shall be determined as follows:

4.4.1.1 Calcium resinate.-An accurately weighed portion of 5 grams of the sample shall be transferred to a tared medium porosity, sintered-glass crucible. The sample shall be extracted

Source: https://assist.dla.mil -- Downloaded: 20261O-22T20:41Z
Check the source to verify that this is the current version before use.

with three 20 milliliters (ml.) portions of chloroform which have been previously saturated with RDX, maintaining each portion in contact with the residue for approximately 5 minutes before applying suction. Any lumps which may persist shall be broken up by stirring occasionally and the sides of the crucible washed down with each 20 ml. portion of chloroform to insure complete removal of the calcium resinate. The residue shall be aspirated until the odor of chloroform is no longer detectable; the crucible and contents shall be placed in an oven at 95 degrees Centrigrade (C.) plus or minus 5 degrees C. for 1/2 hour, cooled in a desiccator and weighed. The above extraction shall be repeated drying and weighing with individual 20 ml. portions of chloroform until the loss in wight on a subsequent extraction totals less than 0.003 grams. The loss in weight of the crucible plus contents shall be calculated to percent calcium resinate in the sample on a moisture free basis as follows:

$$\text{Percentage of Calcium Resinate} = \frac{100A}{W}$$

Where:
A = loss in weight of the crucible plus contents
W = weight of sample.

4.4.1.2 Graphite.-The residue remaining after the calcium resinate has been removed shall be extracted with two 20 ml. portions of dimethyl formamide, each portion maintained in contact with the residue for approximately 5 minutes with intermittent stirring before applying suction. The crucible and contents shall be washed with a minimum of 3 ml. portions of acetone, each portion maintained in contact with the residue for approximately one minute with continuous stirring before applying suction, until the following qualitative test for RDX in the acetone washings is negative. The acetone filtrate shall be transferred to a 25 ml. beaker, evaporated to dryness on a steam bath and several drops of a solution of chromotropic acid added in 36N sulfuric acid. The formation of a reddish-brown color as compared to a pink color obtained by a blank prepared in an identical manner indicates the presence of RDX. The residue shall be aspirated until the odor of acetone is no longer detectable; the crucible and contents shall be placed in a drying oven at 95 degrees C. plus or minus 5 degrees C. for 1/2 hours, cooled in a desiccator and weighed. The weight of the residue in the crucible shall be calculated to the percentage of graphite in the sample on a moisture-free basis as follows:

Source: https://assist.dla.mil -- Downloaded: 20260-22T20:41Z
Check the source to verify that this is the current version before use.

Percentage of Graphite = $\frac{100A}{W}$

Where:
A = increase in weight of filtering crucible
W = weight of sample

4.4.1.3 Total binder-lubricant.-The percentage of total binder-lubricant in the sample shall be calculated by adding the percentage of calcium resinate and graphite found.

4.4.2 Moisture content of lead azide.-The moisture content of the lead azide shall be determined in accordance with MIL-STD 650 Method 101.5 except, use a two gram sample and cover the dish with a sheet of polytetrafluoroethylene.

4.4.3 Functioning

4.4.3.1 Sensitivity.-The detonator shall be assembled to the applicable test fixture. A steel ball 1 3/16 inch in diameter and weighing 3.95 ounces, maximum, shall be dropped on the firing pin to function the M55 primer, from a height of 8 inches, maximum. The height of drop shall be measured as the height from the top of the firing pin to the bottom of the ball. A detonator that fails to fire or fails to create a hole in the lead disc of the required size shall be classed defective. Method of inspection shall be in accordance with Drawings 8816367, 8816368, 8827829, 8827934, 8867811, 9200012 and 9247106.

4.4.3.2 Waterproofness.-The detonator shall be immersed under water as specified for the time specified. Within one hour after removal from the water the detonator shall be subjected to the sensitivity test specified in 4.4.3.1. Any detonator which fails to fire or fails to create a hole in the lead disc of the required size shall be classed defective.

*5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level C.-Packaging shall be as specified on dwgs. 9258182 and 9258183.

5.2 Packing

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

5.2.1 Level C.-Packing shall be as specified on dwg. 9258184.

5.3 Marking.-Marking of all packaging and packing shall comply with dwgs. 9258182, 9258183, and 9259194.

*6. NOTES

6.1 Ordering data.-Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

c. Provisions for submission of first article samples.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. They should be cited as references on drawings of equipment designs submitted by the contractor to the Government for approval (see 6.3.3).

6.3 Inspection Equipment Designs.-Inspection equipment designs are of two types: Government Special Inspection Equipment (SIE) designs and contractor designs. SIE designs are designated by drawing numbers under the "Method of Inspection" headings in Section 4. Design responsibility for all other inspection equipment is assigned to the contractor. The contractor need not furnish any design when a complete Government SIE design is provided. Unless otherwise specified, however, the contractor may submit alternate or modified contractor designs of SIE in accordance with 6.3.2 and 6.3.3 should he elect to do so.

6.3.1 SIE designs.-SIE designs may consist of any of the following:

a. Detailed drawings which completely depict all information necessary for the fabrication and use of the item of inspection equipment.

b. A source control drawing or a specification control drawing as defined in MIL-STD-100.

c. An envelope drawing, as defined in MIL-STD-100, which establishes the criteria which a detail design shall meet.

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:41Z
Check the source to verify that this is the currentversion before use.

When envelope drawings are specified, the contractor shall prepare designs which comply with the criteria therein.

6.3.2 Contractor designs.-Contractor designs are required for all inspection equipment for which SIE designs are not specified and may include commercial equipment which the contractor proposes to use. (Commercial equipment is defined as unmodified equipment which is catalogued and available for purchase by the general public). Contractor designs shall include appropriate operating instructions, calibration procedures and maintenance procedures. Commercial equipment shall be fully described by catalog listings or other means which provide sufficient information to permit identification and evaluation by the Government and may include illustrations and engineering data. Designs shall be prepared for any special fixture(s) required to be used with commercial equipment, or with SIE designs if not otherwise covered thereby (see 6.3.1c). Designs shall be of the category and form (per MIL-D-1000) specified in the Contract Data Requirement Lists (DD Form 1423). The contractor is referred to MIL-HDBK-204, "Inspection Equipment Design" for guidance. The specification number and the applicable five-digit defect code number (or other specific identifying information) from Section 4 of this specification shall be referenced on each contractor design, together with the component or assembly drawing number and revision letter to which the specific design applies.

6.3.3 Submission of Designs for Approval.-Contractor designs shall be approved by the Government prior tc fabricating or procuring the equipment. Designs shall be submitted for approval to Commander, Picatinny Arsenal, Attn: SARPA-QA-A-M, Dover, New Jersey 07801 in accordance with the stipulations, time frame and distribution specified in the Contract Data Requirements List (DD Form 1423)

6.4 *Submission of test data and ammunition data cards.*- In addition to the normal distribution of records, for loaded items procured by the Department of the Army, one copy of all ballistic test data and ammunition data cards shall be forwarded to the following:

Commanding Officer
Picatinny Arsenal
Attn: SARPA-QA-A-M
SARPA-AD-E-P-2
Dover, New Jersey 07801

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:41Z
Check the source to verify that this is the current version before use.

6.5 Check test for possible deterioration.-The following test is designed to prevent major ammunition items being loaded with detonators that may have deteriorated. This test shall be performed on detonators from each lot which have been stored under normal conditions for more than two years, or under adverse conditions for any period of time. If the specification for the ammunition item into which the detonators are loaded does not require a check test, the contracting officer shall insert into the contract a check test performance provision. The contracting officer will arrange for the contractor to be reimbursed for expenses incurred in the performance of the deterioration check test.

6.5.1 Functioning.-A sample of 315 detonators shall be selected at random from each lot. If 4 or more detonators fail to comply with the requirement specified, the lot shall be rejected. If more than one defect is found, a second sample of 315 shall be selected at random and tested. If in the combined first and second sample a total of 5 or more defects are found, the lot shall be rejected. The test shall be performed as specified in 4.4.3 using test equipment as specified in 4.4.3.1.

6.6 The margins of the specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1375-A-077

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:41Z
Check the source to verify that this is the current version before use.